



Lubricants

AMBERGREASE EXL


HIGH PERFORMANCE BEARING GREASE

Ambergrease EXL is a premium quality extremely stable multi-complex soap thickened grease designed to provide extended re-lubrication intervals in a wider range of non arduous and arduous working conditions. Ambergrease EXL is suitable for use in all types of anti-friction, sliding surfaces and plain bearings and has exceptional load carrying capacity which promotes long component life.

It has good water resistance and anti-corrosion agents protect and extend the working life of components. Excellent EP performance provides protection against premature wear. Ambergrease EXL is a versatile lubricant with a wide temperature range.

Ford Tox. Number 196056.

PRODUCT CODES / FILL SIZES

 30304 / 400g

 31574 / 12.5kg

APPLICATIONS

Suitable for use in all types of anti-friction, sliding surfaces and plain bearings.

DIRECTIONS

- Ambergrease EXL can be applied by hand, or by using a standard grease gun (400gm cartridges available), or via a central lubricating system capable of pumping an NLGI No. 2 Grease.
- Due to the higher 'solids' content of this product, it should not be pumped through lubrication systems with pipes that are smaller than 12mm (½ inch) in diameter.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Red Soft Grease
NLGI Classification	2
Thickener	Lithium-Calcium Multi Complex
Base Fluid	Mineral Oil
Dropping Point (ASTM D2265)	>230°C
Water Washout (IP 215, ASTM D1264) @ 79°C	<2%
Dynamic Corrosion Resistance (IP 220)	0:0
Copper Corrosion (IP 112)	1a
Shell Four Ball Weld Load (IP 239)	800kgs
Mean Hertz Load	125kg
Timken OK Load (IP 236)	25kg (55lbs)
Operating Temperature Range	-30°C to 150°C

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 5 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1
Created: July 2019
Updated: October 2020

CRC Industries UK Ltd.
Wyllys Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

