# **TECHNICAL DATA**





# **CLEAR MOULD PROTECTIVE**

## TRANSPARENT CORROSION INHIBITOR

Clear Mould Protective has been specially formulated for use on clean, degreased mould surfaces tool, as a long-term protective during storage. It removes any surface moisture leaving a durable, non-greasy protective film against corrosion.

It has a clear, dry, non-staining film which will not penetrate or creep into the mould tool and will not mark or stain mouldings. It is highly recommended for clear and white polymer tools.

NSF registered for use on food/ beverage packing mould tools.



Polymer Processing



NSF Registered (No. 49688)



Just one of over 25 FG products

#### **PRODUCT CODES / FILL SIZES**



31547 / 400ml

# **APPLICATIONS**

- It can be used on all injection mould tools, blow mould tools, extrusion dies and metal components requiring corrosion protection
- The film will not harden or crack and is easily 'moulded-off' when recommencing production. Alternatively, the film can be easily removed using Ambersil Mould Cleaner or Amberklene FE10.

## **DIRECTIONS**

- Ensure that the surfaces have cooled to below 35°C to ensure optimum film formation.
- Degrease/ clean mould tool surfaces prior to application.
- Apply an even coating to all surfaces to be protected from 9" - 12" (25 - 30cm).
- Film allows subsequent handling resists acid finger marks

# **TECHNICAL DATA**



#### **TECHNICAL DATA (WITHOUT PROPELLANT)**

Appearance	Clear, colourless liquid
Protection against corrosion	TBA
Water displacing	TBA
Salt spray test	TBA
Film forming properties	A continuous, homogenous film forms after 10 minutes
Solubility	Soluble in solvents, insoluble in water
Flammability	Classified as extremely flammable under Current EC Regulations
Flashpoint	Not applicable in sealed aerosol

#### **MATERIALS COMPATIBILITY**

OK Ferrous, non-ferrous and alloy metals

CAUTION -NOT OK -

## **STORAGE & SHELF LIFE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

#### **HEALTH AND SAFETY**

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

# **MISREPRESENTATION ACT 1967**

#### **TRADE DESCRIPTIONS ACT 1968**

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.0 Created: July 2019 Updated: N/A

CRC Industries UK Ltd. Wylds Road,Bridgwater Somerset, TA6 4DD United Kingdom

Company Registered No. 04910479

t +44 (0)1278 727200

f +44 (0)1278 425644

e sales.uk@crcind.com

w www.ambersil.com

VAT No. GB 821 5195 42



