TECHNICAL DATA







Lubricants

DRY FILM ANTI-STICK

DRY PTFE LUBRICANT

Dry Film Anti-Stick spray is a specialist surface coating with excellent anti-stick and lubricating properties. It is based on a special resin bonded PTFE system which has been formulated for applications where the use of wet or silicone based products is undesirable.

PRODUCT CODES / FILL SIZES



APPLICATIONS

Forms a dry, non-staining film which makes it ideal for use in the Food, Paper, Textile and Plastics Manufacturing industries, where direct contact is involved with surfaces which would be contaminated by wet or silicone based products.

The dry lubricating film is unaffected by water, oil or solvents and offers excellent friction retardant properties. The product is also suitable for use as a mould release agent* and electrical anti-tracking agent.

* N.B. The product is completely free of silicones and will therefore allow decorative treatment (e.g. painting, plating) of any moulded parts.

DIRECTIONS

- Caution. Do not smoke during the use of this product and avoid contamination of tobacco.
- If sprayed onto hot surfaces or if coating is heated (over 230°C), ensure local exhaust ventilation is applied and avoid inhalation of fumes.
- Apply a light, even coating from 9" 12" (25 30 cm). Re-apply as necessary.
- Wash hands after use.





TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Opaque liquid
Odour	Mild Solvent
SG @ 25°C	0.89
Pressure @ 25°C	3.5 Bar
Discharge rate	1.0 - 1.1 g/sec
Temperature range	Operational from -100°C to +200°C
Solubility	Insoluble in water and most solvents
Flammability	Classified as extremely flammable under current EC Regulations
Flashpoint	Not applicable in sealed aerosol

MATERIALS COMPATIBILITY

_

OK CAUTION NOT OK

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Ltd. Wylds Road,Bridgwater Somerset, TA6 4DD United Kingdom

Company Registered No. 04910479

t +44 (0)1278 727200 f +44 (0)1278 425644 e sales.uk@crcind.com w www.ambersil.com

VAT No. GB 821 5195 42



Version 3.1 Created: July 2019 Updated: October 2020

ISO 9001 Quality Management