

Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MOULD PROTECTIVE
Bulk

1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom
Tel.: +44 1278 727200
Fax.: +44 1278 425644
E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

| | |
|---|---|
| Physical: | Flammable liquid, category 2 Highly flammable liquid and vapour. |
| Classification is based on test data. | |
| Health: | Aspiration Hazard Category 1 May be fatal if swallowed and enters airways. Skin irritation, category 2 Causes skin irritation. Eye irritation, category 2 Causes serious eye irritation. Specific target organ toxicity - single exposure, category 3 May cause drowsiness or dizziness. |
| Classification based on calculation method. | |
| Environment: | Hazardous to the aquatic environment, chronic category 2 Toxic to aquatic life with long lasting effects. |



Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)





Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

Classification based on calculation method.

Other hazards : Not classified

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

| | |
|------------------------------------|--|
| Product identifier: | Contains: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic xylene |
| Hazard pictogram(s): |     |
| Signal word: | Danger |
| Hazard statement(s): | H225 : Highly flammable liquid and vapour. H304 : May be fatal if swallowed and enters airways. H315 : Causes skin irritation. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness. H411 : Toxic to aquatic life with long lasting effects. |
| Precautionary statement(s): | P101 : If medical advice is needed, have product container or label at hand. P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 : Use only outdoors or in a well-ventilated area. P301/310 : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331 : Do NOT induce vomiting. P405 : Store locked up. P501-2 : Dispose of contents/container to an authorised waste collection point. |

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

| Hazardous ingredient | Registration number | CAS-nr. | EC-nr | w/w % | Hazard Class and Category | Hazard statement | Notes |
|---|---------------------|---------|-------------|--------|--|--|-------|
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic | 01-2119475515-33 | - | (927-510-4) | 60-100 | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2 | H225, H315, H336, H304, H411 | Q |
| xylene | 01- | 1330- | 215- | 0-1 | Flam. Liq. 3. Acute | H226, H312, H332, H315, H319, H335, H373, H304 | A, W |

Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

| | | | |
|----------------|------|-------|--|
| 21194488216-32 | 20-7 | 535-7 | Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1 |
|----------------|------|-------|--|

Explanation notes

A : substance with Community workplace exposure limit

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

W : Note: substance mentioned on the list of CMR-substances of the Dutch Ministry of Social Affairs and Employment (SZW)

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| Contact with eyes : | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| Contact with skin : | Take off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. |
| Inhalation : | Fresh air, keep warm and at rest. Seek medical attention if ill effects occur |
| Ingestion : | If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------------|--|
| Inhalation : | Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting |
| Skin contact : | Irritating to skin Symptoms : redness and pain |
| Eye contact : | Irritating to eyes Symptoms : redness and pain, impaired vision |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-------------------------|---|
| General Advice : | If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor |
|-------------------------|---|

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures



3 / 10

CRC Industries UK Limited
 Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,
 Somerset, TA6 4DD
 Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing including eye/face protection.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.
Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.
Keep out of reach of children.

Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

7.3. Specific end use(s)

Anti Corrosion Products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

| Hazardous ingredient | CAS-nr. | method | |
|---|-----------|--------|---------|
| EU established exposure limits: | | | |
| xylene | 1330-20-7 | TWA | 50 ppm |
| | | STEL | 100 ppm |
| National established exposure limits, United Kingdom | | | |
| xylene | 1330-20-7 | TWA | 50 ppm |
| | | STEL | 100 ppm |
| National established exposure limits, Ireland | | | |
| xylene | 1330-20-7 | TWA | 50 ppm |
| | | STEL | 100 ppm |

8.2. Exposure controls

| | |
|-------------------------------------|---|
| Control procedures : | Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges |
| Personal protection : | Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices. |
| inhalation : | In case of insufficient ventilation, wear suitable respiratory equipment. |
| recommended respiratory protection: | Air purifying respirator equipped with organic gas/vapor cartridge (type A) |
| hands and skin : | When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. |
| Recommended gloves: | Nitrile The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time. |
| eyes : | Wear safety eyewear according to EN 166. |
| Environmental protection: | Avoid release to the environment. Collect spillage. |



Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance : physical state : Liquid.
colour : Yellow.
odour : Solvent.
pH : Not applicable.
Boiling point/range : 94 °C
Flash point : - 4 °C
Evaporation rate : Not available.
Explosion limits : upper limit : 7 %
lower limit : 1 %
Vapour pressure : Not available.
Relative density : 0.74 g/cm³ (@ 20°C).
Solubility in water : Insoluble in water
Auto-ignition : > 200 °C
Viscosity : Not available.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂



Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|---|---|
| acute toxicity: | based on available data the classification criteria are not met |
| skin corrosion/irritation: | Causes skin irritation. |
| serious eye damage/irritation: | Causes serious eye irritation. |
| respiratory or skin sensitisation: | based on available data the classification criteria are not met |
| germ cell mutagenicity: | based on available data the classification criteria are not met |
| carcinogenicity: | based on available data the classification criteria are not met |
| toxicity for reproduction: | based on available data the classification criteria are not met |
| STOT-single exposure: | May cause drowsiness or dizziness. |
| STOT repeated exposure: | based on available data the classification criteria are not met |
| aspiration hazard: | May be fatal if swallowed and enters airways. |

Information on likely routes of exposure:

| | |
|-----------------------|--|
| Inhalation : | Inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. |
| Skin contact : | Irritating to skin |
| Eye contact : | Irritating to eyes |

Toxicological data :

| Hazardous ingredient | CAS-nr. | method | |
|---|---------|----------------|--------------|
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic | - | LD50 oral rat | > 5840 mg/kg |
| | | LC50 inhal.rat | 23.3 mg/l |
| | | LD50 derm.rat | > 2920 mg/kg |

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 2
 Toxic to aquatic life with long lasting effects.

Ecotoxicological data:

| Hazardous ingredient | CAS-nr. | method | |
|---|---------|--------------|-------------|
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic | - | IC50 algae | 10-30 mg/l |
| | | LC50 fish | > 13.4 mg/l |
| | | EC50 daphnia | 3 mg/l |

Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not discharge into drains or the environment, dispose to an authorised waste collection point.

SECTION 14: Transport information

14.1. UN number

UN-number : 3295

14.2. UN proper shipping name

Proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (heptanes, xylene)

14.3. Transport hazard class(es)

Class: 3
ADR/RID - Classification code: F1

14.4. Packing group

Packing group: II

14.5. Environmental hazards



Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN) **Creationdate :** 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

ADR/RID - Environmentally hazardous: Yes
 IMDG - Marine pollutant: Marine pollutant
 IATA/ICAO - Environmentally hazardous: Yes

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D/E)
 IMDG - Ems: F-E, S-D
 IATA/ICAO - PAX: 353
 IATA/ICAO - CAO: 364

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
 Regulation (EC) No 1907/2006 (REACH)
 Regulation (EC) No 1272/2008 (CLP)

| European data | |
|-------------------------|--|
| Wassergefährdungsklasse | class 1 (self classification, Germany) |
| Wassergefährdungsklasse | class 1 (self classification, Germany) |
| Wassergefährdungsklasse | class 1 (self classification, Germany) |
| Wassergefährdungsklasse | class 1 (self classification, Germany) |

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H225 : Highly flammable liquid and vapour.
 H226 : Flammable liquid and vapour.
 H304 : May be fatal if swallowed and enters airways.
 H312 : Harmful in contact with skin.
 H315 : Causes skin irritation.
 H319 : Causes serious eye irritation.
 H332 : Harmful if inhaled.
 H335 : May cause respiratory irritation.
 H336 : May cause drowsiness or dizziness.
 H373 : May cause damage to organs through prolonged or repeated exposure
 .
 H411 : Toxic to aquatic life with long lasting effects.
 acronyms and synonyms: TWA = time weight average

Productname : MOULD PROTECTIVE
Ref.Nr.: UDS000677_3_20200207 (EN)

Creationdate : 07.02.20 Version : 2.2
Replaces: UDS000677_20181102

STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.