



Lubricants



High Temperature Resistant

AMBERGREASE SIL

PURE SILICONE GREASE

Ambergrease SIL is a high quality, pure silicone grease which is water repellent and non-melting, prevents moisture ingress. As an anti-tracking, anti-arcing coating, it will protect electrical systems. It can also be used as a multipurpose lubricating agent. It has many uses in electrical and chemical industries.

It is insoluble in water, alcohol, diluted acids and alkalis, taste free, odourless and non-toxic. Withstands marine environments.

PRODUCT CODES / FILL SIZES



31888 / 100g



31887 / 1Ltr

APPLICATIONS

Electrical servicing:

- Anti-tracking, anti-corona discharge coating
- Waterproofing all types of electric systems
- Protection of switch gear, distributors
- Easing cables into conduits

Lubrication of:

- Instruments subjected to high or low temperatures
- Centrifuge and autoclave lid seals
- Cold room trolley castors
- Conditioning devices
- Conveyor chains
- Glass and ceramic stop-cocks and glands

O-ring and rubber seal assembly:

- Pneumatic, automotive and compressed air systems
- Plastic plumbing systems

Moulding:

- Shell moulding - for the pre-treatment of pattern plates
- Ingot moulding for brass, aluminium and silver

Typical Industries:

- | | |
|--------------------------|--------------------------|
| • Automotive | • Iron and steel |
| • Mechanical engineering | • Dock yards |
| • Workshops | • Agricultural machinery |
| • Civil engineering | • Heavy engineering |
| • Mining | • Offshore |

DIRECTIONS

- Apply straight from container and spread to cover required area.
- Can be applied by brush if desired.

TECHNICAL DATA (WITHOUT PROPELLANT)

Physical appearance	Smooth, translucent grease
Colour	Colourless
Odour	Odourless
Grade (NLGI)	2
Penetration (unworked)	200 - 260 mm/10
Penetration (worked)	280 maximum
Dielectric strength (IEC 243-1)	15.4 kV/mm
Volume resistivity (IEC3)	1.4×10^{15} ohm.mm
Dielectric loss	0.0018 at 1 kHz
TEC250	0.0022 at 1 MHz
Resistance to corrosion - EMCOR (IP220)	0:0
Water washout @38°C - (ASTM D 1264)	2% maximum
Operating temperature range	-40°C to +200°C (220°C intermittently)
Flash point	>300°C

MATERIALS COMPATIBILITY

OK	No effects on rubber, plastic and metals
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 3 years with correct storage.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1
Created: July 2019
Updated: October 2020

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

