



Safety Data Sheet

Copyright, 2019, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-3707-4	Version number:	7.00
Revision date:	16/01/2019	Supersedes date:	18/09/2017
Transportation version number:	5.00 (18/02/2019)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Aerospace Sealant AC-380 B-1/2

Product Identification Numbers

70-0052-0641-5

7000123265

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

30-3155-6, 30-3406-3

TRANSPORTATION INFORMATION

KIT LABEL

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Reproductive Toxicity, Category 1A - Repr. 1A; H360
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Contains:

Manganese dioxide; Lead

HAZARD STATEMENTS:

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P260B	Do not breathe dust.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H360D May damage the unborn child.

<=125 ml Precautionary statements

Prevention:

P201 Obtain special instructions before use.
P280E Wear protective gloves.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:

EUH208 Contains 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer. May produce an allergic reaction.

Supplemental Precautionary Statements:

Restricted to professional users.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Kit Information: CLP Target Organ Hazard Statement information was added.

Kit: Component document group number(s) information was modified.

Label: CLP Ingredients - kit components information was added.

Section 1: Product identification numbers information was modified.

Section 01: SAP Material Numbers information was modified.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Prevention information was modified.



Safety Data Sheet

Supplied by:
Sil-Mid Limited
Roman Park, Roman Way
Coleshill, West Midlands
B46 1HG. UK
T: 01675 432850
E: info@silmid.com

Emergency Telephone No. +44 (0)1675 432850
(Monday to Friday, 08:00 – 17:30 – GMT)

Copyright, 2017, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-3406-3	Version number:	6.00
Revision date:	15/09/2017	Supersedes date:	30/08/2017
Transportation version number:	1.00 (09/08/2013)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Aerospace Sealant AC-380 B-1/2 and B-2 Base

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

HAZARD STATEMENTS:

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

3M™ Aerospace Sealant AC-380 B-1/2 and B-2 Base**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**<=125 ml Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

No precautionary statements are required for containers <=125 mL.

SUPPLEMENTAL INFORMATION**Supplemental Hazard Statements:**

EUH208 Contains 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer. May produce an allergic reaction.

Contains 68% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	68611-50-7			70 - 80	Substance not classified as hazardous
Calcium Carbonate	471-34-1	207-439-9		15 - 20	Substance with a Community level exposure limit in the workplace
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7			5 - 10	Aquatic Chronic 2, H411
Titanium dioxide	13463-67-7	236-675-5	01-2119489379-17	1 - 2	Substance with a Community level exposure limit in the workplace
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8			< 0.5	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317
2-methylbutane	78-78-4	201-142-8		< 0.2	Flam. Liq. 1, H224; Asp. Tox. 1, H304; STOT SE 3, H336; EUH066; Aquatic Chronic 2, H411

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Titanium dioxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m3;TWA(respirable):4 mg/m ³	
Limestone	471-34-1	UK HSC	TWA(as inhalable dust):10 mg/m3;TWA(as respirable dust):4 mg/m3;TWA(Inhalable):10 mg/m3;TWA(respirable):4 mg/m ³	
2-methylbutane	78-78-4	UK HSC	TWA:1800 mg/m ³ (600 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure

Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) are recommended: Nitrile rubber.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Appearance/Odour	Sulphurous odour; White paste
Odour threshold	No data available.
pH	No data available.

Boiling point/boiling range	<i>Not applicable.</i>
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	≥93.3 °C [<i>Test Method: Closed Cup</i>]
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative density	1.1 [<i>Ref Std: WATER=1</i>]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>Not applicable.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	1.1 g/ml

9.2. Other information

EU Volatile Organic Compounds *No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Reducing agents.

Strong acids.

Strong bases.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from

3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

No known health effects.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Dermal	Rat	LD50 > 7,800 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Dermal	Rat	LD50 > 7,800 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	Rat	LD50 > 1,600 mg/kg
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
2-methylbutane	Dermal	Rabbit	LD50 3,000 mg/kg
2-methylbutane	Inhalation-Vapour (4 hours)	Rat	LC50 > 18 mg/l
2-methylbutane	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

3M™ Aerospace Sealant AC-380 B-1/2 and B-2 Base**Skin Corrosion/Irritation**

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Rabbit	No significant irritation
Calcium Carbonate	Rabbit	No significant irritation
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Rabbit	Mild irritant
2-methylbutane	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Rabbit	No significant irritation
Calcium Carbonate	Rabbit	No significant irritation
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Rabbit	Moderate irritant
2-methylbutane	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced		Not classified
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)		Not classified
Titanium dioxide	Human and animal	Not classified
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Human and animal	Sensitising
2-methylbutane	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	In vivo	Not mutagenic
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-methylbutane	In vivo	Not mutagenic
2-methylbutane	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

3M™ Aerospace Sealant AC-380 B-1/2 and B-2 Base

2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
--	--------	-------	--

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	pre mating & during gestation
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
2-methylbutane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
2-methylbutane	Inhalation	Not classified for development	Rat	NOAEL 30 mg/l	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
2-methylbutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
2-methylbutane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
2-methylbutane	Inhalation	cardiac sensitisation	Not classified	Dog	NOAEL Not available	not available
2-methylbutane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	Ingestion	auditory system heart endocrine system hematopoietic	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

3M™ Aerospace Sealant AC-380 B-1/2 and B-2 Base

		system liver eyes kidney and/or bladder				
2-methylbutane	Inhalation	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
2-methylbutane	Inhalation	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 20 mg/l	13 weeks
2-methylbutane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

Aspiration Hazard

Name	Value
2-methylbutane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	68611-50-7		Data not available or insufficient for classification			
Calcium Carbonate	471-34-1	Western Mosquitofish	Experimental	96 hours	LC50	>100 mg/l
Calcium Carbonate	471-34-1	Rainbow trout	Experimental	42 days	NOEC	>100 mg/l
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7	Water flea	Experimental	48 hours	EC50	4.71 mg/l
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and	68611-50-7	Green algae	Experimental	72 hours	EC50	17 mg/l

3M™ Aerospace Sealant AC-380 B-1/2 and B-2 Base

sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)						
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8		Data not available or insufficient for classification			
2-methylbutane	78-78-4		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	68611-50-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Estimated Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)
2-methylbutane	78-78-4	Experimental Biodegradation	28 days	BOD	71.43 % BOD/ThBOD	Other methods
2-methylbutane	78-78-4	Experimental Photolysis		Photolytic half-life (in air)	8.11 days (t 1/2)	Other methods

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	68611-50-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods

3M™ Aerospace Sealant AC-380 B-1/2 and B-2 Base

2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer	25085-99-8	Estimated BCF-Carp	28 days	Bioaccumulation factor	<= 42	Other methods
2-methylbutane	78-78-4	Experimental Bioconcentration		Log Kow	2.3	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

ADR/IMDG/IATA: Not restricted for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

Titanium dioxide

CAS Nbr

13463-67-7

Classification

Grp. 2B: Possible human carc.

Regulation

International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The

components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 5: Fire - Advice for fire fighters information information was modified.

Section 5: Hazardous combustion products table information was modified.

Section 08: Skin protection - incidental contact text information was added.

Section 08: Skin protection - incidental contact information was added.

Section 13: Standard Phrase Category Waste GHS information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Supplied by:
Sil-Mid Limited
Roman Park, Roman Way
Coleshill, West Midlands
B46 1HG, UK
T: 01675 432850
E: info@silmid.com

Emergency Telephone No. +44 (0)1675 432850
(Monday to Friday, 08:00 – 17:30 – GMT)

Copyright, 2019, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-3155-6	Version number:	9.00
Revision date:	10/12/2019	Supersedes date:	19/02/2018
Transportation version number:	1.00 (19/09/2013)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Aerospace Sealant AC-380 B-1/2 Catalyst

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Hardener

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Reproductive Toxicity, Category 1A - Repr. 1A; H360
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS07 (Exclamation mark) | GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
manganese dioxide	1313-13-9	215-202-6	30 - 45
lead powder	7439-92-1	231-100-4	< 0.1

HAZARD STATEMENTS:

H302	Harmful if swallowed.	
H319	Causes serious eye irritation.	
H315	Causes skin irritation.	
H360D	May damage the unborn child.	
H373	May cause damage to organs through prolonged or repeated exposure:	nervous system
H410	Very toxic to aquatic life with long lasting effects.	

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P260B	Do not breathe dust.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H360D	May damage the unborn child.
-------	------------------------------

<=125 ml Precautionary statements

Prevention:

3M Aerospace Sealant AC-380 B-1/2 Catalyst

P201 Obtain special instructions before use.
P280E Wear protective gloves.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:**Supplemental Precautionary Statements:**

Restricted to professional users.

13% of the mixture consists of components of unknown acute oral toxicity.

Contains 13% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Contains a substance that meets the criteria for vPvB according to Regulation (EC) No 1907/2006, Annex XIII

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
manganese dioxide	1313-13-9	215-202-6	01-2119452801-43	30 - 45	Acute Tox. 4, H332; Acute Tox. 4, H302 EUH031; STOT RE 2, H373
Terphenyl, hydrogenated	61788-32-7	262-967-7	01-2119488183-33	30 - 45	Aquatic Chronic 2, H411
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	273-316-1		0 - 10	Substance not classified as hazardous
Natural Amorphous compounds	Trade Secret			0 - 5	Substance not classified as hazardous
Water	7732-18-5	231-791-2		0.5 - 5	Substance not classified as hazardous
Terphenyl	26140-60-3	247-477-3		< 5	Aquatic Acute 1, H400,M=10; Aquatic Chronic 1, H410,M=10
Bis(piperidinothiocarbonyl) hexasulphide	971-15-3	213-537-2		1 - 3	Substance not classified as hazardous
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.- (NONYLPHENYL)-.OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	68412-53-3			0.1 - 1	Skin Irrit. 2, H315; Eye Dam. 1, H318
Quartz	14808-60-7	238-878-4		< 1	STOT RE 1, H372
sodium hydroxide	1310-73-2	215-185-5		0.1 - 1	Skin Corr. 1A, H314 Met. Corr. 1, H290
ferbam (ISO)	14484-64-1	238-484-2		<= 0.5	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Acute 1, H400,M=10; Aquatic Chronic 1, H410,M=100

3M Aerospace Sealant AC-380 B-1/2 Catalyst

lead powder	7439-92-1	231-100-4		< 0.1	Acute Tox. 2, H330 Repr. 1A, H360FD; Lact., H362 STOT SE 2, H371; STOT RE 2, H373; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=10
-------------	-----------	-----------	--	-------	--

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Hydrocarbons.
Carbon monoxide
Carbon dioxide.
Oxides of nitrogen.
Oxides of Lead
Oxides of sulphur.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Avoid contact during pregnancy/while nursing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
sodium hydroxide	1310-73-2	UK HSC	STEL:2 mg/m ³	
Manganese, inorganic compounds	1313-13-9	UK HSC	TWA(as Mn):0.5 mg/m ³ ;TWA(as Mn, respirable fraction):0.05 mg/m ³	
Quartz	14808-60-7	UK HSC	TWA(respirable):0.1 mg/m ³	
Terphenyl	26140-60-3	UK HSC	STEL:4.8 mg/m ³ (0.5 ppm)	
Terphenyl, hydrogenated	61788-32-7	UK HSC	TWA:19 mg/m ³ (2	

3M Aerospace Sealant AC-380 B-1/2 Catalyst

lead powder 7439-92-1 UK HSC ppm);STEL:48 mg/m³(5 ppm)
 UK HSC : UK Health and Safety Commission TWA(as Pb):0.15 mg/m³
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
Terphenyl, hydrogenated		Worker	Dermal, Long-term exposure (8 hours), Local effects	0.2 mg/cm ²
Terphenyl, hydrogenated		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	46.3 mg/kg bw/d
Terphenyl, hydrogenated		Worker	Inhalation, Long-term exposure (8 hours), Local effects	83.8 mg/m ³
Terphenyl, hydrogenated		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	8.38 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
Terphenyl, hydrogenated		Agricultural soil	12.6 mg/kg d.w.
Terphenyl, hydrogenated		Concentration in freshwater fish for secondary poisoning	2.22 mg/kg w.w.
Terphenyl, hydrogenated		Freshwater sediments	63.2 mg/kg d.w.
Terphenyl, hydrogenated		Intermittent releases to water	13.4 mg/l
Terphenyl, hydrogenated		Marine water sediments	6.32 mg/kg d.w.
Terphenyl, hydrogenated		Sewage Treatment Plant	10.3 mg/l

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	> 8 hours
Neoprene.	0.5	> 8 hours
Nitrile rubber.	0.35	> 8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid.

Colour

Dark Brown

Odor

Slight Odor

Odour threshold

No data available.

pH

Not applicable.

Boiling point/boiling range

No data available.

Melting point

Not applicable.

Flammability (solid, gas)

Not applicable.

Explosive properties

Not classified

Oxidising properties

Not classified

Flash point

> 110 °C [*Test Method: Closed Cup*]

Autoignition temperature

No data available.

Flammable Limits(LEL)

None detected

3M Aerospace Sealant AC-380 B-1/2 Catalyst

Flammable Limits(UEL)	None detected
Relative density	≥ 1.58 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	Not applicable.
Evaporation rate	Nil
Vapour density	≥ 1
Decomposition temperature	No data available.
Viscosity	No data available.
Density	1.58 g/ml

9.2. Other information

EU Volatile Organic Compounds	No data available.
Percent volatile	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Reducing agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

3M Aerospace Sealant AC-380 B-1/2 Catalyst

and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which may interfere with lactation or be harmful to breastfed children.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
manganese dioxide	Dermal	Rat	LD50 2,000 mg/kg
manganese dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
manganese dioxide	Ingestion	Rat	LD50 > 2,197 mg/kg
Terphenyl, hydrogenated	Dermal	Rabbit	LD50 6,800 mg/kg
Terphenyl, hydrogenated	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 11.1 mg/l
Terphenyl, hydrogenated	Ingestion	Rat	LD50 > 10,000 mg/kg
Terphenyl	Dermal	Rabbit	LD50 > 5,000 mg/kg
Terphenyl	Inhalation-Dust/Mist (4 hours)	Rat	LD50 > 3.8 mg/l
Terphenyl	Ingestion	Rat	LD50 2,304 mg/kg
Bis(piperidinethiocarbonyl) hexasulphide	Ingestion	Rat	LD50 > 5,000 mg/kg
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(NONYLPHENYL)-.OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	Ingestion	Rat	LD50 4,450
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
ferbam (ISO)	Dermal	Rabbit	LD50 > 4,000 mg/kg
ferbam (ISO)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.4 mg/l
ferbam (ISO)	Ingestion	Rat	LD50 1,130 mg/kg

3M Aerospace Sealant AC-380 B-1/2 Catalyst

lead powder	Dermal	LD50 estimated to be 2,000 - 5,000 mg/kg
-------------	--------	--

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
manganese dioxide	Rabbit	No significant irritation
Terphenyl, hydrogenated	Rabbit	No significant irritation
Terphenyl	Rabbit	No significant irritation
sodium hydroxide	Rabbit	Corrosive
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(NONYLPHENYL)-OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	Rabbit	Irritant
Quartz	Professional judgement	No significant irritation
ferbam (ISO)	Rabbit	No significant irritation
lead powder	similar compounds	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
manganese dioxide	Rabbit	Mild irritant
Terphenyl, hydrogenated	Rabbit	No significant irritation
Terphenyl	Rabbit	No significant irritation
sodium hydroxide	Rabbit	Corrosive
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(NONYLPHENYL)-OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	Rabbit	Corrosive
ferbam (ISO)	Rabbit	Severe irritant
lead powder	similar compounds	Mild irritant

Skin Sensitisation

Name	Species	Value
manganese dioxide	Mouse	Not classified
Terphenyl, hydrogenated	Human	Not classified
sodium hydroxide	Human	Not classified
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(NONYLPHENYL)-OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	Human	Not classified
ferbam (ISO)	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
manganese dioxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
manganese dioxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Terphenyl, hydrogenated	In vivo	Not mutagenic
Terphenyl	In Vitro	Not mutagenic
Terphenyl	In vivo	Not mutagenic
Bis(piperidinothiocarbonyl) hexasulphide	In Vitro	Not mutagenic
sodium hydroxide	In Vitro	Not mutagenic
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(NONYLPHENYL)-OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	In Vitro	Not mutagenic

3M Aerospace Sealant AC-380 B-1/2 Catalyst

Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
lead powder	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Quartz	Inhalation	Human and animal	Carcinogenic.
ferbam (ISO)	Ingestion	Rat	Not carcinogenic
lead powder	Not specified.	official classification	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
manganese dioxide	Inhalation	Not classified for female reproduction	Rat	NOAEL 20 mg/m3	2 generation
manganese dioxide	Inhalation	Not classified for male reproduction	Rabbit	LOAEL 250 mg/kg	1 days
manganese dioxide	Ingestion	Not classified for development	Rat	LOAEL 354 mg/kg/day	pre mating into lactation
manganese dioxide	Inhalation	Not classified for development	Rat	LOAEL 61 mg/m3	gestation into lactation
Terphenyl, hydrogenated	Ingestion	Not classified for female reproduction	Rat	NOAEL 81 mg/kg/day	2 generation
Terphenyl, hydrogenated	Ingestion	Not classified for male reproduction	Rat	NOAEL 62 mg/kg/day	2 generation
Terphenyl, hydrogenated	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	2 generation
ferbam (ISO)	Ingestion	Not classified for female reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
ferbam (ISO)	Ingestion	Not classified for male reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
ferbam (ISO)	Ingestion	Not classified for development	Rat	NOAEL 11 mg/kg/day	during organogenesis
lead powder	Not specified.	Toxic to female reproduction	Human	LOAEL 10 ug/dl blood	
lead powder	Not specified.	Toxic to male reproduction	Human	LOAEL 37 ug/dl blood	
lead powder	Not specified.	Toxic to development	Human	NOAEL Not available	

Lactation

Name	Route	Species	Value
ferbam (ISO)	Ingestion	Rat	Causes effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
sodium hydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
lead powder	Ingestion	nervous system	May cause damage to organs	Human	LOAEL 90 ug/dl blood	poisoning and/or abuse
lead powder	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning

3M Aerospace Sealant AC-380 B-1/2 Catalyst

					available	and/or abuse
--	--	--	--	--	-----------	--------------

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
manganese dioxide	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Monkey	LOAEL 1.1 mg/m ³	10 months
manganese dioxide	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Terphenyl, hydrogenated	Inhalation	liver	Not classified	Rat	NOAEL 0.5 mg/l	90 days
Terphenyl, hydrogenated	Ingestion	endocrine system blood liver kidney and/or bladder	Not classified	Rat	NOAEL 144 mg/kg/day	14 weeks
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
lead powder	Inhalation	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	occupational exposure
lead powder	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 50 ug/dl blood	occupational exposure
lead powder	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	occupational exposure
lead powder	Inhalation	gastrointestinal tract	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
lead powder	Inhalation	heart endocrine system immune system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
lead powder	Ingestion	bone, teeth, nails, and/or hair	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 20 ug/dl blood	3 months
lead powder	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.5 mg/kg/day	20 days
lead powder	Ingestion	hematopoietic system kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	environmental exposure
lead powder	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 11 ug/dl blood	environmental exposure
lead powder	Ingestion	auditory system heart endocrine system vascular system	Not classified	Human	NOAEL Not available	environmental exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

3M Aerospace Sealant AC-380 B-1/2 Catalyst

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Terphenyl, hydrogenated	61788-32-7		Data not available or insufficient for classification			
manganese dioxide	1313-13-9	Rainbow trout	Endpoint not reached	96 hours	LC50	>100 mg/l
manganese dioxide	1313-13-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
manganese dioxide	1313-13-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
manganese dioxide	1313-13-9	Green algae	Experimental	72 hours	Effect Concentration 10%	>100 mg/l
manganese dioxide	1313-13-9	Water flea	Experimental	8 days	NOEC	>100 mg/l
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1		Data not available or insufficient for classification			
Terphenyl	26140-60-3	Water flea	Estimated	48 hours	EC50	0.022 mg/l
Terphenyl	26140-60-3	Green Algae	Experimental	72 hours	EC50	0.102 mg/l
Terphenyl	26140-60-3	Rainbow trout	Experimental	96 hours	LC50	27 mg/l
Terphenyl	26140-60-3	Fathead minnow	Experimental	34 days	NOEC	0.064 mg/l
Terphenyl	26140-60-3	Green Algae	Experimental	72 hours	NOEC	0.003 mg/l
Terphenyl	26140-60-3	Water flea	Experimental	21 days	NOEC	0.005 mg/l
Bis(piperidinothiocarbonyl) hexasulphide	971-15-3	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Bis(piperidinothiocarbonyl) hexasulphide	971-15-3	Green Algae	Experimental	72 hours	Effect Concentration 10%	>100 mg/l
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.- (NONYLPHENYL)-O MEGA.-HYDROXY-, BRANCHED, PHOSPHATES	68412-53-3		Data not available or insufficient for classification			
Quartz	14808-60-7	Green Algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz	14808-60-7	Green Algae	Estimated	72 hours	NOEC	60 mg/l
sodium hydroxide	1310-73-2		Data not available or insufficient for classification			
ferbam (ISO)	14484-64-1	Green Algae	Experimental	96 hours	EC50	2.4 mg/l
ferbam (ISO)	14484-64-1	Guppy	Experimental	96 hours	LC50	0.09 mg/l
ferbam (ISO)	14484-64-1	Water flea	Experimental	48 hours	LC50	0.09 mg/l
ferbam (ISO)	14484-64-1	Rainbow trout	Experimental	60 days	NOEC	0.00056 mg/l
lead powder	7439-92-1	Green Algae	Estimated	72 hours	EC50	0.0205 mg/l
lead powder	7439-92-1	Water flea	Estimated	48 hours	LC50	0.026 mg/l

3M Aerospace Sealant AC-380 B-1/2 Catalyst

lead powder	7439-92-1	Fathead minnow	Experimental	96 hours	LC50	0.0408 mg/l
lead powder	7439-92-1		Estimated	30 days	Effect Concentration 10%	0.0017 mg/l
lead powder	7439-92-1	Green Algae	Estimated	72 hours	Effect Concentration 10%	0.0061 mg/l
lead powder	7439-92-1	Rainbow trout	Experimental	578 days	NOEC	0.003 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Terphenyl, hydrogenated	61788-32-7	Experimental Biodegradation	28 days	CO2 evolution	1 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
manganese dioxide	1313-13-9	Data not availbl-insufficient			N/A	
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	Data not availbl-insufficient			N/A	
Terphenyl	26140-60-3	Experimental Biodegradation	14 days	BOD	0.5 % BOD/ThBOD	OECD 301C - MITI test (I)
Bis(piperidinothiocarbonyl) hexasulphide	971-15-3	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301F - Manometric respirometry
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.- (NONYLPHENYL)-.OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	68412-53-3	Data not availbl-insufficient			N/A	
Quartz	14808-60-7	Data not availbl-insufficient			N/A	
sodium hydroxide	1310-73-2	Data not availbl-insufficient			N/A	
ferbam (ISO)	14484-64-1	Experimental Hydrolysis		Hydrolytic half-life	≤31 minutes (t 1/2)	
ferbam (ISO)	14484-64-1	Estimated Biodegradation	14 days	BOD	0 % weight	OECD 301C - MITI test (I)
lead powder	7439-92-1	Data not availbl-insufficient			N/A	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Terphenyl, hydrogenated	61788-32-7	Estimated BCF - Bluegill	42 days	Bioaccumulation factor	5200	Other methods
manganese dioxide	1313-13-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Terphenyl	26140-60-3	Estimated BCF- Carp	60 days	Bioaccumulation factor	2300	OECD 305E - Bioaccumulation flow-through fish test
Bis(piperidinothiocarbonyl) hexasulphide	971-15-3	Estimated Bioconcentration		Bioaccumulation factor	2.8	Estimated: Bioconcentration factor
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.- (NONYLPHENYL)-.OMEGA.-HYDROXY-, BRANCHED, PHOSPHATES	68412-53-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for	N/A	N/A	N/A	N/A

3M Aerospace Sealant AC-380 B-1/2 Catalyst

		classification				
sodium hydroxide	1310-73-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ferbam (ISO)	14484-64-1	Experimental Bioconcentration		Log Kow	-1.6	Other methods
lead powder	7439-92-1	Experimental BCF - Other	days	Bioaccumulation factor	1322	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

Ingredient	CAS Nbr	PBT/vPvB status
Terphenyl, hydrogenated	61788-32-7	Meets REACH PBT criteria
Terphenyl, hydrogenated	61788-32-7	Meets REACH PBT criteria

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Exemption: For vessels containing a net quantity of 5 l or a net mass of 5 kg or less per single or inner packaging , special provision 375 (ADR), exemption per 2.10.2.7 (IMDG) or special provision A197 (IATA) may be applied, if applicable ADR: UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (FERBAM, TERPHENYL); 9; III; (-); M6.

IMDG: UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (FERBAM, TERPHENYL); 9; III; FA, SF.

IATA: UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (FERBAM, TERPHENYL); 9; III.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

3M Aerospace Sealant AC-380 B-1/2 Catalyst

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
ferbam (ISO)	14484-64-1	Gr. 3: Not classifiable	International Agency for Research on Cancer
lead powder	7439-92-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Quartz	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
lead powder	7439-92-1

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Authorization status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

<u>Ingredient</u>	<u>CAS Nbr</u>
Terphenyl, hydrogenated	61788-32-7
lead powder	7439-92-1

Authorization status: listed in the Candidate List of Substances of Very High Concern for Authorization

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH031	Contact with acid liberates toxic gas.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H362	May cause harm to breast-fed children.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Industrial Use of Adhesives and Sealants: Section 16: Annex information was added.
 CLP: Ingredient table information was modified.
 Section 2: Other hazards phrase information was modified.
 Section 3: Composition/ Information of ingredients table information was modified.
 Section 5: Hazardous combustion products table information was modified.
 Section 8: 8.2. Exposure controls information information was added.
 Section 8: 8.2.3. Environmental exposure controls information information was added.
 Section 8: DNEL table row information was added.
 Section 8: Occupational exposure limit table information was modified.
 Section 8: PNEC table row information was added.
 Section 09: Color information was added.
 Section 09: Odor information was added.
 Sections 3 and 9: Odour, colour, grade information information was deleted.
 Section 11: Acute Toxicity table information was modified.
 Section 11: Carcinogenicity Table information was modified.
 Section 11: Germ Cell Mutagenicity Table information was modified.
 Lactation Table information was modified.
 Section 11: Reproductive and/or Developmental Effects text information was deleted.
 Section 11: Reproductive Toxicity Table information was modified.
 Section 11: Serious Eye Damage/Irritation Table information was modified.
 Section 11: Skin Corrosion/Irritation Table information was modified.
 Section 11: Skin Sensitization Table information was modified.
 Section 11: Target Organs - Repeated Table information was modified.
 Section 11: Target Organs - Single Table information was modified.
 Section 12: Component ecotoxicity information information was modified.
 Section 12: No PBT/vPvB information available warning information was deleted.
 Section 12: PBT/vPvB table row information was added.
 Section 12: Persistence and Degradability information information was modified.
 Section 12: Biocumulative potential information information was modified.
 Section 13: 13.1. Waste disposal note information was modified.
 Section 14: Transportation classification information was modified.
 Section 15: Authorization status under REACH: SVHC Authorization ingredient information information was added.
 Section 15: Carcinogenicity information information was modified.
 Section 15: Chemical Safety Assessment information was modified.
 Section 15: Regulations - Inventories information was deleted.
 Section 15: Restrictions on manufacture ingredients information information was added.
 Annex: Prediction of exposure statement information was added.
 Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material.
 information was modified.
 Sectio 16: UK disclaimer information was deleted.

Annex

1. Title	
Substance identification	Terphenyl, hydrogenated; EC No. 262-967-7; CAS Nbr 61788-32-7;
Exposure Scenario Name	Industrial Use of Adhesives and Sealants
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 05 -Mixing or blending in batch processes PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article

3M Aerospace Sealant AC-380 B-1/2 Catalyst

Processes, tasks and activities covered	Application of product. Manual application of product. Mixing or blending of solid or liquid materials. Transfer of substance/mixture with dedicated engineering controls.
2. Operational conditions and risk management measures	
Operating Conditions	<p>Physical state:Liquid.</p> <p>General operating conditions: Emission days per year: 220 days/year; Indoors with LEV and good general ventilation; Processing Temperature:: <= 40 degree Celsius;</p> <p>Task: PROC05; Duration of use: 4 hours/day;</p> <p>Task: PROC08b; Duration of use: 8 hours/day;</p> <p>Task: PROC10; Duration of use: 4 hours/day;</p> <p>Task: PROC13; Duration of use: 8 hours/day;</p>
Risk management measures	<p>Under the operational conditions described above the following risk management measures apply:</p> <p>General risk management measures:</p> <p>Human health: None needed;</p> <p>Environmental: Industrial Sewage Treatment Plant; Waste Water treatment - Incineration; ;</p> <p>The following task-specific risk management measures apply in addition to those listed above:</p> <p>Task: Mixing; Human Health; Air-purifying Half-Mask (with gas/vapour-cartridge, that can be combined with a particulate filter) (APF 10);</p> <p>Task: PROC10; Human Health; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.;</p> <p>Task: PROC13; Human Health; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.;</p>
Waste management measures	Incinerate in a permitted hazardous waste incinerator;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk