

Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 35-1986-5 **Version number:** 4.04

Revision date: 11/10/2022 **Supersedes date:** 29/03/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

08861 UNDERBODY COATING

Product Identification Numbers

UU-0037-1138-7 UU-0111-0392-4

7100077962 7100235847

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 E Mail: tox.uk@mmm.com Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms







Ingredients:

Ingredient CAS Nbr EC No. % by Wt

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics 920-750-0 20 - 60

HAZARD STATEMENTS:

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261A Avoid breathing vapours.

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

Notes on labelling

2004/42/EC IIB(e)(840) 370 g/l

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Limestone	(CAS-No.) 1317-65-3 (EC-No.) 215-279-6	20 - 60	Substance with a national occupational exposure limit
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(EC-No.) 920-750-0 (REACH-No.) 01- 2119473851-33	20 - 60	Aquatic Chronic 2, H411 Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066
Asphalt, oxidized	(CAS-No.) 64742-93-4 (EC-No.) 265-196-4	20 - 60	Substance not classified as hazardous
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	(CAS-No.) 68953-58-2 (EC-No.) 273-219-4	0.1 - 10	Substance not classified as hazardous
propylene carbonate	(CAS-No.) 108-32-7 (EC-No.) 203-572-1	0.1 - 7	Eye Irrit. 2, H319
Hydrocarbons, C9, aromatics	(EC-No.) 918-668-5 (REACH-No.) 01- 2119455851-35	1 - 5	EUH066 Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT SE 3, H335

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Toxic by eye contact. Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring combustion.Carbon dioxide.During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Limestone	1317-65-3	UK HSC	TWA(respirable):4	
			mg/m3;TWA(as respirable	
			dust):4	
			mg/m3;TWA(Inhalable):10	
			mg/m3;TWA(as inhalable	
			dust):10 mg/m3	

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile rubber.

Applicable Norms/Standards Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Specific Physical Form:

Colour

Black

Colour Black
Odor Chara

OdorCharacteristic OdourOdour thresholdNo data available.Melting point/freezing pointNo data available.Boiling point/boiling range90 °C

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Not applicable.

0.6 % volume

7 % volume

Flash point 9 °C [Test Method: Closed Cup]

Autoignition temperatureNo data available.Decomposition temperatureNo data available.

H substance/mixture is non-soluble (in water)

(inematic Viscosity 45 mm²/sec

Kinematic Viscosity Water solubility45 mm²/sec
No data available.

Solubility- non-water Nil [Details: Not miscible or difficult to mix]

Partition coefficient: n-octanol/waterNo data available.Vapour pressure2 kPa [Details:20°C]Density1.09 g/cm3

Relative density 1.09 [Ref Std: WATER=1]

Relative Vapor Density

No data available.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds Evaporation rate

No data available. No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Dermal	Rabbit	LD50 > 2,920 mg/kg
Asphalt, oxidized	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Inhalation- Vapour (4 hours)	Rat	LC50 > 23.3 mg/l
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,820 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation- Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Asphalt, oxidized	Ingestion	Rat	LD50 > 5,000 mg/kg
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Dermal		LD50 estimated to be > 5,000 mg/kg
Hydrocarbons, C9, aromatics	Dermal	Rabbit	LD50 > 3,160 mg/kg
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 12.6 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C9, aromatics	Inhalation- Vapour (4 hours)	Rat	LC50 > 6.2 mg/l
Hydrocarbons, C9, aromatics	Ingestion	Rat	LD50 3,492 mg/kg
propylene carbonate	Dermal	Rabbit	LD50 > 3,000 mg/kg
propylene carbonate	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Name	Species	value
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Rabbit	Minimal irritation
Limestone	Rabbit	No significant irritation
Asphalt, oxidized	Human	Minimal irritation
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts	Rat	No significant irritation
with bentonite		
Hydrocarbons, C9, aromatics	Rabbit	Mild irritant
propylene carbonate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Rabbit	Mild irritant
Limestone	Rabbit	No significant irritation
Asphalt, oxidized	Human	Mild irritant
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts	Rabbit	No significant irritation
with bentonite		
Hydrocarbons, C9, aromatics	Rabbit	Mild irritant
propylene carbonate	Rabbit	Severe irritant

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Guinea	Not classified
	pig	
Hydrocarbons, C9, aromatics	Guinea	Not classified
	pig	

Photosensitisation

Name	Species	Value
Asphalt, oxidized	Human	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Germ Cen Mutagementy		
Name	Route	Value
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	In Vitro	Not mutagenic
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	In vivo	Not mutagenic
Asphalt, oxidized	In vivo	Not mutagenic
Asphalt, oxidized	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydrocarbons, C9, aromatics	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Asphalt, oxidized	Not	Human	Some positive data exist, but the data are not
	specified.	and	sufficient for classification
		animal	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Hydrocarbons, C9, aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C9, aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C9, aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation

Page: 9 of 15

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Hydrocarbons, C9, aromatics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrocarbons, C9, aromatics	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Asphalt, oxidized	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value	
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Aspiration hazard	
Hydrocarbons, C9, aromatics	Aspiration hazard	

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Туре	Exposure	Test endpoint	Test result
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	Green algae	Estimated	72 hours	EC50	10 mg/l
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	Rainbow trout	Estimated	96 hours	LL50	3 mg/l
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	Water flea	Estimated	48 hours	EC50	4.6 mg/l
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	Green algae	Estimated	72 hours	NOEC	6.3 mg/l

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	Water flea	Estimated	21 days	NOEL	1 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Asphalt, oxidized	64742-93-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Activated sludge	Estimated	3 hours	EC50	>300 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Green algae	Estimated	72 hours	EC50	>100 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Water flea	Estimated	48 hours	EC50	>100 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
propylene carbonate	108-32-7	Activated sludge	Experimental	30 minutes	EC10	>=800 mg/l
propylene carbonate	108-32-7	Bacteria	Experimental	17 hours	EC50	>10,000 mg/l
propylene carbonate	108-32-7	Common Carp	Experimental	96 hours	LC50	>1,000 mg/l
propylene carbonate	108-32-7	Green algae	Experimental	72 hours	EC50	>900 mg/l
propylene carbonate	108-32-7	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
propylene carbonate	108-32-7	Green algae	Experimental	72 hours	EC10	900 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Activated sludge	Experimental	10 minutes	EC50	>99 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Green algae	Experimental	72 hours	EC50	0.42 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Rainbow trout	Experimental	96 hours	LL50	9.2 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Water flea	Experimental	48 hours	EL50	3.2 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Green algae	Experimental	72 hours	NOEC	0.07 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C7-C9, n-	920-750-0	Estimated	28 days	BOD	98 %BOD/ThO	OECD 301F - Manometric
alkanes, isoalkanes, cyclics		Biodegradation			D	respirometry
Limestone	1317-65-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Asphalt, oxidized	64742-93-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Quaternary ammonium	68953-58-2	Estimated	28 days	BOD	3 %BOD/ThO	OECD 301D - Closed bottle

Page: 11 of 15

compounds,		Biodegradation			D	test
bis(hydrogenated tallow						
alkyl)dimethyl, salts with						
bentonite						
propylene carbonate	108-32-7	Experimental	28 days	BOD	82 %BOD/ThO	OECD 301C - MITI test (I)
		Biodegradation	-		D	
Hydrocarbons, C9,	918-668-5	Experimental	28 days	BOD	78 %BOD/ThO	OECD 301F - Manometric
aromatics		Biodegradation	-		D	respirometry

12.3: Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Asphalt, oxidized	64742-93-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
propylene carbonate	108-32-7	Experimental Bioconcentration		Log Kow	-0.41	
Hydrocarbons, C9, aromatics	918-668-5	Estimated BCF - Fish	70 days	Bioaccumulation factor	342	

12.4. Mobility in soil

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are

complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN1139	UN1139	UN1139
14.2 UN proper shipping name	COATING SOLUTION	COATING SOLUTION	COATING SOLUTION
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	II	II	II
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<u>Ingredient</u> <u>CAS Nbr</u> <u>Classification</u> <u>Regulation</u>

Page: 13 of

Asphalt, oxidized

64742-93-4

Grp. 2A: Probable human carc.

International Agency for Research on Cancer

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Label: CLP Precautionary - Response information was modified.

Section 9: Relative density information information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Target Organs - Repeated Table information was added.

Section 11: Target Organs - Repeated Table information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 14 Classification Code – Regulation Data information was modified.

Section 14 Control Temperature – Regulation Data information was modified.

Section 14 Emergency Temperature – Regulation Data information was modified.

Section 14 Multiplier – Main Heading information was deleted.

Section 14 Multiplier – Regulation Data information was deleted.

Section 14 Other Dangerous Goods - Regulation Data information was modified.

Section 14 Segregation – Regulation Data information was modified.

Section 14 Transport Category – Main Heading information was deleted.

Section 14 Transport Category – Regulation Data information was deleted.

Section 14 Transport in bulk – Regulation Data information was modified.

Section 14 Marine transport in bulk according to IMO instruments - Main Heading information was modified.

Section 14 Transport Not Permitted – Main Heading information was deleted.

Section 14 Transport Not Permitted – Regulation Data information was deleted.

Section 14 Tunnel Code – Main Heading information was deleted.

Section 14 Tunnel Code – Regulation Data information was deleted.

Section 14 UN Number information was modified.

Section 15: Regulations - Inventories information was added.

Section 2: No PBT/vPvB information available warning information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk