



## Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	10-2796-0	<b>Version number:</b>	2.00
<b>Revision date:</b>	19/06/2023	<b>Supersedes date:</b>	23/02/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M™ Neoprene Rubber and Gasket Adhesive 2141

#### Product Identification Numbers

62-2141-6530-0

7000046346

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Rubber and gasket adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com/uk

##### EU Member State Responsible Contact

Address: 3M Ireland Ltd, The Iveagh Building, Carrickmines Park, Dublin D18 X015.  
Telephone: +353 1 280 3555

#### 1.4. Emergency telephone number

+44 (0)1344 858 000 or call your doctor.

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

**CLASSIFICATION:**

Flammable Liquid, Category 2 - Flam. Liq. 2; H225  
 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
 Skin Sensitization, Category 1 - Skin Sens. 1; H317  
 Reproductive Toxicity, Category 2 - Repr. 2; H361fd  
 Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373  
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

**2.2. Label elements**

**CLP REGULATION (EC) No 1272/2008**

**SIGNAL WORD**

DANGER.

**Symbols**

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

**Pictograms**



**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
toluene	108-88-3	203-625-9	30 - 40
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane		924-168-8	10 - 25
rosin	8050-09-7	232-475-7	< 1
Phenol, styrenated	61788-44-1	262-975-0	< 1

**HAZARD STATEMENTS:**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system   sensory organs.
H411	Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

P260A Do not breathe vapours.  
P273 Avoid release to the environment.  
P280K Wear protective gloves and respiratory protection.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

5% of the mixture consists of components of unknown acute inhalation toxicity.  
Contains 27% of components with unknown hazards to the aquatic environment.

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (REACH-No.) 01-2119471310-51	30 - 40	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	(EC-No.) 924-168-8	10 - 25	Aquatic Chronic 2, H411 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373
Polychloroprene	(CAS-No.) 9010-98-4	10 - 20	Substance not classified as hazardous
Magnesium Resinate	(CAS-No.) 68037-42-3	10 - 20	Substance not classified as hazardous
acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (REACH-No.) 01-2119471330-49	10 - 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	(CAS-No.) 25085-50-1	10 - 15	Substance not classified as hazardous
Resin acids and rosin acids, esters with glycerol	(CAS-No.) 8050-31-5 (EC-No.) 232-482-5	1 - 5	Substance not classified as hazardous
Phenol, styrenated	(CAS-No.) 61788-44-1	< 1	Skin Sens. 1A, H317

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

	(EC-No.) 262-975-0		Aquatic Chronic 2, H411
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4	< 1	Flam. Liq. 2, H225 Acute Tox. 4, H332 Asp. Tox. 1, H304 STOT RE 2, H373 Aquatic Chronic 3, H412
methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6	< 1	Flam. Liq. 2, H225 Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 STOT SE 1, H370
zinc oxide	(CAS-No.) 1314-13-2 (EC-No.) 215-222-5	< 1	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
rosin	(CAS-No.) 8050-09-7 (EC-No.) 232-475-7	< 1	Skin Sens. 1B, H317

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.  
Please see section 16 for the full text of any H statements referred to in this section

**Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6	(C >= 10%) STOT SE 1, H370 (3% <= C < 10%) STOT SE 2, H371

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous

## 3M™ Neoprene Rubber and Gasket Adhesive 2141

system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

## 3M™ Neoprene Rubber and Gasket Adhesive 2141

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
ethylbenzene	100-41-4	UK HSC	TWA:441 mg/m <sup>3</sup> (100 ppm);STEL:552 mg/m <sup>3</sup> (125 ppm)	SKIN
toluene	108-88-3	UK HSC	TWA: 191 mg/m <sup>3</sup> (50 ppm); STEL: 384 mg/m <sup>3</sup> (100 ppm)	SKIN
DUST, INERT OR NUISANCE	1314-13-2	UK HSC	TWA(as respirable dust):4 mg/m <sup>3</sup> ;TWA(as inhalable dust):10 mg/m <sup>3</sup>	
methanol	67-56-1	UK HSC	TWA:266 mg/m <sup>3</sup> (200 ppm);STEL:333 mg/m <sup>3</sup> (250 ppm)	SKIN
acetone	67-64-1	UK HSC	TWA:1210 mg/m <sup>3</sup> (500 ppm);STEL:3620 mg/m <sup>3</sup> (1500 ppm)	
rosin	8050-09-7	UK HSC	TWA(as fume):0.05 mg/m <sup>3</sup> ;STEL(as fume):0.15 mg/m <sup>3</sup>	Respiratory Sensitizer

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
------------	---------------------	------------	------------------------	------

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

acetone		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	186 mg/kg bw/d
acetone		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	1,210 mg/m <sup>3</sup>
acetone		Worker	Inhalation, Short-term exposure, Local effects	2,420 mg/m <sup>3</sup>
toluene		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	384 mg/kg bw/d
toluene		Worker	Inhalation, Long-term exposure (8 hours), Local effects	192 mg/m <sup>3</sup>
toluene		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	192 mg/m <sup>3</sup>
toluene		Worker	Inhalation, Short-term exposure, Local effects	384 mg/m <sup>3</sup>
toluene		Worker	Inhalation, Short-term exposure, Systemic effects	384 mg/m <sup>3</sup>

**Predicted no effect concentrations (PNEC)**

Ingredient	Degradation Product	Compartment	PNEC
acetone		Agricultural soil	29.5 mg/kg d.w.
acetone		Freshwater	10.6 mg/l
acetone		Freshwater sediments	30.4 mg/kg d.w.
acetone		Intermittent releases to water	21 mg/l
acetone		Marine water	1.06 mg/l
acetone		Marine water sediments	3.04 mg/kg d.w.
acetone		Sewage Treatment Plant	100 mg/l
toluene		Agricultural soil	2.89 mg/kg d.w.
toluene		Freshwater	0.68 mg/l
toluene		Sewage Treatment Plant	13.61 mg/l

**8.2. Exposure controls**

In addition, refer to the annex for more information.

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

## 3M™ Neoprene Rubber and Gasket Adhesive 2141

Safety glasses with side shields.  
Indirect vented goggles.

### *Applicable Norms/Standards*

Use eye protection conforming to EN 166

### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

<b>Material</b>	<b>Thickness (mm)</b>	<b>Breakthrough Time</b>
Polymer laminate	No data available	No data available

### *Applicable Norms/Standards*

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

### *Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

### **8.2.3. Environmental exposure controls**

Refer to Annex

## SECTION 9: Physical and chemical properties

### **9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Colour</b>	Tan
<b>Odor</b>	Sweet Petroleum
<b>Odour threshold</b>	<i>No data available.</i>
<b>Melting point/freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/boiling range</b>	$\geq 56$ °C [ <i>Details:acetone</i> ]
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	1 % volume
<b>Flammable Limits(UEL)</b>	12.8 % volume
<b>Flash point</b>	-26 °C [ <i>Test Method:Closed Cup</i> ] [ <i>Details:Petroleum</i> ]



Autoignition temperature	Distillate] 465 °C
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	1,395 mm <sup>2</sup> /sec
Water solubility	Slight (less than 10%)
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<=24,664.6 Pa [@ 20 °C ]
Density	0.86 g/ml
Relative density	0.86 [Ref.Std:WATER=1]
Relative Vapour Density	2 [Ref.Std:AIR=1]

## 9.2. Other information

### 9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	>=2.5 [Ref.Std:ETHER=1]
Molecular weight	<i>No data available.</i>
Solids content	20 - 45 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.  
Sparks and/or flames.

### 10.5 Incompatible materials

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

**Eye contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Prolonged or repeated exposure may cause target organ effects:**

Ocular effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Peripheral neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy. Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

toluene	Ingestion	Rat	LD50 5,550 mg/kg
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Dermal	Rat	LD50 > 2,800 mg/kg
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 25.2 mg/l
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Ingestion	Rat	LD50 > 5,840 mg/kg
acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
acetone	Ingestion	Rat	LD50 5,800 mg/kg
Polychloroprene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Dermal		LD50 estimated to be > 5,000 mg/kg
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Ingestion	Rat	LD50 5,660 mg/kg
Magnesium Resinate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium Resinate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Resin acids and rosin acids, esters with glycerol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Resin acids and rosin acids, esters with glycerol	Ingestion	Rat	LD50 > 2,000 mg/kg
zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
rosin	Dermal	Rabbit	LD50 > 2,500 mg/kg
rosin	Ingestion	Rat	LD50 7,600 mg/kg
ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
ethylbenzene	Inhalation-Vapour (4 hours)	Rat	LC50 17.4 mg/l
ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Phenol, styrenated	Dermal	Rat	LD50 > 2,000 mg/kg
Phenol, styrenated	Ingestion	Rat	LD50 > 2,000 mg/kg
methanol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
methanol	Inhalation-Vapour		LC50 estimated to be 10 - 20 mg/l
methanol	Ingestion		LD50 estimated to be 50 - 300 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
toluene	Rabbit	Irritant
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Rabbit	Irritant
acetone	Mouse	Minimal irritation
Polychloroprene	Human	No significant irritation
Resin acids and rosin acids, esters with glycerol	Rabbit	Minimal irritation
zinc oxide	Human and animal	No significant irritation
rosin	Rabbit	No significant irritation
ethylbenzene	Rabbit	Mild irritant
Phenol, styrenated	Rabbit	No significant irritation
methanol	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
toluene	Rabbit	Moderate irritant

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Rabbit	Mild irritant
acetone	Rabbit	Severe irritant
Polychloroprene	Professional judgement	No significant irritation
Resin acids and rosin acids, esters with glycerol	Rabbit	Mild irritant
zinc oxide	Rabbit	Mild irritant
rosin	Rabbit	Mild irritant
ethylbenzene	Rabbit	Moderate irritant
Phenol, styrenated	Rabbit	Mild irritant
methanol	Rabbit	Moderate irritant

**Skin Sensitisation**

Name	Species	Value
toluene	Guinea pig	Not classified
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Guinea pig	Not classified
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Human	Some positive data exist, but the data are not sufficient for classification
Resin acids and rosin acids, esters with glycerol	Guinea pig	Not classified
zinc oxide	Guinea pig	Not classified
rosin	Guinea pig	Sensitising
ethylbenzene	Human	Not classified
Phenol, styrenated	Mouse	Sensitising
methanol	Guinea pig	Not classified

**Respiratory Sensitisation**

Name	Species	Value
rosin	Human	Not classified

**Germ Cell Mutagenicity**

Name	Route	Value
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
acetone	In vivo	Not mutagenic
acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Resin acids and rosin acids, esters with glycerol	In Vitro	Not mutagenic
zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
ethylbenzene	In vivo	Not mutagenic
ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
methanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
methanol	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
acetone	Not specified.	Multiple animal species	Not carcinogenic
ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
methanol	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity**
**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Ingestion	Toxic to male reproduction	similar compounds	NOAEL Not available	not available
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Inhalation	Toxic to male reproduction	similar compounds	NOAEL Not available	not available
acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	prematuring & during gestation
ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
methanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
methanol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
methanol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

		system depression	dizziness		available	and/or abuse
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL Not available	not available
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL Not available	not available
acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
methanol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
methanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
methanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
methanol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
methanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	nervous system	May cause damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for	Rat	NOAEL 625 mg/kg/day	13 weeks

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

toluene	Ingestion	heart	classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, >5% n-hexane	Inhalation	peripheral nervous system	May cause damage to organs though prolonged or repeated exposure	similar compoun ds	NOAEL Not available	not available
acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
acetone	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Resin acids and rosin acids, esters with glycerol	Ingestion	liver   heart   skin   endocrine system   bone, teeth, nails, and/or hair   blood   bone marrow   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 5,000 mg/kg/day	90 days
zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
zinc oxide	Ingestion	endocrine system   hematopoietic system   kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
methanol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
methanol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
methanol	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
toluene	Aspiration hazard
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	Aspiration hazard
ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l



**3M™ Neoprene Rubber and Gasket Adhesive 2141**

toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	924-168-8	Green algae	Estimated	72 hours	EL50	30-100 mg/l
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	924-168-8	Rainbow trout	Estimated	96 hours	LL50	11.4 mg/l
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	924-168-8	Water flea	Estimated	48 hours	EL50	3 mg/l
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	924-168-8	Green algae	Estimated	72 hours	NOEL	3 mg/l
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	924-168-8	Water flea	Estimated	21 days	NOEC	0.17 mg/l
acetone	67-64-1	Algae or other aquatic plants	Experimental	96 hours	EC50	11,493 mg/l
acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l
acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
Magnesium Resinate	68037-42-3	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
Polychloroprene	9010-98-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Rainbow trout	Estimated	96 hours	No tox obs at lmt of water sol	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

ethylbenzene	100-41-4	Atlantic Silverside	Experimental	96 hours	LC50	5.1 mg/l
ethylbenzene	100-41-4	Green algae	Experimental	96 hours	EC50	3.6 mg/l
ethylbenzene	100-41-4	Mysid Shrimp	Experimental	96 hours	LC50	2.6 mg/l
ethylbenzene	100-41-4	Rainbow trout	Experimental	96 hours	LC50	4.2 mg/l
ethylbenzene	100-41-4	Water flea	Experimental	48 hours	EC50	1.8 mg/l
ethylbenzene	100-41-4	Water flea	Experimental	7 days	NOEC	0.96 mg/l
methanol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	EC50	16.9 mg/l
methanol	67-56-1	Bay mussel	Experimental	96 hours	LC50	15,900 mg/l
methanol	67-56-1	Bluegill	Experimental	96 hours	LC50	15,400 mg/l
methanol	67-56-1	Green algae	Experimental	96 hours	ErC50	22,000 mg/l
methanol	67-56-1	Sediment organism	Experimental	96 hours	LC50	54,890 mg/l
methanol	67-56-1	Water flea	Experimental	48 hours	LC50	3,289 mg/l
methanol	67-56-1	Green algae	Experimental	96 hours	NOEC	9.96 mg/l
methanol	67-56-1	Medaka	Experimental	8.33 days	NOEC	158,000 mg/l
methanol	67-56-1	Water flea	Experimental	21 days	NOEC	122 mg/l
methanol	67-56-1	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
methanol	67-56-1	Barley	Experimental	14 days	EC50	15,492 mg/kg (Dry Weight)
methanol	67-56-1	Redworm	Experimental	63 days	EC50	26,646 mg/kg (Dry Weight)
methanol	67-56-1	Springtail	Experimental	28 days	EC50	5,683 mg/kg (Dry Weight)
rosin	8050-09-7	Bacteria	Experimental	N/A	EC50	76.1 mg/l
rosin	8050-09-7	Green algae	Experimental	72 hours	EL50	>100 mg/l
rosin	8050-09-7	Water flea	Experimental	48 hours	EL50	911 mg/l
rosin	8050-09-7	Zebra Fish	Experimental	96 hours	LL50	>1 mg/l
rosin	8050-09-7	Green algae	Experimental	72 hours	NOEL	100 mg/l
Phenol, styrenated	61788-44-1	Activated sludge	Experimental	3 hours	EC50	362 mg/l
Phenol, styrenated	61788-44-1	Green algae	Experimental	72 hours	EC50	1.35 mg/l
Phenol, styrenated	61788-44-1	Medaka	Experimental	96 hours	LC50	5.6 mg/l
Phenol, styrenated	61788-44-1	Water flea	Experimental	48 hours	EC50	4.6 mg/l
Phenol, styrenated	61788-44-1	Green algae	Experimental	72 hours	NOEC	0.42 mg/l
Phenol, styrenated	61788-44-1	Water flea	Experimental	21 days	NOEC	0.2 mg/l
zinc oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	924-168-8	Estimated Biodegradation	28 days	BOD	98 %BOD/ThOD	OECD 301F - Manometric respirometry
acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 %BOD/ThOD	OECD 301D - Closed bottle test
acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Magnesium Resinate	68037-42-3	Data not available/insufficient	N/A	N/A	N/A	N/A
Polychloroprene	9010-98-4	Data not available/insufficient	N/A	N/A	N/A	N/A
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	
Resin acids and rosin acids, esters with glycerol	8050-31-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
ethylbenzene	100-41-4	Experimental Biodegradation	28 days	CO2 evolution	70-80 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	
methanol	67-56-1	Experimental Biodegradation	3 days	Percent degraded	91 %degraded	
methanol	67-56-1	Experimental Biodegradation	14 days	BOD	92 %BOD/ThOD	OECD 301C - MITI test (I)
methanol	67-56-1	Experimental Photolysis		Photolytic half-life (in air)	35 days (t 1/2)	
methanol	67-56-1	Experimental Soil Metabolism Aerobic	5 days	CO2 evolution	53.4 %CO2 evolution/THCO2 evolution	
rosin	8050-09-7	Experimental Biodegradation	28 days	CO2 evolution	64 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Phenol, styrenated	61788-44-1	Experimental Biodegradation	28 days	BOD	7 %BOD/ThOD	OECD 301F - Manometric respirometry
zinc oxide	1314-13-2	Data not available/insufficient	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, >5% n-hexane	924-168-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	
Magnesium Resinate	68037-42-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polychloroprene	9010-98-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	Estimated Bioconcentration		Bioaccumulation factor	7.4	
Resin acids and rosin acids, esters with glycerol	8050-31-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ethylbenzene	100-41-4	Experimental BCF - Fish	42 days	Bioaccumulation factor	1	
methanol	67-56-1	Experimental BCF - Fish	3 days	Bioaccumulation factor	<4.5	
methanol	67-56-1	Experimental Bioconcentration		Log Kow	-0.77	
rosin	8050-09-7	Analogous Compound BCF - Fish	20 days	Bioaccumulation factor	129	
Phenol, styrenated	61788-44-1	Experimental BCF - Fish	10 days	Bioaccumulation factor	10395	
zinc oxide	1314-13-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	≤217	OECD305-Bioconcentration

**12.4. Mobility in soil**

Material	Cas No.	Test type	Study Type	Test result	Protocol
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	
acetone	67-64-1	Modeled Mobility in Soil	Koc	9.7 l/kg	Episuite™
Resin acids and rosin acids, esters with glycerol	8050-31-5	Estimated Mobility in Soil	Koc	>1000 l/kg	Episuite™
methanol	67-56-1	Experimental Mobility in Soil	Koc	0.13 l/kg	
Phenol, styrenated	61788-44-1	Estimated Mobility in Soil	Koc	≥20000 l/kg	Episuite™

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Endocrine disrupting properties**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances  
20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

**SECTION 14: Transportation information**

	<b>Ground Transport (ADR)</b>	<b>Air Transport (IATA)</b>	<b>Marine Transport (IMDG)</b>
<b>14.1 UN number or ID number</b>	UN1133	UN1133	UN1133
<b>14.2 UN proper shipping name</b>	ADHESIVES	ADHESIVES	ADHESIVES
<b>14.3 Transport hazard class(es)</b>	3	3	3
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	F1	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the

transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Polychloroprene	9010-98-4	Gr. 3: Not classifiable	International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
methanol	67-56-1
toluene	108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

#### Regulation (EU) 2019/1148 (marketing and use of explosive precursors)

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see your local legislation.

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500
P5c FLAMMABLE LIQUIDS*	5000	50000

\*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
acetone	67-64-1	10	50
ethylbenzene	100-41-4	10	50
methanol	67-56-1	500	5000
toluene	108-88-3	10	50
zinc oxide	1314-13-2	100	200

**Regulation (EU) No 649/2012**

No chemicals listed

**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

**SECTION 16: Other information****List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system   sensory organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

Label: CLP Percent Unknown information was added.

Label: CLP Percent Unknown information was modified.

Section 2: Other hazards phrase information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 03: SCL table information was added.

Section 8: Eye/face protection information information was modified.

Section 8: Occupational exposure limit table information was modified.

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

Section 8: Respiratory protection - recommended respirators information information was modified.  
 Section 11: Acute Toxicity table information was modified.  
 Section 11: Carcinogenicity Table information was modified.  
 Section 11: Germ Cell Mutagenicity Table information was modified.  
 Section 11: Health Effects - Skin information information was modified.  
 Section 11: Reproductive Toxicity Table information was modified.  
 Section 11: Serious Eye Damage/Irritation Table information was modified.  
 Section 11: Skin Corrosion/Irritation Table information was modified.  
 Section 11: Skin Sensitization Table information was modified.  
 Section 11: Target Organs - Repeated Table information was modified.  
 Section 11: Target Organs - Single Table information was modified.  
 Section 12: Component ecotoxicity information information was modified.  
 Section 12: Endocrine disruptor table row information was deleted.  
 Section 12: Mobility in soil information information was modified.  
 Section 12: No endocrine disruptor information available warning information was added.  
 Section 12: Persistence and Degradability information information was modified.  
 Section 12: Bioaccumulative potential information information was modified.  
 Section 15: Authorization status under REACH: SVHC Authorization ingredient information information was deleted.  
 Section 15: Restrictions on manufacture ingredients information information was modified.  
 Section 15: Seveso Hazard Category Text information was added.  
 Section 15: Seveso Substance Text information was modified.  
 Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

**Annex**

<b>1. Title</b>	
<b>Substance identification</b>	acetone; EC No. 200-662-2; CAS Nbr 67-64-1;
<b>Exposure Scenario Name</b>	Formulation
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
<b>Processes, tasks and activities covered</b>	Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs. Transfers with dedicated controls, including loading, filling, dumping, bagging. Transfers without dedicated controls, including loading, filling, dumping, bagging.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: <= 360 days per year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour);



**3M™ Neoprene Rubber and Gasket Adhesive 2141**

	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	toluene; EC No. 203-625-9; CAS Nbr 108-88-3;
<b>Exposure Scenario Name</b>	Formulation
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
<b>Processes, tasks and activities covered</b>	Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Duration of use: 5 days/week; Emission days per year: 300 days/year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); <b>Environmental:</b> None needed;
<b>Waste management measures</b>	Do not apply industrial sludge to natural soils; Send to an industrial sewage treatment plant;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	acetone; EC No. 200-662-2; CAS Nbr 67-64-1;
<b>Exposure Scenario Name</b>	Industrial Use of Adhesives and Sealants
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 07 -Industrial spraying ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Spraying of substances/mixtures.

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: <= 360 days per year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed; ; The following task-specific risk management measures apply in addition to those listed above: <b>Task: PROC07;</b> <b>Human Health;</b> Local exhaust ventilation;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	toluene; EC No. 203-625-9; CAS Nbr 108-88-3;
<b>Exposure Scenario Name</b>	Industrial Use of Adhesives and Sealants
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 05 -Mixing or blending in batch processes PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Application of product with a roller or brush. Application of product. Mixing operations (open systems). Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Duration of use: 5 days/week; Emission days per year: 300 days/year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b>

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); <b>Environmental:</b> Air abatement;
<b>Waste management measures</b>	Do not apply industrial sludge to natural soils; Send to an industrial sewage treatment plant;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	acetone; EC No. 200-662-2; CAS Nbr 67-64-1;
<b>Exposure Scenario Name</b>	Industrial Use of Coatings
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Application of product with a roller or brush. Transfers with dedicated controls, including loading, filling, dumping, bagging. Transfers without dedicated controls, including loading, filling, dumping, bagging.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: <= 360 days per year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	toluene; EC No. 203-625-9; CAS Nbr 108-88-3;
<b>Exposure Scenario Name</b>	Industrial Use of Coatings
<b>Lifecycle Stage</b>	Use at industrial sites

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

<b>Contributing activities</b>	PROC 03 -Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC 07 -Industrial spraying PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC 10 -Roller application or brushing ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Application of product with a roller or brush. Manual application of product. Spraying of substances/mixtures. Transfers with dedicated controls, including loading, filling, dumping, bagging. Transfers without dedicated controls, including loading, filling, dumping, bagging.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Duration of use: 5 days/week; Emission days per year: 300 days/year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); <b>Environmental:</b> Air abatement; Industrial Sewage Treatment Plant; ; The following task-specific risk management measures apply in addition to those listed above: <b>Task: Spraying;</b> <b>Human Health;</b> Ventilated Process Enclosures; Air-purifying Full-Face (with gas/vapour cartridge, that can be combined with a particulate filter);
<b>Waste management measures</b>	Do not apply industrial sludge to natural soils;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	acetone; EC No. 200-662-2; CAS Nbr 67-64-1;
<b>Exposure Scenario Name</b>	Professional Use of Coatings
<b>Lifecycle Stage</b>	Widespread use by professional workers
<b>Contributing activities</b>	PROC 10 -Roller application or brushing PROC 11 -Non industrial spraying ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

3M™ Neoprene Rubber and Gasket Adhesive 2141

<b>Processes, tasks and activities covered</b>	Application with a wipe. Spraying of substances/mixtures.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: <= 360 days per year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed; ; The following task-specific risk management measures apply in addition to those listed above: <b>Task: PROC11;</b> <b>Human Health;</b> Local exhaust ventilation;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	toluene; EC No. 203-625-9; CAS Nbr 108-88-3;
<b>Exposure Scenario Name</b>	Professional Use of Coatings
<b>Lifecycle Stage</b>	Widespread use by professional workers
<b>Contributing activities</b>	PROC 05 -Mixing or blending in batch processes PROC 10 -Roller application or brushing PROC 11 -Non industrial spraying ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
<b>Processes, tasks and activities covered</b>	Application of product. Mixing or blending of solid or liquid materials.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 365 days/year; Outdoor use;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Air-purifying Full-Face (with gas/vapour cartridge, that can be combined with a particulate filter); Air-purifying Half-Mask (with gas/vapour-cartridge, that can be combined with a

**3M™ Neoprene Rubber and Gasket Adhesive 2141**

	particulate filter) (APF 10); Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> Municipal Sewage Treatment Plant;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**For Northern Ireland documents, please contact your 3M representative to obtain a copy.**