Revision: 13.04.2023

Printing date 13.04.2023 Version number 16 (replaces version 15)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ADEKIT A 210 ISOCYANATE (B)
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SIKA AUTOMOTIVE FRANCE SAS

15 Rue de l'Equerre - F-95310 SAINT OUEN L'AUMONE

Tél.+33 (0)1 34 40 34 60

- · Further information obtainable from: DPT HSE +33 (0)1 34 40 34 60 safety@fr.sika.com
- · 1.4 Emergency telephone number:

ORFILA: +33 (0)1 45 42 59 59

+44 (0)1707 363899 (available during office hours).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:

Hexamethylene-1,6-diisocyanate homopolymer

4-methyl-m-phenylene diisocyanate

· Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)



Printing date 13.04.2023 Version number 16 (replaces version 15)

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17	Hexamethylene-1,6-diisocyanate homopolymer Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335 ATE: ATE inhalative: 1.5 mg/l	10-25%	
CAS: 2530-83-8 EINECS: 219-784-2 Reg.nr.: 01-2119513212-58	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318; Aquatic Chronic 3, H412		
CAS: 38640-62-9 EINECS: 254-052-6 Reg.nr.: 01-2119565150-48	diisopropylnaphthalene, isomers Asp. Tox. 1, H304; Aquatic Chronic 1, H410 (M=1)		
CAS: 584-84-9 EINECS: 209-544-5 Reg.nr.: 01-2119486974-18	4-methyl-m-phenylene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 ATE: ATE inhalative: 0.107 mg/l Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	<0.1%	
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37	hexamethylene-di-isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 ATE: ATE inhalative: 1.5 mg/l Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	<0.09%	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Carbon dioxide

(Contd. on page 3)

Revision: 13.04.2023

Printing date 13.04.2023 Version number 16 (replaces version 15)

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 2)

Fire-extinguishing powder

Foam

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

(Traces)

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

After approximately one hour, transfer to suitable drum containers. Do not close these (likelihood of CO2 production). Cover tops only.

Leave open to air in a supervised area for 7 to 14 days before transferring to an authorized dumping site.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Inform personnel of risks associated with the product, the precautions to be taken and procedures to follow where an accident occurs.

Avoid exposure to the material of persons having suffered from chronic respiratory affections (especially asthmatic and bronchitic persons) and those having an isocyanate allergia.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from humidity and water.

· 7.3 Specific end use(s) No further relevant information available.

GB

Version number 16 (replaces version 15) *Printing date 13.04.2023*

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 3)

Revision: 13.04.2023

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

584-84-9 4-methyl-m-phenylene diisocyanate

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m³

Sen; as -NCO

822-06-0 hexamethylene-di-isocyanate

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

· Ingredients with biological limit values:

584-84-9 4-methyl-m-phenylene diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

822-06-0 hexamethylene-di-isocyanate

BMGV 1 µmol creatinine/mol Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection



Protective gloves

· Material of gloves

PVC gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Sika®

Printing date 13.04.2023 Version number 16 (replaces version 15)

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 4)

Revision: 13.04.2023

· Eye/face protection



Safety glasses

Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Transparent
· Odour: Characteristic

· Melting point/freezing point: NA

· Boiling point or initial boiling point and boiling

range NA

Flash point: > 200 °C (P. Martens)
 Auto-ignition temperature: > 500 °C (DIN 51 794)

· pH at 20 •C NA

· Kinematic viscosity

·Solubility

· water: Insoluble.

organic solvents: Soluble in many organic solvents.

· Vapour pressure:

· Density and/or relative density

• Density at 20 °C: 1.09 g/cm³ (ISO 1675:1985)

9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void
Oxidising liquids Void

(Contd. on page 6)



Printing date 13.04.2023 Version number 16 (replaces version 15)

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 5)

· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Violent reactions with -NHx, -OH and -SH- groups.

In the presence of water or humidity gas is produced (CO2) and/or uncontrolled polymerization, possibly leading to internal pressure rises and consequent risk of container breach.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

28182-81-2 Hexamethylene-1,6-diisocyanate homopolymer

Oral	LD50	>2,500 mg/kg (rat)
Dermal		>2,000 mg/kg (rat)
Inhalative	LC50/4 h	1.5 mg/l (avis d'expert)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 7)

Revision: 13.04.2023

Printing date 13.04.2023 Version number 16 (replaces version 15)

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 6)

· Other information:

This product is not miscible in water. It acts on water, producing CO2 and polyurea (a solid, non-fusible and insoluble compound) which is, to the best of our knowledge, inert and non-biodegradable. This reaction is promoted by the presence of surfactants such as liquide soap, or water-soluble solvents. Do not dispose of this product or the neutralization products in sewers, rivers or streams.

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of the product by burning in a suitable incinerator or bury in an approved landfield following all applicable local and/or national regulations.

- · Uncleaned packaging:
- · Recommendation:

Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed.

Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

• 14.5 Environmental hazards: Not applicable. • 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

· UN ''Model Regulation'': Void

OD.

Revision: 13.04.2023

Printing date 13.04.2023 Version number 16 (replaces version 15)

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing SDS: -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 1: Acute toxicity - Category 1

Acute Tox. 2: Acute toxicity - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 9)



Printing date 13.04.2023 Version number 16 (replaces version 15)

Trade name: ADEKIT A 210 ISOCYANATE (B)

(Contd. of page 8)

Asp. Tox. 1: Aspiration hazard — Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

* Data compared to the previous version altered.