



Cleaners

## FASTCLEAN 200

### SUPER FAST DRY DEGREASER

As a substitute for 1,1,1-trichloroethane and other chlorinated solvents, Fastclean 200 immediately responds to the needs of users for all degreasing and surface preparation:

- when a very high evaporation speed is required
- when a high KB solvent is necessary for cleansing and cleaning heavily soiled parts
- when a hydrolysis risk must be avoided

FastClean 200 has a high KB factor – 106 vs 30 to 75 for other formulations. (A high KB value = more effective degreasing action).

Extremely low surface tension – half that of 1,1,1-trichloroethane - means improved surface wetting to get under dirt more effectively.

### PRODUCT CODES / FILL SIZES



31890 / 400ml

### APPLICATIONS

#### SURFACE PREPARATION

- Cleaning metallic parts, certain plastics, composites and elastomers
- Eliminating organic and inorganic soiling before assembly, surface treatment, bonding, painting or plating

#### CLEANING OPERATIONS

- Can be used as a thinner for most organic materials
- Will clean off adhesives including liquid, paste or gel anaerobics, UV adhesives and uncured plastics materials
- Brake disks and shoes
- Cleaning operations on electrical equipment

### DIRECTIONS

- Always switch off electrical equipment and unplug from mains before using a liquid cleaner .
- Eliminate all ignition sources when using the product.
- Shake can thoroughly before use.
- Hold upright 30 cm (12 inches) from surface to be treated.
- Spray and shake alternately until area is fully covered.

## TECHNICAL DATA (WITHOUT PROPELLANT)

	Physical Characteristics	Test Method
Physical Appearance	Fluid	Visual
Colour	Colourless	Visual
Odour	Light, Characteristic	Smell
Specific Gravity at 25°C	0.742 g/ml	NFT 60.101
Boiling Point	43°C	ASTM D 1078
Auto Ignition Temperature	>200°C	ASTM E 659
Freezing Point	<-70°C	NFT 60.105
Viscosity at 25°C	0.766 mm <sup>2</sup> /s	ASTM D445
Evaporation Rate (DEE=1)	3	DIN 53.170
KB Index	106	ASTM D 1133
Water Solubility	<10 ppm	-
Surface Tension	12.8 dynes/cm	ASTM D 971
Copper Corrosion, 100h at 40°C	1a	ASTM D 1616
Discharge Rate	1.5 g/sec	-
Surface tension at 25°C /dynes/cm	Fastclean 200 – 12.8	1,1,1 Trichloroethane – 25.5

## MATERIALS COMPATIBILITY

OK	Highly effective on all metals and most plastics and rubbers. Always test cleaner on a small piece of plastic first
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1  
Created: July 2019  
Updated: October 2020

CRC Industries UK Ltd.  
Wylds Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e sales.uk@crcind.com  
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

