According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® AV 170 GB

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Adhesives

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA

Address : Everslaan 45

3078 Everberg Belgium

Telephone : +41 61 299 20 41 Telefax : +41 61 299 20 40

E-mail address of person

responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333

Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Hazard pictograms







Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

P391 Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,4-bis(2,3 epoxypropoxy)butane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
bis-[4-(2,3-	1675-54-3	Skin Irrit. 2; H315	>= 50 -

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

epoxipropoxi)phenyl]propane	216-823-5 603-073-00-2	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	< 70
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute dermal toxicity: 1,100 mg/kg	>= 10 - < 20
4,5-bis(hydroxymethyl)-2-phenyl-1H-imidazole	61698-32-6 262-911-1	Acute Tox. 4; H302 Acute toxicity estimate Acute oral toxicity: 1,610 mg/kg	>= 1 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon oxides

Halogenated compounds

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

Version Date of last issue: 27.11.2018 Revision Date: SDS Number: 400001007682 1.4 22.03.2022 Date of first issue: 03.10.2016

Print Date 21.06.2022

Hygiene measures When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Keep in properly

labelled containers.

Advice on common storage For incompatible materials please refer to Section 10 of this

SDS.

Further information on

storage stability

Stable under normal conditions.

Recommended storage

temperature

: 2-8°C

7.3 Specific end use(s)

Specific use(s) No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis-[4-(2,3- epoxipropoxi)phenyl]p ropane	Workers	Inhalation	Long-term systemic effects	4.93 mg/m3
	Workers	Dermal	Long-term systemic effects	0.75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.5 mg/kg bw/day
cyanoguanidine	Workers	Inhalation	Long-term systemic effects	15.3 mg/m3
	Workers	Inhalation	Acute systemic effects	76.5 mg/m3
	Workers	Dermal	Long-term systemic effects	30.1 mg/kg
	Consumers	Inhalation	Long-term local effects	11.2 mg/m3
	Consumers	Inhalation	Acute systemic	56 mg/m3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

			effects	
	Consumers	Dermal	Long-term systemic effects	6.5 mg/kg
	Consumers	Oral	Long-term systemic effects	6.5 mg/kg
1,4-bis(2,3 epoxypropoxy)butane	Workers	Inhalation	Long-term systemic effects	4.7 mg/m3
	Workers	Dermal	Long-term systemic effects	6.66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.16 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.33 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value	
bis-[4-(2,3-	Fresh water	0.006 mg/l	
epoxipropoxi)phenyl]propane			
	Marine water	0.001 mg/l	
	Fresh water sediment	0.341 mg/kg dry	
		weight (d.w.)	
	Marine sediment	0.034 mg/kg dry	
		weight (d.w.)	
	Soil	0.065 mg/kg dry	
		weight (d.w.)	
	Sewage treatment plant	10 mg/l	
	Secondary Poisoning	11 mg/kg	
cyanoguanidine	Fresh water	2.5 mg/l	
	Marine water	0.25 mg/l	
	Freshwater - intermittent	10 mg/l	
	Sewage treatment plant	34 mg/l	
	Fresh water sediment	5.83 mg/kg	
	Marine sediment	0.58 mg/kg	
	Soil	3.16 mg/kg	
Siloxanes and silicones, di-Me,	Fresh water sediment	> 100 mg/kg	
reaction products with silica			
	Remarks: Assessment Factors		
	Soil	23 mg/kg	
	Remarks: Assessment Factors		
1,4-bis(2,3 epoxypropoxy)butane	Fresh water	0.024 mg/l	
	Remarks:Assessment Factors		
	Marine water	0.002 mg/l	
	Remarks:Assessment Factors		
	Sewage treatment plant	100 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	0.084 mg/kg dry	
		weight (d.w.)	
	Remarks:Equilibrium method		
	Marine sediment	0.008 mg/kg dry	
		weight (d.w.)	
	Remarks:Equilibrium method		
	Soil	0.003 mg/kg dry	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

Version Revision Date: SDS Number: Date of last issue: 27.11.2018 400001007682 1.4 22.03.2022 Date of first issue: 03.10.2016

Print Date 21.06.2022

		weight (d.w.)
	Remarks:Equilibrium method	
	Oral	0.028 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butvl-rubber Break through time : >8h Glove thickness : 0.7 mm

: Ethyl Vinyl Alcohol Laminate (EVAL) Material

Break through time : > 8 h

Material : Nitrile rubber Break through time : > 10 - 480 min

Glove thickness : 0.4 mm

Remarks : Chemical-resistant, impervious gloves complying with an

> approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing

> Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : white

Odour : odourless

Odour Threshold : No data is available on the product itself.

рΗ : substance/mixture is non-soluble (in water)

Respiratory protection

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Melting point/freezing point : No data is available on the product itself.

Boiling point : > 200 °C

Flash point : > 200 °C

Method: closed cup

Flammability (solid, gas) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : ca. 1.2 (25 °C)

Density : ca. 1.2 g/cm3 (25 °C)

Solubility(ies)

Water solubility : insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 70 °C

Viscosity

Viscosity, dynamic : 20,000 - 50,000 mPa.s (20 °C)

Method: DIN, Other

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI

Enriching lives through innovation

ARALDITE® AV 170 GB

Version Revision Date: Date of last issue: 27.11.2018 SDS Number: 400001007682 1.4 22.03.2022 Date of first issue: 03.10.2016

Print Date 21.06.2022

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid None known.

10.6 Hazardous decomposition products

Hazardous decomposition carbon dioxide products carbon monoxide

Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute toxicity estimate: > 2,000 mg/kg Acute oral toxicity

Method: Calculation method

: Acute toxicity estimate: > 5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

: Acute toxicity estimate: > 2,000 mg/kg Acute dermal toxicity

Method: Calculation method

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

toxicity

Remarks: No mortality observed at this dose.

LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

1,4-bis(2,3 epoxypropoxy)butane:

Acute oral toxicity LD50 (Rat, male and female): 1,163 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Assessment: The component/mixture is moderately toxic after

single ingestion.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Acute inhalation toxicity : LC50 (Rat): > 2.068 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg

Method: Converted acute toxicity point estimate

Assessment: The component/mixture is moderately toxic after

single contact with skin.

4,5-bis(hydroxymethyl)-2-phenyl-1H-imidazole:

Acute oral toxicity : LD50 (Rat): 1,610 mg/kg

Method: No information available.

Acute toxicity estimate: 1,610 mg/kg

Method: Calculation method

Skin corrosion/irritation

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species : Rabbit Exposure time : 4 h

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

GLP : yes

Serious eye damage/eye irritation

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species : Rabbit

Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Result : Irritating to eyes.

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rabbit

Assessment : Risk of serious damage to eyes.
Method : OECD Test Guideline 405

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

GLP : yes

Respiratory or skin sensitisation

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1B.

1,4-bis(2,3 epoxypropoxy)butane:

Exposure routes : Skin Species : Guinea pig

Method : OECD Test Guideline 406

Result : May cause sensitisation by skin contact.

GLP : yes

Assessment : Harmful if inhaled.

Germ cell mutagenicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

Test Type: reverse mutation assay Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay) Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Mouse (male)

Cell type: Germ

Application Route: Oral Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test

Species: Rat (male)
Cell type: Somatic
Application Route: Oral

Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488

Result: negative

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

1,4-bis(2,3 epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay

Concentration: 10 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster lung cells

Concentration: 1 - 100 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

GLP: no

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male) Cell type: Somatic Application Route: Oral Exposure time: 4 d Dose: 187.5 - 750 mg/kg

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Test Type: unscheduled DNA synthesis assay

Species: Rat Cell type: Liver cells Application Route: Oral

Method: OECD Test Guideline 486

Result: negative

Germ cell mutagenicity-

Assessment

Weight of evidence does not support classification as a germ cell mutagen., Animal testing did not show any mutagenic

effects.

Carcinogenicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Species : Rat, male
Application Route : Oral
Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week

NOAEL : 15 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment : 3 days/week

NOEL : 0.1 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative
Target Organs : Digestive organs

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment : 5 days/week

NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Species : Rat, female
Application Route : Oral
Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOAEL : 100 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, females

Application Route : Oral Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOEL : 2 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Reproductive toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Effects on fertility : Test Type: Two-generation study

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily

General Toxicity - Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight

Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal development

Species: Rabbit, female Application Route: Dermal

Dose: 0, 30, 100 or 300 milligram per kilogram

Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: Other guidelines Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

Dose: 0, 20, 60 or 180 milligram per kilogram

Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0, 60, 180 and 540 milligram per kilogram

Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 180 mg/kg body weight Developmental Toxicity: NOAEL: > 540 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

1,4-bis(2,3 epoxypropoxy)butane:

Effects on foetal : Test Type: Pre-natal development Species: Rat, female

Application Route: Oral

Dose: 0/30/100/300 mg/kg bw/day Duration of Single Treatment: 17 d

General Toxicity Maternal: NOAEL: 300 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Remarks: Information given is based on data obtained from similar substances.

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species : Rat, male and female

NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks

Number of exposures : 7 d

Dose : 0, 50, 250, 1000 mg/kg/day Method : OECD Test Guideline 408

Species : Rat, male and female

NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

Number of exposures : 5 d

Dose : 0, 10, 100, 1000 mg/kg/day Method : OECD Test Guideline 411

Species: Mouse, maleNOAEL: 100 mg/kgApplication Route: Skin contactExposure time: 13 Weeks

Number of exposures : 3 d

Dose : 0, 1, 10, 100 mg/kg/day Method : OECD Test Guideline 411

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rat, male and female

NOAEL : 200 mg/kg Application Route : Oral Exposure time : 28 d Number of exposures : daily

Dose : 25, 100, 200, 400 mg/kg

Method : Subacute toxicity

Species : Rat, male and female

NOAEL : 263 mg/kg
Application Route : Oral
Exposure time : 90 h
Number of exposures : daily

Dose : 0,30,100,300 mg/kg bw/day
Method : OECD Test Guideline 408

GLP : yes

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAI

Enriching lives through innovation

ARALDITE® AV 170 GB

Version Revision Date: SDS Number: Date of last issue: 27.11.2018 400001007682 1.4 22.03.2022 Date of first issue: 03.10.2016

Print Date 21.06.2022

Remarks Information given is based on data obtained from similar

substances.

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

The substance/mixture does not contain components Assessment

> considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50: 11 mg/l Exposure time: 72 h

> Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009

NOEC: 4.2 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 0.3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,4-bis(2,3 epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l

End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203

GLP: no

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 75 mg/l

End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202

GLP: no

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 160

mq/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209

GLP: no

12.2 Persistence and degradability

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)

pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)

pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

1,4-bis(2,3 epoxypropoxy)butane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 43 % Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

Test Type: aerobic

Inoculum: Sewage (STP effluent)

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 38 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 28 d

Method: OECD Test Guideline 301E

GLP: no

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

12.3 Bioaccumulative potential

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Bioaccumulation : Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3.242 (25 °C)

octanol/water pH: 7.1

Method: OECD Test Guideline 117

1,4-bis(2,3 epoxypropoxy)butane:

Partition coefficient: n- : log Pow: -0.269 (25 °C)

octanol/water pH: 6.7

Method: OECD Test Guideline 117

GLP: yes

12.4 Mobility in soil

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Distribution among : Koc: 445

environmental compartments

1,4-bis(2,3 epoxypropoxy)butane:

Distribution among : Koc: 12.59

environmental compartments Method: OECD Test Guideline 121

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

 ADR
 : UN 3082

 RID
 : UN 3082

 IMDG
 : UN 3082

 IATA
 : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es)

 ADR
 : 9

 RID
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADR

Packing group : III Classification Code : M6

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

Hazard Identification Number : 90 Labels : 9 Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction : 964

(passenger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

Version Revision Date: SDS Number: Date of last issue: 27.11.2018 1.4 22.03.2022 400001007682 Date of first issue: 03.10.2016

Print Date 21.06.2022

(Annex XIV)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL

HAZARDS

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the

Canadian NDSL.

AIIC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Dam. 1 H318 Calculation method
Skin Sens. 1 H317 Calculation method
Aquatic Chronic 2 H411 Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



ARALDITE® AV 170 GB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.11.2018

 1.4
 22.03.2022
 400001007682
 Date of first issue: 03.10.2016

Print Date 21.06.2022

behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.