



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 14

BONDERITE L-GP 12 ACHESON known as BERKATEKT 12

SDS No. : 364063
V005.3

Revision: 26.01.2023

printing date: 16.02.2023

Replaces version from: 04.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BONDERITE L-GP 12 ACHESON known as BERKATEKT 12

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Protective product for nickel alloys-stainless steels

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

SDSinfo.Adhesive@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Toxic to reproduction	Category 2
H361d Suspected of damaging the unborn child.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard	Category 1
H304 May be fatal if swallowed and enters airways.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements**Label elements (CLP):****Hazard pictogram:****Contains**

Toluene

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Supplemental information

Contains: 1-(2-Methyl-4-(2-methylphenylazo)phenylazo)-2-naphthol May produce an allergic reaction.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P260 Do not breathe mist/vapours.
 P280 Wear protective gloves.

**Precautionary statement:
Response**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P331 Do NOT induce vomiting.
 P370+P378 In case of fire: Use CO₂, dry chemical, or foam for extinction.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Toluene 108-88-3 203-625-9 01-2119471310-51	80- 100 %	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, Inhalation, H373 Skin Irrit. 2, H315 STOT SE 3, Inhalation, H336 Aquatic Chronic 3, H412		EU OEL
1-(2-Methyl-4-(2-methylphenylazo)phenylazo)-2-naphthol 85-83-6 201-635-8 01-2120150875-50	0,1- < 1 %	Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351		

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.
In case of adverse health effects seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

After ingestion or vomit: danger of product entering the lung.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Do not induce vomiting.

Seek medical attention from a specialist.

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

Fine water spray

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

Water jet (solvent-containing product).

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in fires.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated.

See advice in section 8

Take measures to prevent the build-up of electrostatic charges.

Avoid open flames and sources of ignition.

Ground/bond container and receiving equipment.

Use explosion proof electric equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in sealed original container.

Do not store near sources of heat or ignition, or reactive materials.

7.3. Specific end use(s)

Protective product for nickel alloys-stainless steels

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Toluene 108-88-3 [TOLUENE]	50	191	Time Weighted Average (TWA):		EH40 WEL
Toluene 108-88-3 [TOLUENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Toluene 108-88-3 [TOLUENE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Toluene 108-88-3 [TOLUENE]	50	192	Time Weighted Average (TWA):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Toluene 108-88-3 [TOLUENE]	100	384	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Toluene 108-88-3	aqua (freshwater)		0,68 mg/l				
Toluene 108-88-3	sediment (freshwater)				16,39 mg/kg		
Toluene 108-88-3	sediment (marine water)				16,39 mg/kg		
Toluene 108-88-3	Soil				2,89 mg/kg		
Toluene 108-88-3	sewage treatment plant (STP)		13,61 mg/l				
Toluene 108-88-3	aqua (marine water)		0,68 mg/l				
Toluene 108-88-3	aqua (intermittent releases)		0,68 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Toluene 108-88-3	Workers	Inhalation	Acute/short term exposure - local effects		384 mg/m3	
Toluene 108-88-3	Workers	Inhalation	Acute/short term exposure - systemic effects		384 mg/m3	
Toluene 108-88-3	Workers	Inhalation	Long term exposure - local effects		192 mg/m3	
Toluene 108-88-3	Workers	Inhalation	Long term exposure - systemic effects		192 mg/m3	
Toluene 108-88-3	Workers	dermal	Long term exposure - systemic effects		384 mg/kg	
Toluene 108-88-3	General population	Inhalation	Acute/short term exposure - local effects		226 mg/m3	
Toluene 108-88-3	General population	Inhalation	Acute/short term exposure - systemic effects		226 mg/m3	
Toluene 108-88-3	General population	Inhalation	Long term exposure - systemic effects		56,5 mg/m3	
Toluene 108-88-3	General population	dermal	Long term exposure - systemic effects		226 mg/kg	
Toluene 108-88-3	General population	oral	Long term exposure - systemic effects		8,13 mg/kg	
Toluene 108-88-3	General population	inhalation	Long term exposure - local effects		56,5 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/suction at the workplace.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	liquid
Delivery form	liquid
Colour	red
Odor	Solvent
Melting point	Not applicable, Product is a liquid
Solidification temperature	-95 °C (-139 °F)
Initial boiling point	110 °C (230 °F)no method
Flammability	Highly flammable.
Explosive limits	
lower	1,2 %(V);
upper	7,0 %(V);
Flash point	Upper/lower explosion limit
Auto-ignition temperature	5 °C (41 °F); no method
Decomposition temperature	480 °C (896 °F)
	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (40 °C (104 °F);)	< 20 mm ² /s
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture 22 hPa
Vapour pressure (50 °C (122 °F))	93 hPa
Density (20 °C (68 °F))	0,9 g/cm ³ no method

Relative vapour density: (20 °C)	3,18
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

In case of fire toxic gases can be released.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Toluene 108-88-3	LD50	5.580 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))
1-(2-Methyl-4-(2-methylphenylazo)phenylazo)-2-naphthol 85-83-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Toluene 108-88-3	LD50	> 5.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Toluene 108-88-3	LC50	28,1 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Toluene 108-88-3	irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Toluene 108-88-3	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Toluene 108-88-3	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Toluene 108-88-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Toluene 108-88-3	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Toluene 108-88-3	not carcinogenic	inhalation: vapour	103 w 6.5 h/d, 5 d/w	rat	male/female	equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Toluene 108-88-3	NOAEL P 7500 mg/m ³ NOAEL F1 1875 mg/m ³ NOAEL F2 1875 mg/m ³	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Toluene 108-88-3	NOAEL P 2261 mg/m ³ NOAEL F1 2261 mg/m ³	fertility	inhalation: vapour	rat	not specified

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Toluene 108-88-3	NOAEL 625 mg/kg	oral: gavage	13 w daily, 5 d/w	rat	EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Toluene 108-88-3	NOAEL 1131 mg/m ³	inhalation: vapour	24 m 6.5 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Toluene 108-88-3	NOAEL 2355 mg/m ³	inhalation: vapour	15 w 6.5 h/d, 5 d/w	rat	EU Method B.29 (Sub-Chronic Inhalation Toxicity Test: 90-Day Repeated Inhalation Dose Study Using Rodent Species)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Toluene 108-88-3	0,57 mm ² /s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Toluene 108-88-3	NOEC	3,2 mg/l	28 d	Cyprinodon variegatus	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Toluene 108-88-3	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	OECD Guideline 203 (Fish, Acute Toxicity Test)
1-(2-Methyl-4-(2- methylphenylazo)phenylazo)- 2-naphthol 85-83-6	LC50	Toxicity > Water solubility	48 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Toluene 108-88-3	EC50	3,78 mg/l	48 h	Ceriodaphnia dubia	other guideline:

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Toluene 108-88-3	NOEC	0,74 mg/l	7 d	Ceriodaphnia dubia	other guideline:

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Toluene 108-88-3	IC50	12 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Toluene 108-88-3	NOEC	29 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Toluene 108-88-3	readily biodegradable	aerobic	80 %	20 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1-(2-Methyl-4-(2-methylphenylazo)phenylazo)-2-naphthol 85-83-6	readily biodegradable	anaerobic	100 %	2 d	OECD 301 A - F

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Toluene 108-88-3	90	3 d		Leuciscus idus melanotus	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
1-(2-Methyl-4-(2-methylphenylazo)phenylazo)-2-naphthol 85-83-6	2,9 - 11			not specified	not specified

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Toluene 108-88-3	2,73	20 °C	EU Method A.8 (Partition Coefficient)
1-(2-Methyl-4-(2-methylphenylazo)phenylazo)-2-naphthol 85-83-6	8,72		QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Toluene 108-88-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1-(2-Methyl-4-(2-methylphenylazo)phenylazo)-2-naphthol 85-83-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

The product contains organic solvents which are insoluble in water. According to the requirements of the ATV regulations for the discharge of wastewater from commercial and industrial plant, organic solvents which are immiscible with water can only be discharged to an extent which corresponds to their solubility in water. The local discharge regulations take precedence.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080111

SECTION 14: Transport information
--

14.1. UN number or ID number

ADR	1139
RID	1139
ADN	1139
IMDG	1139
IATA	1139

14.2. UN proper shipping name

ADR	COATING SOLUTION
RID	COATING SOLUTION
ADN	COATING SOLUTION
IMDG	COATING SOLUTION
IATA	Coating solution

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	92,4 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Great Britain):

Remarks	Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, e.g COSHH Essentials. EH40 Occupational Exposure Limits Chemicals (Hazard Information & Packaging for Supply) Regulations. The Personnel Protective Equipment at Work Regulations. The Carriage of Dangerous Goods by Road Regulations. The Health & Safety at Work Act 1974. (Note: Use latest editions/amendments of above referenced documents.)
---------	--

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.