



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK 2402

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Adhesives

**Uses advised against** Consumer use; Adhesive, Paint, Aerosol, Adhesives or spray paint shall not be placed on the market containing above substance equal to or greater than 0.1% where supplied to the general public. Professional cleaning activities with Aprotic Polar Solvents are not supported

**Reason why uses advised against** Restricted substance per REACH Annex XVII Use advised against in Chemical Safety Assessment per REACH Annex I point 7 2.3

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

<b>Skin corrosion/irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 2 - (H319)
<b>Respiratory sensitisation</b>	Category 1 - (H334)
<b>Skin sensitisation</b>	Category 1 - (H317)
<b>Carcinogenicity</b>	Category 2 - (H351)
<b>Reproductive toxicity</b>	Category 2 - (H361)
<b>Specific target organ toxicity — single exposure</b>	Category 3 - (H335, H336)
Category 3 Respiratory irritation, Narcotic effects	
<b>Specific target organ toxicity — repeated exposure</b>	Category 2 - (H373)
<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
<b>Flammable liquids</b>	Category 2 - (H225)

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

## 2.2. Label elements

Contains Methylene chloride; Methyl ethyl ketone; Diphenylmethane-diisocyanate, isomers and homologues; Toluene



**Signal word**  
Danger

### **Hazard statements**

H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.  
H361d - Suspected of damaging the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.  
H225 - Highly flammable liquid and vapour.

### **Precautionary Statements - EU (§28, 1272/2008)**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P354 + P338 - IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor  
P391 - Collect spillage  
P370 + P378 - In case of fire: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam to extinguish  
P403 + P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/ container to an approved waste disposal plant

### **Special provisions concerning the labelling of certain mixtures**

Reserved for industrial and professional use. As from 24 August 2023 adequate training is required before industrial or professional use.

### **Additional information**

This product requires tactile warnings if supplied to the general public.

## 2.3. Other hazards

Harmful to aquatic life. In use, may form flammable/explosive vapour-air mixture.

### **PBT & vPvB**

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

## 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Methylene chloride	200-838-9 (602-004-00-3)	75-09-2	40 - <80	STOT SE 3 (H335) STOT SE 3 (H336) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Carc. 2 (H351)	-	01-2119480404-41-XXXX
Methyl ethyl ketone	201-159-0 (606-002-00-3)	78-93-3	10 - <20	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119457290-43-XXXX
Diphenylmethane-diisocyanate, isomers and homologues	618-498-9	9016-87-9	10 - <20	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	[7]
Toluene	203-625-9 (601-021-00-3)	108-88-3	5 - <10	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225)	-	01-2119471310-51-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic	-	01-2119475515-33-xxxx

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

				2 (H411) Flam. Liq. 2 (H225)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	RR-100242-2	1 - <5	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)	-	01-2119484651- 34-XXXX
Acetone	200-662-2 (606-001-00- 8)	67-64-1	1 - <5	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119471330- 49-XXXX
Zinc oxide	215-222-5 (030-013-00- 7)	1314-13-2	0.1 - <0.5	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	01-2119463881- 32-XXXX
Rosin	232-475-7 (650-015-00- 7)	8050-09-7	0.1 - <0.3	Skin Sens. 1 (H317)	-	01-2119480418- 32-XXXX
Maleic anhydride	203-571-6 (607-096-00- 9)	108-31-6	0.01 - < 0.05	Acute Tox. 4 (H302) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Resp. Sens. 1 (H334) Skin Sens. 1A (H317) STOT RE 1 (H372) (EUH071)	Skin Sens. 1A :: C>=0.001%	01-2119472428- 31-XXXX

*NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration*

## **Full text of H- and EUH-phrases: see section 16**

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

---

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
<b>Inhalation</b>	May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical attention.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

## 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
<b>Effects of Exposure</b>	No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam.
<b>Unsuitable extinguishing media</b>	No information available.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitiser. May cause sensitisation by inhalation. May cause sensitisation by skin contact.
---	--

<b>Hazardous combustion products</b>	Carbon oxides. Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). Hydrocarbons.
--------------------------------------	--

### 5.3. Advice for firefighters

<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
<b>Other information</b>	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
<b>For emergency responders</b>	Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

### 6.3. Methods and material for containment and cleaning up

<b>Methods for containment</b>	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
<b>Methods for cleaning up</b>	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
<b>Prevention of secondary hazards</b>	Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

<b>Reference to other sections</b>	See section 8 for more information. See section 13 for more information.
------------------------------------	--

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

<b>Advice on safe handling</b>	Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and shoes.
<b>General hygiene considerations</b>	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

### 7.2. Conditions for safe storage, including any incompatibilities

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

**Recommended storage temperature** Keep at temperatures between 5 and 25 °C.

## 7.3. Specific end use(s)

**Specific use(s)**  
Adhesives.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Methylene chloride 75-09-2	TWA: 353 mg/m <sup>3</sup> TWA: 100 ppm STEL: 706 mg/m <sup>3</sup> STEL: 200 ppm *	TWA: 353 mg/m <sup>3</sup> TWA: 100 ppm STEL: 200 ppm STEL: 706 mg/m <sup>3</sup> Sk*
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m <sup>3</sup> STEL: 300 ppm STEL: 900 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 600 mg/m <sup>3</sup> STEL: 300 ppm STEL: 899 mg/m <sup>3</sup> Sk*
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	-	TWA: 0.02 mg/m <sup>3</sup> STEL: 0.07 mg/m <sup>3</sup> SEN; as -NCO
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 191 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup> STEL: 1500 ppm STEL: 3620 mg/m <sup>3</sup>
4,4'-Methylenediphenyl diisocyanate 101-68-8	-	TWA: 0.02 mg/m <sup>3</sup> STEL: 0.07 mg/m <sup>3</sup> Sen+
Rosin 8050-09-7	-	TWA: 0.05 mg/m <sup>3</sup> STEL: 0.15 mg/m <sup>3</sup> Sen+
Magnesium oxide (MgO) 1309-48-4	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Maleic anhydride 108-31-6	-	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup> Sen+

Chemical name	European Union	Ireland	United Kingdom
Methylene chloride	-	4 % hemoglobin (blood -	30 ppm end-tidal breath

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

75-09-2		Carboxyhemoglobin measure at end of shift 0.3 mg/L (urine - Methylene chloride measure at end of shift) 1 mg/L (blood - Methylene chloride measure at end of shift)	
Methyl ethyl ketone 78-93-3	-	70 µmol/L (urine - Butan-2-one post shift)	70 µmol/L urine
Toluene 108-88-3	-	0.02 mg/L (blood - Toluene prior to last shift of workweek) 0.03 mg/L (urine - Toluene end of shift) 0.3 mg/g Creatinine (urine - o-Cresol end of shift)	-
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-
4,4'-Methylenediphenyl diisocyanate 101-68-8	-	1 µmol/mol Creatinine (urine - urinary Diamine post task)	-

**Derived No Effect Level (DNEL)**      No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>Methylene chloride (75-09-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Inhalation	706 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	4750 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	353 mg/m <sup>3</sup>	

<b>Methyl ethyl ketone (78-93-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m <sup>3</sup>	

<b>Toluene (108-88-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	384 mg/kg bw/d	
Long term Systemic health effects Local health effects worker	Inhalation	192 mg/m <sup>3</sup>	
Short term Systemic health effects worker	Inhalation	384 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	192 mg/m <sup>3</sup>	



# SAFETY DATA SHEET

**BOSTIK 2402**

**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024

**Revision Number** 1.02

worker Short term Local health effects	Inhalation	384 mg/m <sup>3</sup>	
--	------------	-----------------------	--

## Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d	

## Acetone (67-64-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Dermal	186 mg/kg bw/d	
worker Short term Local health effects	Inhalation	2420 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	1210 mg/m <sup>3</sup>	

## Zinc oxide (1314-13-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	5 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	0.5 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	83 mg/kg bw/d	

## Rosin (8050-09-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	2131 mg/kg bw/d	

## Maleic anhydride (108-31-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	0.4 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	0.8 mg/m <sup>3</sup>	
worker	Inhalation	0.4 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

Long term Local health effects			
worker Short term Local health effects	Inhalation	0.8 mg/m <sup>3</sup>	

## Derived No Effect Level (DNEL) Methylene chloride (75-09-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Inhalation	353 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	2395 mg/kg bw/d	
Consumer Long term Local health effects	Oral	0.06 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	88.3 mg/m <sup>3</sup>	

## Methyl ethyl ketone (78-93-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m <sup>3</sup>	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	

## Toluene (108-88-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	56.5 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	226 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	56 mg/m <sup>3</sup>	
Consumer Local health effects Short term	Inhalation	226 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	226 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	8.13 mg/kg bw/d	

## Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	447 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

## Acetone (67-64-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

## Zinc oxide (1314-13-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	2.5 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	83 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.83 mg/kg bw/d	

## Rosin (8050-09-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	1065 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	1065 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

## Predicted No Effect Concentration (PNEC)

### Methylene chloride (75-09-2)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.54 mg/l
Freshwater sediment	4.47 mg/kg dry weight
Marine water	0.194 mg/kg dry weight
Marine sediment	1.61 mg/kg dry weight
Soil	0.583 mg/kg dry weight

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

<b>Methyl ethyl ketone (78-93-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

<b>Toluene (108-88-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.68 mg/l
Marine water	0.68 mg/l
Sewage treatment plant	13.61 mg/l
Freshwater sediment	16.39 mg/kg dry weight
Marine sediment	16.39 mg/kg dry weight
Soil	2.89 mg/kg dry weight

<b>Acetone (67-64-1)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

<b>Zinc oxide (1314-13-2)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0206 mg/l
Marine water	0.0061 mg/l
Freshwater sediment	235.6 mg/kg dry weight
Marine sediment	113 mg/kg dry weight
Soil	106.8 mg/kg dry weight
Microorganisms in sewage treatment	0.1 mg/l

<b>Rosin (8050-09-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.002 mg/l
Marine water	0 mg/l
Sewage treatment plant	1000 mg/l
Freshwater sediment	0.007 mg/l
Marine sediment	0.001 mg/l

<b>Maleic anhydride (108-31-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Microorganisms in sewage treatment	44.6 mg/l
Freshwater sediment	0.334 mg/kg dry weight
Marine water	0.033 mg/kg dry weight
Soil	0.042 mg/kg dry weight

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

### Personal protective equipment

#### Eye/face protection

Tight sealing safety goggles. Face protection shield.

#### Hand protection

Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

#### Skin and body protection

Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

**Respiratory protection** clothing.  
In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	
<b>Appearance</b>	Liquid	
<b>Colour</b>	Amber Off-white	
<b>Odour</b>	Solvent.	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	>= 48 °C	
<b>Flammability</b>	No data available	Flammable liquid
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	<= -20 °C	CC (closed cup)
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	> 100 mm <sup>2</sup> /s	@ 40°C
<b>Dynamic viscosity</b>	2250 - 2750 mPa s	@ 23 °C
<b>Water solubility</b>	Insoluble in water.	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	<110 kPa	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Density</b>	0.9 g/cm <sup>3</sup>	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

**Solid content (%)** >= 22

**VOC content** No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** No information available.

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

## 10.2. Chemical stability

**Stability** Stable under normal conditions.

### **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** Yes.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

## 10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks.

## 10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** Carbon oxides.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. May cause additional effects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Acute toxicity

#### **Numerical measures of toxicity**

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	13.60 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methylene chloride	>2000 mg/kg (Rattus)	> 2000 mg/kg ( Rat )	>86 mg/L (Rattus) 4 h
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Diphenylmethane-diisocyanate, isomers and homologues	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus)	1.5 mg/L (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m <sup>3</sup> (vapour) (rat OECD 403)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Zinc oxide	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 (4h) >5.7 mg/l
Rosin	>2000 mg/Kg (Rattus)	> 2500 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h
Maleic anhydride	LD50 = 1090 mg/kg (Rattus) OECD 401	= 2620 mg/kg (Oryctolagus cuniculus)	>4.35 mg/L (Rattus) 1 h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Skin corrosion/irritation

Classification based on data available for ingredients. Causes skin irritation.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

### Serious eye damage/eye irritation

Classification based on data available for ingredients. Causes serious eye irritation.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

Acute Eye Irritation/Corrosion					
--------------------------------	--	--	--	--	--

**Respiratory or skin sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

Toluene (108-88-3)

Method	Species	Exposure route	Results
Regulation (EC) No. 440/2008, Annex, B.6 (Maximisation test)	Guinea pig		No sensitisation responses were observed

Acetone (67-64-1)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser

Maleic anhydride (108-31-6)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Injection	sensitising
Not available	Rat	Inhalation	sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information  
Toluene (108-88-3)

Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic
OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Mouse	Not mutagenic

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information  
Methylene chloride (75-09-2)

Method	Species	Results
OECD 453	Rat	Carcinogenic

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Results
OECD Test No. 453: Combined Chronic	Rat	Carcinogenic



# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

Toxicity/Carcinogenicity Studies		
----------------------------------	--	--

Chemical name	European Union
Methylene chloride	Carc. 2

**Reproductive toxicity** Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Toluene	Repr. 2

Toluene (108-88-3)

Method	Species	Results
OECD 407	in vivo	reproductive toxicant

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

H373 - May cause damage to the following organs through prolonged or repeated exposure: Liver.

H373 - May cause damage to the following organs through prolonged or repeated exposure if inhaled: lungs;inhalation.

Methylene chloride (75-09-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 453	Rat	Inhalation	500 ppm	600 days	NOAEC 200 ppm

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapour			NOAEL: 1.131 mg/l

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Methylene chloride	EC50: >500mg/L	LC50: =193mg/L	EC50 = 1 mg/L	EC50 48 h = 27		

# SAFETY DATA SHEET

**BOSTIK 2402**

**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024

**Revision Number** 1.02

75-09-2	(72h, Pseudokirchneriella subcapitata) EC50: >500mg/L (96h, Pseudokirchneriella subcapitata)	(96h, Lepomis macrochirus) LC50: 140.8 - 277.8mg/L (96h, Pimephales promelas) LC50: 262 - 855mg/L (96h, Pimephales promelas)	24 h EC50 = 2.88 mg/L 15 min	mg/L (Daphnia magna)		
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna		
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane RR-100242-2	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h)= 31.9 mg/l (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h = 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L (Danio rerio)	-	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)	1	1
Rosin 8050-09-7	EC50: =400mg/L (72h, Desmodesmus subspicatus)	LC50 (96h) >10mg/L (Danio rerio)	EC50 = 31.5 mg/L 30 min	EC50 48 h >100 mg/L (Daphnia magna)		
Maleic anhydride 108-31-6	EC50: =29mg/L (72h, Desmodesmus subspicatus)	LC50 (96h) = 75 mg/L (Oncorhynchus mykiss)	-	EC50: =84mg/L (24h, Daphnia magna)		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Methyl ethyl ketone (78-93-3)

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

Zinc oxide (1314-13-2)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Methylene chloride	1.25
Methyl ethyl ketone	0.3
Toluene	2.73
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
Acetone	-0.24
Rosin	7.7
Maleic anhydride	-2.61

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Methylene chloride	The substance is not PBT / vPvB
Methyl ethyl ketone	The substance is not PBT / vPvB
Toluene	The substance is not PBT / vPvB
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
Hydrocarbons, C6, isoalkanes, <5% n-hexane	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB
Zinc oxide	The substance is not PBT / vPvB

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

Rosin	The substance is not PBT / vPvB
Maleic anhydride	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

### Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (E)
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None
Classification code	F1
Tunnel restriction code	(E)
Limited quantity (LQ)	5 L

### IMDG

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1133, Adhesives, 3, III, (-20°C c.c.)
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	223, 955
Limited Quantity (LQ)	5 L

# SAFETY DATA SHEET

BOSTIK 2402  
Supersedes Date: 29-Jan-2024

Revision date 29-Jan-2024  
Revision Number 1.02

EmS-No. F-E, S-D

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1133  
14.2 UN proper shipping name Adhesives  
14.3 Transport hazard class(es) 3  
14.4 Packing group III  
Description UN1133, Adhesives, 3, III  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions A3  
Limited quantity (LQ) 10 L  
ERG Code 3L

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Methylene chloride	75-09-2	59. 75.
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9	56 74.
Toluene	108-88-3	48.
Diisocyanates	--	74

**48** . Reserved for industrial and professional use. Adhesives or spray paint shall not be placed on the market containing above substance equal to or greater than 0.1% where supplied to the general public. **56** . If product supplied to the general public with substance  $\geq 0.1\%$ , then gloves must be provided with the product. **74** If product supplied to the industrial or professional users with total monomeric diisocyanates  $\geq 0.1\%$ , then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

##### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

## **Dangerous substance category per Seveso Directive (2012/18/EU)**

P5a - FLAMMABLE LIQUIDS  
P5b - FLAMMABLE LIQUIDS  
P5c - FLAMMABLE LIQUIDS

## **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

## **Persistent Organic Pollutants**

Not applicable

## **REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**

This product contains

<b>Chemical name</b>	<b>Reporting of suspicious transactions, disappearances and thefts</b>	<b>Restricted</b>
Acetone - 67-64-1	X	

## **National regulations**

### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

EUH066 - Repeated exposure may cause skin dryness or cracking  
EUH071 - Corrosive to the respiratory tract  
H225 - Highly flammable liquid and vapour  
H302 - Harmful if swallowed  
H304 - May be fatal if swallowed and enters airways  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H351 - Suspected of causing cancer  
H361d - Suspected of damaging the unborn child  
H372 - Causes damage to organs through prolonged or repeated exposure  
H373 - May cause damage to organs through prolonged or repeated exposure  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H411 - Toxic to aquatic life with long lasting effects  
H412 - Harmful to aquatic life with long lasting effects

#### **Legend**

# SAFETY DATA SHEET

**BOSTIK 2402**  
**Supersedes Date:** 29-Jan-2024

**Revision date** 29-Jan-2024  
**Revision Number** 1.02

---

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 29-Jan-2024  
**Indication of changes**

**Revision note** Not applicable.  
**Training Advice** Provide adequate information, instruction, and training for operator AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE INDUSTRIAL OR PROFESSIONAL USE For further information, please contact:  
<https://www.safeusediisocyanates.eu/>  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**