Revision date: 25/04/2017 Revision: 19 Supersedes date: 14/05/2015

# **ITW** Engineered Polymers

# SAFETY DATA SHEET **5 MINUTE EPOXY RESIN**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

**Product name 5 MINUTE EPOXY RESIN** 

Product number X0039

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier

**ITW Engineered Polymers** 

Bay 150

Shannon Industrial Estate

Shannon Co. Clare

+353 (0)61 471 299 +353 (0)61 471 285 mail@itwep.com

1.4. Emergency telephone number

+44(0)1235 239 670 (24h) **Emergency telephone** 

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Chronic 2 - H411

Classification (67/548/EEC or Xi;R36/38. R43. N;R51/53.

1999/45/EC)

Human health The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive

individuals.

2.2. Label elements

**Pictogram** 





Signal word Warning Revision date: 25/04/2017 Revision: 19 Supersedes date: 14/05/2015

## **5 MINUTE EPOXY RESIN**

Hazard statements H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

Supplemental label

information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

**Contains** EPOXY RESIN (Number average MW <= 700)

Supplementary precautionary

statements

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/ container in accordance with national regulations.

## 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

# EPOXY RESIN (Number average MW <= 700)

60-100%

CAS number: 25068-38-6 EC number: 500-033-5 REACH registration number: 01-

2119456619-26-0000

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 R43 Xi:R36/38 N:R51/53

Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General information Avoid contact with eyes. In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head

should be kept low so that vomit does not enter the lungs. Get medical attention.

Skin contact Remove affected person from source of contamination. Wash skin thoroughly with soap and

water. Get medical attention if irritation persists after washing.

Revision date: 25/04/2017 Revision: 19 Supersedes date: 14/05/2015

## **5 MINUTE EPOXY RESIN**

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if irritation persists after washing.

# 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor 
No specific recommendations. If in doubt, get medical attention promptly.

## SECTION 5: Firefighting measures

# 5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Irritating gases or vapours.

## 5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Control run-off water by

containing and keeping it out of sewers and watercourses.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

## SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this

safety data sheet. Provide adequate ventilation.

## 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled

discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste

disposal containers and seal securely. Containers with collected spillage must be properly

labelled with correct contents and hazard symbol.

# 6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

#### SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Use only in well-ventilated areas. Handle and open container with care. Keep away from heat,

sparks and open flame. Good personal hygiene procedures should be implemented.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away

from incompatible materials (see Section 10).

# 7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure Controls/personal protection

## 8.1. Control parameters

Ingredient comments WEL = Workplace Exposure Limits

## EPOXY RESIN (Number average MW <= 700 ) (CAS: 25068-38-6)

**DNEL**Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day
Workers - Inhalation; Short term systemic effects: 12.25 mg/m³

# 8.2. Exposure controls

#### Protective equipment









Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Rubber or plastic. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body

protection

Avoid contact with skin.

Hygiene measures Provide eyewash station. Keep away from food, drink and animal feeding stuffs. Good

personal hygiene procedures should be implemented. Wash hands and any other

contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

Promptly remove any clothing that becomes wet or contaminated.

**Respiratory protection** If ventilation is inadequate, suitable resp

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Wear a respirator fitted with the following cartridge: Gas filter,

type A2.

## **SECTION 9: Physical and Chemical Properties**

# 9.1. Information on basic physical and chemical properties

Appearance Liquid.

**Colour** Colourless to pale yellow.

Odour Slight.

pH (concentrated solution): 7 @ 20 °C

Melting point n/d°C

Initial boiling point and range > 200°C @

Flash point > 150°C

Revision date: 25/04/2017 Revision: 19 Supersedes date: 14/05/2015

## **5 MINUTE EPOXY RESIN**

Vapour pressure <0.01 Pa @ °C

Relative density 1.147@ @ 20 °C °C

Solubility(ies) Slightly soluble in water.

Partition coefficient : >3

Auto-ignition temperature >300°C

**Viscosity** 12-14 Pa s @ 25°C

9.2. Other information

Other information Not available.

# SECTION 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity** Strong oxidising agents. Acids. Amines.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not available.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong oxidising agents. Strong acids. Amines.

# 10.6. Hazardous decomposition products

Hazardous decomposition

on

Does not decompose when used and stored as recommended.

products

# SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Skin contact Irritating to skin. May cause sensitisation by skin contact. The product contains a small

amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive

individuals.

**Eye contact** Irritating to eyes.

Acute and chronic health

hazards

The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive

individuals.

Route of entry Inhalation Ingestion. Skin and/or eye contact

# SECTION 12: Ecological Information

**Ecotoxicity** Avoid releasing into the environment. Dangerous for the environment. May cause long-term

adverse effects in the aquatic environment.

12.1. Toxicity

**Toxicity** Very toxic to aquatic organisms.

#### 12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential**The product contains potentially bioaccumulating substances.

Partition coefficient : >3

12.4. Mobility in soil

**Mobility** Do not discharge into drains or watercourses or onto the ground.

## 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be

considered.

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

**Waste class** 08 04 99

# SECTION 14: Transport information

**General** No other information known.

14.1. UN number

UN No. (ADR/RID) 3082 UN No. (IMDG) 3082 UN No. (ICAO) 3082

# 14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700))

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700 ))

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700))

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700))

# 14.3. Transport hazard class(es)

ADR/RID class 9
ADR/RID label 9
IMDG class 9

ICAO class/division 9

Transport labels



#### 14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

# 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



# 14.6. Special precautions for user

**EmS** F-A, S-F

Emergency Action Code •3Z

Hazard Identification Number 90

(ADR/RID)

Tunnel restriction code (E)

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** No information required. **Annex II of MARPOL 73/78** 

Alliex II of MAIX OL 73/70

and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

# SECTION 16: Other information

Revision date 25/04/2017

Revision 19

Supersedes date 14/05/2015

Risk phrases in full R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.