

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Elmotherm® 009-0051

1.2 Relevant identified uses of the substance or mixture and uses advised against

Type of Application (Use) : Insulating varnish

Recommended restrictions : For industrial use only.
on use

1.3 Details of the supplier of the safety data sheet

Company : ELANTAS Europe S.r.l.
Strada Antolini 1
43044 Collecchio
Italy

Telephone : +3907363081

Telefax : +390736402746

E-mail address of person : msds.elantas.europe@altana.com
responsible for the SDS

1.4 Emergency telephone number

+44 1235 239670 (All languages)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006




Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 + H332 Harmful in contact with skin or if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Xylene, mixture of isomers

4-methylpentan-2-one

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**Elmotherm® 009-0051**Version
6.1 SDB_GBRevision Date:
06.07.2023Date of last issue: 11.10.2022
Date of first issue: 05.01.2013**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

Chemical nature : Acrylic polymer

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Xylene, mixture of isomers	1330-20-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 50 - <= 100
4-methylpentan-2-one	108-10-1 203-550-1 606-004-00-4 01-2119473980-30	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 Carc. 2; H351 STOT SE 3; H336 (Central nervous system) EUH066	>= 7 - < 10
ethylbenzene	100-41-4 202-849-4 601-023-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304	>= 7 - < 10
toluene	108-88-3 203-625-9 601-021-00-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
Reaction mass of ethyl benzene and xylene	Not Assigned 01-2119539452-40	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 3

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Do not leave the victim unattended.
Consult a physician.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- If inhaled : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
Oxygen or artificial respiration if needed.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off immediately with plenty of water for at least 15 minutes.
Use a mild soap if available.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Consult a physician.
Keep eye wide open while rinsing.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Gently wipe or rinse the inside of the mouth with water.
Call a physician immediately.
Never give anything by mouth to an unconscious person.
Do not give milk or alcoholic beverages.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Nausea
Vomiting
Central nervous system depression

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Warning: water promotes the spread of fire.
Cool containers/tanks with water spray.
Burning produces irritant fumes.
The pressure in sealed containers can increase under the influence of heat.
Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Local authorities should be advised if significant spillages cannot be contained.
Retain and dispose of contaminated wash water.
Prevent spreading over a wide area (e.g. by containment or oil barriers).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Sweep up and shovel into suitable containers for disposal.
Clean contaminated surface thoroughly.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms. Ensure all equipment is electrically grounded before beginning transfer operations. Avoid inhalation, ingestion and contact with skin and eyes. Keep away from fire, sparks and heated surfaces. Keep container closed when not in use.
- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition.
- Hygiene measures : Store personal protection equipment in a clean location away from the work area. Keep working clothes separately.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Do not store together with explosives, gases, oxidizing solids, products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive products.

7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Xylene, mixture of isomers	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 220 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm 441 mg/m ³	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**Elmotherm® 009-0051**Version
6.1 SDB_GBRevision Date:
06.07.2023Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
4-methylpentan-2-one	108-10-1	TWA	20 ppm 83 mg/m ³	2000/39/EC
		Further information: Indicative		
		STEL	50 ppm 208 mg/m ³	2000/39/EC
		Further information: Indicative		
		TWA	50 ppm 208 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm 416 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	200 ppm 884 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	100 ppm 441 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	125 ppm 552 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
toluene	108-88-3	TWA	50 ppm 192 mg/m ³	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
		STEL	100 ppm 384 mg/m ³	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
		TWA	50 ppm 191 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm 384 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned sub-		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene, mixture of isomers	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
4-methylpentan-2-one	108-10-1	4-methylpentan-2-one: 20 micromol per litre (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Xylene, mixture of isomers	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
	Workers	Inhalation	Acute local effects	442 mg/m ³
	Workers	Dermal	Long-term systemic effects	212 mg/kg
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m ³
	Consumers	Dermal	Long-term systemic effects	125 mg/kg
	Consumers	Oral	Long-term systemic effects	1,5 mg/kg
	Consumers	Inhalation	Acute local effects	260 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Xylene, mixture of isomers	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Soil	2,31 mg/kg
	Sewage treatment plant	6,58 mg/l
	Intermittent releases	0,327 mg/l

8.2 Exposure controls

Engineering measures

Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Ensure that eyewash stations and safety showers are close to the workstation location.
Do not wear contact lenses.

Hand protection

Material : Polyvinyl alcohol or nitrile- butyl-rubber gloves

Material : Protective gloves complying with EN 374.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Remarks	:	Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin and body protection	:	Workers should wear antistatic footwear. Remove and wash contaminated clothing before re-use. Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	In the case of vapour formation use a respirator with an approved filter. Equipment should conform to EN 14387
Filter type	:	Organic vapour type (A)
Protective measures	:	Ensure that eye flushing systems and safety showers are located close to the working place. Do not wear contact lenses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	light yellow
Odour	:	characteristic
Melting point/freezing point	:	lower -15 °C
Boiling point/boiling range	:	117 - 139 °C
Upper explosion limit / Upper flammability limit	:	7,5 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Flash point	:	14 °C
Auto-ignition temperature	:	not determined
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	200 - 350 cPs (25 °C)
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	not determined
Density	:	0,91 g/ml (23 °C)
Bulk density	:	not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Relative vapour density : upper 1
(Air = 1.0)

9.2 Other information

Self-ignition : 460 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Keep away from oxidizing agents, strongly acid or alkaline materials and amines.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents
Strong reducing agents
Alkali metals
Alkaline earth metals

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.
Hazardous decomposition products : Stable under recommended storage conditions.
Heating can release vapours which can be ignited.
Burning produces noxious and toxic fumes.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Acute toxicity estimate: 14,94 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 1.978 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Method: Calculation method

Acute toxicity (other routes of administration)

Remarks: No data available

Components:

Xylene, mixture of isomers:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 4.200 mg/kg
GLP: No information available.

Reaction mass of ethyl benzene and xylene:

Acute oral toxicity : LD50 (Rat, male): 3.523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Skin corrosion/irritation

Product:

Remarks : No data available

Components:

4-methylpentan-2-one:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Product:

Remarks : No data available

Respiratory or skin sensitisation

Product:

Remarks : No data available

Components:

Reaction mass of ethyl benzene and xylene:

Test Type : Mouse Local Lymph Node assay (LLNA)
Exposure routes : Dermal
Species : Mouse
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Product:

Remarks : No data available

STOT - repeated exposure

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

Aspiration toxicity

Components:

Reaction mass of ethyl benzene and xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

Xylene, mixture of isomers:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 24 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia sp. (water flea)

NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Daphnia sp. (water flea)

4-methylpentan-2-one:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 179 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

GLP: yes

Reaction mass of ethyl benzene and xylene:

Toxicity to fish : LC50 (Fish): 2,6 mg/l
End point: mortality
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: Immobilization

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to fish (Chronic toxicity) : > 1,3 mg/l
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
End point: Reproduction
Exposure time: 7 d
Species: Daphnia sp. (water flea)

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Xylene, mixture of isomers:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

4-methylpentan-2-one:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

Reaction mass of ethyl benzene and xylene:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

Xylene, mixture of isomers:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Exposure time: 56 d
Bioconcentration factor (BCF): 25,9
GLP: no

Partition coefficient: n-
octanol/water : Pow: 3,2 (20 °C)
pH: 7

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
The product should not be allowed to enter drains, water courses or the soil.
Container hazardous when empty.
Dispose of in accordance with local regulations.
Can be incinerated, when in compliance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR/RID/ADN : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

ADR/RID/ADN : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR/RID/ADN
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : D/E

IMDG
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Remarks : IMDG Code segregation group - none

IATA (Cargo)
Packing instruction (cargo aircraft) : 364
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADR/RID/ADN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version	Revision Date:	Date of last issue: 11.10.2022
6.1 SDB_GB	06.07.2023	Date of first issue: 05.01.2013

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : The transport of dangerous goods, including their loading and unloading, must be done by people who received the necessary training required by Modal Regulations.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

toluene (Number on list: 48)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list: 3

toluene (Number on list: 48)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

: Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors : Not applicable

Seveso III: Directive 2012/18/EU of the Euro- P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Seveso III Directive (2012/18/EU) implemented P5c FLAMMABLE LIQUIDS
by Control of Major Accident Hazards Regulations 2015 (COMAH)

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer.
H361d	: Suspected of damaging the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Classification of the mixture:

Flam. Liq. 2	H225
Acute Tox. 4	H332
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

Elmotherm® 009-0051

Version
6.1 SDB_GB

Revision Date:
06.07.2023

Date of last issue: 11.10.2022
Date of first issue: 05.01.2013

GB / EN