

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Elmotherm® VA63 SPRAY

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Type of Application (Use) : Spray insulating varnish

Recommended restrictions : For industrial use only.  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : ELANTAS Europe S.r.l.  
Strada Antolini 1  
43044 Collecchio  
Italy

Telephone : +3907363081

Telefax : +390736402746

E-mail address of person : msds.elantas.europe@altana.com  
responsible for the SDS

#### 1.4 Emergency telephone number

+44 1235 239670 (All languages)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust or mist.  
P280 Wear protective gloves/ eye protection/ face protection.

### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Hazardous components which must be listed on the label:

acetone

Xylene, mixture of isomers

cobalt bis(2-ethylhexanoate)

octhilinone (ISO)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Elmotherm® VA63 SPRAY**Version  
8.0 SDB\_GBRevision Date:  
17.11.2023Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

Chemical nature : Alkyd Resin Solution

**Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 30
Hydrocarbons, C3-4; Petroleum gas	68476-40-4 270-681-9 649-199-00-1	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	>= 12,5 - < 20
Xylene, mixture of isomers	1330-20-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 12,5
Reaction mass of ethyl benzene and xylene	Not Assigned 01-2119539452-40	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 12,5
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319  Acute toxicity estimate  Acute oral toxicity: 1.200 mg/kg 1.200 mg/kg Acute inhalation toxicity (vapour): 3 mg/l	>= 1 - < 3
cobalt bis(2-ethylhexanoate)	136-52-7	Eye Irrit. 2; H319	>= 0,1 - < 0,25

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

	205-250-6 01-2119524678-29	Skin Sens. 1A; H317 Repr. 1B; H360 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	
octhilinone (ISO)	26530-20-1 247-761-7 613-112-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 100 100  M-Factor (Chronic aquatic toxicity): 100 100  specific concentration limit Skin Sens. 1A; H317 >= 0,0015 % Skin Sens. 1A; H317 >= 0,0015 %  Acute toxicity esti- mate  Acute oral toxicity: 125 mg/kg 125 mg/kg Acute inhalation tox- icity (dust/mist): 0,27 mg/l 0,27 mg/l Acute dermal toxicity: 311 mg/kg 311 mg/kg	>= 0,0015 - < 0,0025
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8	Flam. Gas 1; H220 Press. Gas	>= 30 - < 50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Show this safety data sheet to the doctor in attendance.  
Treat symptomatically.  
Consult a physician.  
Do not leave the victim unattended.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.  
Avoid inhalation, ingestion and contact with skin and eyes.
- If inhaled : Move to fresh air.  
If symptoms persist, call a physician.  
Oxygen or artificial respiration if needed.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off immediately with plenty of water for at least 15 minutes.  
Use a mild soap if available.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.  
Keep eye wide open while rinsing.
- If swallowed : Call a physician immediately.  
Gently wipe or rinse the inside of the mouth with water.  
Do not induce vomiting without medical advice.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Nausea  
Central nervous system depression  
Drowsiness

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

Keep containers and surroundings cool with water spray.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : The pressure in sealed containers can increase under the influence of heat.  
Warning: water promotes the spread of fire.  
Burning produces irritant fumes.  
Exposure to decomposition products may be a hazard to health.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.  
Further information : Cool containers/tanks with water spray.  
Keep away from heat and sources of ignition.  
Prevent fire extinguishing water from contaminating surface water or the ground water system.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation.  
Keep people away from and upwind of spill/leak.  
Refer to protective measures listed in sections 7 and 8.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Do not allow material to contaminate ground water system.  
Prevent product from entering drains.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
Sweep up and shovel into suitable containers for disposal.  
Clean contaminated surface thoroughly.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

- Advice on safe handling : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep away from children.  
Operate if possible out of doors or in a well-ventilated place.
- Advice on protection against fire and explosion : Use only in area provided with appropriate exhaust ventilation.
- Hygiene measures : Store personal protection equipment in a clean location away from the work area. Keep working clothes separately.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place.

### 7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m <sup>3</sup>	2000/39/EC
		Further information: Indicative		
		TWA	400 ppm 766 mg/m <sup>3</sup>	GB EH40
		STEL	500 ppm 958 mg/m <sup>3</sup>	GB EH40
acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC
		Further information: Indicative		
		TWA	500 ppm 1.210 mg/m <sup>3</sup>	GB EH40
		STEL	1.500 ppm 3.620 mg/m <sup>3</sup>	GB EH40
Xylene, mixture of isomers	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Elmotherm® VA63 SPRAY**Version  
8.0 SDB\_GBRevision Date:  
17.11.2023Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 123 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 246 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
cobalt bis(2-ethylhexanoate)	136-52-7	TWA	0,1 mg/m <sup>3</sup> (Cobalt)	GB EH40
	Further information: Capable of causing occupational asthma., Capable of causing cancer and/or heritable genetic damage.			

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene, mixture of isomers	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

Substance name	End Use	Exposure routes	Potential health effects	Value
Xylene, mixture of isomers	Workers	Inhalation	Long-term systemic effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	442 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	212 mg/kg
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic	125 mg/kg



**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Elmotherm® VA63 SPRAY**Version  
8.0 SDB\_GBRevision Date:  
17.11.2023Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

			effects	
	Consumers	Oral	Long-term systemic effects	1,5 mg/kg
	Consumers	Inhalation	Acute local effects	260 mg/m3
acetone	Workers	Inhalation	Acute local effects	2420 mg/m3
	Workers	Inhalation	Long-term exposure	1210 mg/m3
	Workers	Skin contact	Long-term exposure	186 mg/kg
	Consumers	Skin contact	Long-term exposure	62 mg/kg
	Consumers	Inhalation	Long-term exposure	200 mg/m3
	Consumers	Ingestion	Long-term exposure	62 mg/kg
2-butoxyethanol	Workers	Skin contact	Acute systemic effects	89 mg/kg
	Workers	Inhalation	Acute systemic effects	135 ppm
	Workers	Inhalation	Acute local effects	50 ppm
	Workers	Skin contact	Long-term systemic effects	75 mg/kg
	Workers	Inhalation	Long-term systemic effects	20 ppm
	Consumers	Skin contact	Acute systemic effects	44,5 mg/kg
	Consumers	Inhalation	Acute systemic effects	426 mg/m3
	Consumers	Ingestion	Acute systemic effects	13,4 mg/kg
	Consumers	Inhalation	Acute local effects	123 mg/m3
	Consumers	Skin contact	Long-term systemic effects	38 mg/kg
	Consumers	Inhalation	Long-term systemic effects	49 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,2 mg/kg

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value
Xylene, mixture of isomers	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Soil	2,31 mg/kg
	Sewage treatment plant	6,58 mg/l
	Intermittent releases	0,327 mg/l
acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg
	Intermittent releases	21 mg/l
2-butoxyethanol	Sewage treatment plant	19,5 mg/l
	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

	Marine sediment	3,46 mg/kg
	Soil	2,8 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
- Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
In the case of dust or aerosol formation use respirator with an approved filter.
- Filter type : Organic vapour type (A)
- Protective measures : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : aerosol
- Colour : dark
- Odour : characteristic
- Melting point/freezing point : lower -15 °C
- Initial boiling point : max. 35 °C
- Flammability : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : not determined
- Lower explosion limit / Lower flammability limit : not determined
- Flash point : Not applicable
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)
- Viscosity  
Viscosity, kinematic : not determined
- Solubility(ies)  
Water solubility : not determined  
Solubility in other solvents : not determined

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

Partition coefficient: n-octanol/water : No data available  
Vapour pressure : No data available  
Density : 0,75 g/cm<sup>3</sup> (20 °C)  
Bulk density : Not applicable  
Relative vapour density : lower 1  
(Air = 1.0)  
Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Self-ignition : No data available  
Heat of combustion : 28 kJ/g  
Sublimation point : Not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Keep away from open flames, hot surfaces and sources of ignition.

### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Strong oxidizing agents  
Strong reducing agents

### 10.6 Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

###### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Remarks: see also section 2.1

Acute inhalation toxicity : Remarks: see also section 2.1

Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Remarks: see also section 2.1

Acute toxicity (other routes of administration) : Remarks: No data available

###### Components:

###### **Xylene, mixture of isomers:**

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 4.200 mg/kg  
GLP: No information available.

###### **Reaction mass of ethyl benzene and xylene:**

Acute oral toxicity : LD50 (Rat, male): 3.523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.

###### **2-butoxyethanol:**

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Test atmosphere: vapour

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

### octhilinone (ISO):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute toxicity estimate: 125 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute toxicity estimate: 0,27 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute toxicity estimate: 311 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

### Skin corrosion/irritation

#### Product:

Remarks : No data available

#### Components:

##### 2-butoxyethanol:

Species : Rabbit  
Result : Skin irritation

### Serious eye damage/eye irritation

#### Product:

Remarks : No data available

#### Components:

##### acetone:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Eye irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

### 2-butoxyethanol:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Eye irritation  
GLP : yes

### Respiratory or skin sensitisation

#### Product:

Remarks : No data available

#### Components:

#### Reaction mass of ethyl benzene and xylene:

Test Type : Mouse Local Lymph Node assay (LLNA)  
Exposure routes : Dermal  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : Does not cause skin sensitisation.

### 2-butoxyethanol:

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

### Germ cell mutagenicity

#### Components:

#### Hydrocarbons, C3-4; Petroleum gas:

Germ cell mutagenicity- Assessment : Classified based on 1,3-butadiene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note K)

### Carcinogenicity

#### Product:

Remarks : No data available

#### Components:

#### Hydrocarbons, C3-4; Petroleum gas:

Carcinogenicity - Assessment : Classified based on 1,3-butadiene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note K)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### STOT - single exposure

#### Product:

Remarks : No data available

### STOT - repeated exposure

#### Product:

Remarks : No data available

### Repeated dose toxicity

#### Product:

Remarks : No data available

### Aspiration toxicity

#### Components:

##### acetone:

No aspiration toxicity classification

### Reaction mass of ethyl benzene and xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

##### Components:

##### **Xylene, mixture of isomers:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l  
Exposure time: 24 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: Daphnia sp. (water flea)

NOEC: 0,96 mg/l  
Exposure time: 7 d  
Species: Daphnia sp. (water flea)

##### **Reaction mass of ethyl benzene and xylene:**

Toxicity to fish : LC50 (Fish): 2,6 mg/l  
End point: mortality  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Test Type: Immobilization

Toxicity to algae/aquatic : ErC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

plants  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to fish (Chronic toxicity) : > 1,3 mg/l  
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l  
End point: Reproduction  
Exposure time: 7 d  
Species: Daphnia sp. (water flea)

### **2-butoxyethanol:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.550 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211

### **octhilinone (ISO):**

M-Factor (Acute aquatic toxicity) : 100

100

M-Factor (Chronic aquatic toxicity) : 100

100

## 12.2 Persistence and degradability

### **Product:**

Biodegradability : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

Physico-chemical removability : Remarks: No data available

### Components:

#### **Xylene, mixture of isomers:**

Biodegradability : Test Type: aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

#### **Reaction mass of ethyl benzene and xylene:**

Biodegradability : Test Type: aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

#### **2-butoxyethanol:**

Biodegradability : Test Type: aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301B

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

### Components:

#### **Xylene, mixture of isomers:**

Bioaccumulation : Species: *Oncorhynchus mykiss* (rainbow trout)  
Exposure time: 56 d  
Bioconcentration factor (BCF): 25,9  
GLP: no

Partition coefficient: n-octanol/water : Pow: 3,2 (20 °C)  
pH: 7

#### **2-butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0,81 (25 °C)  
pH: 7

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with the European Directives on waste and hazardous waste.  
Do not dispose of with domestic refuse.  
Container hazardous when empty.  
The product should not be allowed to enter drains, water courses or the soil.  
Can be incinerated, when in compliance with local regulations.

Contaminated packaging : Offer empty spray cans to an established disposal company.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN : UN 1950  
IMDG : UN 1950  
IATA : UN 1950  
Not permitted for transport

### 14.2 UN proper shipping name

ADR/RID/ADN : AEROSOLS  
IMDG : AEROSOLS  
IATA : AEROSOLS, FLAMMABLE  
Not permitted for transport

### 14.3 Transport hazard class(es)

ADR/RID/ADN : 2.1  
IMDG : 2.1  
IATA (Cargo) : 2.1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

**IATA (Passenger)** : Not permitted for transport

### 14.4 Packing group

#### ADR/RID/ADN

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : D

#### IMDG

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Remarks : IMDG Code segregation group - none

**IATA (Cargo)** : Not permitted for transport

**IATA (Passenger)** : Not permitted for transport

### 14.5 Environmental hazards

#### ADR/RID/ADN

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : The transport of dangerous goods, including their loading and unloading, must be done by people who received the necessary training required by Modal Regulations.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable  
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable  
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable  
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable  
Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

tants (recast)

UK REACH List of substances subject to authorisation (Annex XIV) Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Not applicable

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

Seveso III Directive (2012/18/EU) implemented by Control of Major Accident Hazards Regulations 2015 (COMAH) P3a FLAMMABLE AEROSOLS

### 15.2 Chemical safety assessment

Not applicable

## SECTION 16: Other information

### Full text of H-Statements

H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H311 : Toxic in contact with skin.  
H312 : Harmful in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H331 : Toxic if inhaled.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H360 : May damage fertility or the unborn child.  
H373 : May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.
EUH071	: Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Elmotherm® VA63 SPRAY

Version  
8.0 SDB\_GB

Revision Date:  
17.11.2023

Date of last issue: 26.10.2022  
Date of first issue: 03.01.2013

tative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

GB / EN