

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

**SECTION 1. IDENTIFICATION**

Product name : EpoxyLite® C 6203 Hi Temp Hardener

**Manufacturer or supplier's details**

Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)

E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)

Emergency telephone number : INFOTRAC - 1-800-535-5053

**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Serious eye damage : Category 1

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H350 May cause cancer.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

Precautionary statements : **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear eye protection/ face protection.  
 P280 Wear protective gloves.  
 P281 Use personal protective equipment as required.  
 P285 In case of inadequate ventilation wear respiratory protection.  
**Response:**  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P363 Wash contaminated clothing before reuse.  
**Storage:**  
 P405 Store locked up.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Modified Aromatic Anhydride

**Hazardous components**

Component	CAS-No.	Concentration (%)
Pyromellitic dianhydride	89-32-7	>= 68 - < 69
Crystalline silica	14808-60-7	>= 15 - < 16
Magnesium Silicate Talc (contains no asbestos)	14807-96-6	>= 14 - < 15

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

fibers)		
1,2,4,5-Benzenetetracarboxylic acid	89-05-4	>= 1 - < 2

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
 Avoid dust formation.  
 Avoid breathing dust.  
 Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.  
 Prevent further leakage or spillage if safe to do so.  
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Sweep or vacuum and place into closable container for disposal, avoiding dusting conditions.  
 Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid formation of respirable particles.  
 Do not breathe vapours/dust.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Dispose of rinse water in accordance with local and national regulations.  
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type	Control	Basis
------------	---------	------------	---------	-------

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

		(Form of exposure)	parameters / Permissible concentration	
Crystalline silica	14808-60-7	TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Use with adequate ventilation.  
 All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)  
 This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.  
 Repeated inhalation of such dust may cause lung injury.

**Personal protective equipment**

**Respiratory protection** : In the case of dust or aerosol formation use respirator with an approved filter.  
 Dust safety masks are recommended when the dust concentration is more than 10 mg/m<sup>3</sup>.

**Hand protection**  
**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Eye wash bottle with pure water  
 Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Dust impervious protective suit  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures** : When using do not eat or drink.  
 When using do not smoke.

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: powder
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: Greater than 201 °F (94 °C) Method: Literature Value
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.9048 g/cm <sup>3</sup> (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

Viscosity, kinematic : Greater than 22 mm<sup>2</sup>/s (104 °F (40 °C))**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

Conditions to avoid : No data available

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Acute toxicity****Components:****89-32-7 Pyromellitic dianhydride:**

Acute oral toxicity : LD50 (Mouse): 2.4 mg/kg

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 : Remarks: No data available

**Skin corrosion/irritation****Product:**

Remarks: Extremely corrosive and destructive to tissue.

**Components:****89-32-7 Pyromellitic dianhydride:**

Remarks: No data available

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Components:****89-32-7 Pyromellitic dianhydride:**

Species: Rabbit

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

Result: Severe eye irritation  
 Method: Draize Test

**Respiratory or skin sensitisation**
**Product:**

Remarks: Causes sensitisation.

**Components:**
**89-32-7 Pyromellitic dianhydride:**

Result: No data available

**Carcinogenicity**

<b>IARC</b>	Group 1: Carcinogenic to humans	
	Crystalline silica	14808-60-7
<b>ACGIH</b>	Suspected human carcinogen	
	Crystalline silica	14808-60-7
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
<b>NTP</b>	Known to be human carcinogen	
	Crystalline silica	14808-60-7

**Further information**
**Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available



**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s) : none

Waste from residues : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International Regulation****IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION**

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Acute Health Hazard  
 Chronic Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

**Massachusetts Right To Know**

Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

**Pennsylvania Right To Know**

Pyromellitic dianhydride	89-32-7
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

**New Jersey Right To Know**

Pyromellitic dianhydride	89-32-7
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 3

Revision Date 07/10/2015

Print Date 07/10/2015

1,2,4,5-Benzenetetracarboxylic acid 89-05-4

**New Jersey Trade Secret** : NOT APPLICABLE  
**Registry Number for the product (NJ TSRN)**

**California Prop 65**

WARNING! This product contains a chemical known to the State of California to cause cancer.


Crystalline silica 14808-60-7  
 Titanium dioxide 13463-67-7

**The components of this product are reported in the following inventories:**

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

DSL : We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

Revision Date : 07/10/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.