

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 1 of 13

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **CHO-SHIELD® 610, Part B**

Other means of identification : 52-03-0610-0000

Recommended use of the chemical and restrictions on use

: Three part conductive paint system.
No restrictions on use known.

Chemical family

: Mixture of: Polyamide resin; Alcohols; Ketones; Amines

SDS number

: PHC-265

Name, address, and telephone number of the manufacturer:

Parker Hannifin Corp.

Chomerics Division
77 Dragon Court
Woburn, MA, USA
01888

Manufacturer's Telephone # : (781) 935-4850

24 Hr. Emergency Tel # : INFOTRAC - (800) 535-5053 (Within Continental US); (352) 323-3500 (Outside US)

Name, address, and telephone number of the supplier:

Refer to manufacturer

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Amber liquid. Solvent odor.

Most important hazards:

Highly flammable liquid and vapor. This material may be ignited by heat, sparks and direct flame.

Causes serious eye damage. Irritating to skin. Irritating to respiratory system. May cause an allergic skin reaction.

Inhalation may cause central nervous system depression. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. See Section 12 for more environmental information.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Flammable liquid - Category 2

Skin corrosion/irritation - Category 2

Eye damage/irritation - Category 1

Skin sensitization - Category 1

Specific target organ toxicity, single exposure - Category 3 (Respiratory irritation; Narcotic effects)

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 2 of 13

SAFETY DATA SHEET

Hazard statement(s)

Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fumes, mists or vapors. Wash exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves and eye/face protection.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

In case of fire, use dry chemical, CO₂, or alcohol foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

After prolonged storage, may release explosive peroxides in the presence of air. Direct sunlight or heat may accelerate the release of peroxides. May cause gastrointestinal irritation. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Polyamide resin	Polyamidoamine epoxy adduct	68424-41-9	40.0 - 60.0
Methyl ethyl ketone	Butanone Methyl acetone MEK	78-93-3	15.0 - 30.0
Triethylenetetramine	N,N'-Bis(2-aminoethyl)ethylene diamine TETA	112-24-3	0.5 - 3.0
n-Butyl alcohol	n-Butanol 1-Hydroxybutane	71-36-3	20.0 - 35.0
Isopropyl alcohol	Isopropanol 2-Propanol	67-63-0	7.0 - 13.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

SAFETY DATA SHEET

- Inhalation* : IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.
- Skin contact* : IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Flush eyes with water for at least 15 minutes. Immediately call a POISON CENTER or doctor/physician.

Most important symptoms and effects, both acute and delayed

- : Causes skin irritation. Contact may cause redness, swelling and a painful sensation. Causes serious eye damage. Contact may cause redness, swelling and a painful sensation. May cause irreversible eye damage. May cause severe skin sensitization with allergic contact dermatitis symptoms such as swelling, rash and eczema. May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or narcotic effects. Exposure to low vapour concentrations may cause swelling (edema) of the eyes, resulting in blurring of vision with a bluish haze and/or appearance of halos around lights. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Causes serious eye damage. Provide general supportive measures and treat symptomatically. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Carbon dioxide (CO₂); Dry chemical; Alcohol resistant foam.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Highly flammable liquid and vapor. This material may be ignited by heat, sparks and direct flame. After prolonged storage, may release explosive peroxides in the presence of air. Rate of peroxide formation is not known. Toxic fumes, gases or vapors may evolve on burning. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable liquid - Category 2

Hazardous combustion products

- : Carbon oxides; Nitrogen oxides (NO_x); Aldehydes; Ketones; unburned alcohols; hydrogen cyanide; Ammonia; Amines; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

SAFETY DATA SHEET

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Wear appropriate protective equipment. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains, sewers, waterways and soil. Avoid release to the environment.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): Methyl ethyl ketone (5000 lbs / 2270 kg);
n-Butyl alcohol (5000 lbs / 2270 kg)

In Canada: Contact appropriate local and provincial environmental authorities for assistance and/or reporting requirements.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Persons with recurrent skin eczema or sensitization problems should be excluded from working with this product. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted.
Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves and eye/face protection. Avoid breathing fumes, mists or vapors. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep away from incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Contaminated work clothing must not be allowed out of the workplace.

Conditions for safe storage : Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Keep away from incompatibles.

Incompatible materials : Strong oxidizing agents; Strong acids; Alkali metals; Halogenated compounds; Isocyanates; Acrylates; Nitrogen compounds; Nitrosating agents

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 5 of 13

SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Polyamide resin	N/Av	N/Av	N/Av	N/Av
Methyl ethyl ketone	200 ppm	300 ppm	200 ppm (590 mg/m ³)	N/Av
Triethylenetetramine	1 ppm (AIHA WEEL) (skin)	N/Av	N/Av	N/Av
n-Butyl alcohol	20 ppm	N/Av	100 ppm (300 mg/m ³)	N/Av
Isopropyl alcohol	200 ppm	400 ppm	400 ppm (980 mg/m ³)	N/Av

Exposure controls

Ventilation and engineering measures

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof electrical and ventilating equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection

- : Wear protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Depending on conditions of use, an impervious apron should be worn.

Eye / face protection

- : Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles; Safety glasses with side shields. A full face shield may also be necessary.

Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Avoid breathing fumes, mists or vapors. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Contaminated work clothing must not be allowed out of the workplace. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Amber liquid.

Odour : Solvent odor.

Odour threshold : N/Av

pH : N/Av

Melting Point/Freezing point : N/Av

Initial boiling point and boiling range

- : > 79.6°C (175°F) (based on ingredients)

Flash point : 7.78°C (46°F) (based on ingredients)

Flashpoint (Method) : closed cup

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 6 of 13

SAFETY DATA SHEET

Evaporation rate (BuAe = 1) : N/Av
Flammability (solid, gas) : Not applicable.
Lower flammable limit (% by vol.)
: N/Av
Upper flammable limit (% by vol.)
: N/Av
Oxidizing properties : None known.
Explosive properties : Not explosive
Vapour pressure : N/Av
Vapour density : N/Av
Relative density / Specific gravity
: 0.9
Solubility in water : Insoluble.
Other solubility(ies) : N/Av
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution
: N/Av
Auto-ignition temperature : N/Av
Decomposition temperature : N/Av
Viscosity : N/Av
Volatiles (% by weight) : N/Av
Volatile organic Compounds (VOC's)
: 429 g/L
Absolute pressure of container
: N/Av
Flame projection length : N/Av
Other physical/chemical comments
: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions. After prolonged storage, may release explosive peroxides in the presence of air. Rate of peroxide formation is not known.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Direct sources of heat. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials.
Incompatible materials : Strong oxidizing agents; Strong acids; Alkali metals; Halogenated compounds; Isocyanates; Acrylates; Nitrogen compounds; Nitrosating agents
Hazardous decomposition products
: Peroxides. Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption
: YES

SAFETY DATA SHEET

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

- : May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or narcotic effects. Exposure to low vapour concentrations may cause swelling (edema) of the eyes, resulting in blurring of vision with a bluish haze and/or appearance of halos around lights.

Sign and symptoms ingestion

- : Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin

- : Causes skin irritation. Contact may cause redness, swelling and a painful sensation. May be absorbed through the skin.

Sign and symptoms eyes

- : Causes serious eye damage. Contact may cause redness, swelling and a painful sensation. May cause irreversible eye damage.

Potential Chronic Health Effects

- : Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Mutagenicity

- : No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

- : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

- : This product is not expected to cause reproductive or developmental effects.

Sensitization to material

- : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Skin sensitization - Category 1. May cause an allergic skin reaction. May cause severe skin sensitization with allergic contact dermatitis symptoms such as swelling, rash and eczema.

Specific target organ effects

- No data available to indicate product or components may be respiratory sensitizers. This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Specific target organ toxicity, single exposure - Category 3. May cause respiratory irritation. May cause drowsiness or dizziness.

According to the classification criteria of U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause target organ toxicity through repeated exposures.

Medical conditions aggravated by overexposure

- : Pre-existing skin, eye and respiratory disorders.

Synergistic materials

- : None known or reported by the manufacturer.

Toxicological data

- : Not classified for acute toxicity based on available data. No data is available on the product itself. The calculated ATE values for this mixture are:
ATE oral = 2201 mg/kg
ATE dermal = 9651 mg/kg
ATE inhalation (vapours) = 21.8 - 29 mg/L/4H

See below for individual ingredient acute toxicity data.

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 8 of 13

SAFETY DATA SHEET

<u>Chemical name</u>	<u>LC₅₀(4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Polyamide resin	N/Av	> 2000 mg/kg (No mortality)	> 2000 mg/kg (No mortality)
Methyl ethyl ketone	11 300 ppm (33.3 mg/L (vapour))	2740 mg/kg	6480 mg/kg
Triethylenetetramine	N/Av	4340 mg/kg	805 mg/kg
n-Butyl alcohol	8000 ppm (24.3 mg/L) (vapour)	790 - 4360 mg/kg	3402 mg/kg
Isopropyl alcohol	17 000 ppm (41.8 mg/L) (vapour)	4720 mg/kg	12 890 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. The product contains the following substances which are hazardous for the environment: Triethylenetetramine.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Polyamide resin	68424-41-9	N/Av	N/Av	None.
Methyl ethyl ketone	78-93-3	2993 mg/L (Fathead minnow)	N/Av	None.
Triethylenetetramine	112-24-3	570 mg/L (Guppy)	N/Av	None.
n-Butyl alcohol	71-36-3	1376 mg/L (Fathead minnow)	N/Av	None.
Isopropyl alcohol	67-63-0	9640 mg/L (Fathead minnow)	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Daphnia</u>		
		<u>EC50 / 48h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Polyamide resin	68424-41-9	N/Av	N/Av	None.
Methyl ethyl ketone	78-93-3	308 mg/L (Daphnia magna)	N/Av	None.
Triethylenetetramine	112-24-3	31.1 mg/L (Daphnia magna)	N/Av	None.
n-Butyl alcohol	71-36-3	1328 mg/L (Daphnia magna)	4.1 mg/L	None.
Isopropyl alcohol	67-63-0	> 10 000 mg/L/24hr (Daphnia magna)	30 mg/L	None.

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 9 of 13

SAFETY DATA SHEET

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Polyamide resin	68424-41-9	N/Av	N/Av	None.
Methyl ethyl ketone	78-93-3	1972 mg/L/72hr (Green algae)	1240 mg/L/96hr	None.
Triethylenetetramine	112-24-3	20 mg/L/72hr (Green algae)	N/Av	None.
n-Butyl alcohol	71-36-3	225 mg/L/96hr (Green algae)	129 mg/L/96hr	None.
Isopropyl alcohol	67-63-0	N/Av	N/Av	None.

Persistence and degradability

- : The product itself has not been tested.
- The following ingredients are considered to be readily biodegradable: Methyl ethyl ketone; n-Butyl alcohol; Isopropyl alcohol.
- Contains the following chemicals which are not readily biodegradable: Triethylenetetramine.

Bioaccumulation potential

- : The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Methyl ethyl ketone (CAS 78-93-3)	0.29	3.0
Triethylenetetramine (CAS 112-24-3)	- 1.4	N/Av
n-Butyl alcohol (CAS 71-36-3)	0.88	3.0
Isopropyl alcohol (CAS 67-63-0)	0.05	1.0

Mobility in soil

- : The product itself has not been tested.

Other Adverse Environmental effects

- : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

- : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. This material and its container must be disposed of in a safe way.
- Empty containers retain residue and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal

- : Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

- : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

CHO-SHIELD® 610, Part B





52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 10 of 13

SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1866	RESIN SOLUTION	3	II	
49CFR/DOT Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass. Refer to 49 CFR 173.150(b) and Special Provision 149.				
TDG	UN1866	RESIN SOLUTION	3	II	
TDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass. Under the TDG, refer to Section 1.17 for additional exemption requirements, if shipping under this exemption.				
ICAO/IATA	UN1866	Resin solution	3	II	
ICAO/IATA Additional information	Refer to the appropriate Packing Instruction, prior to shipping this material. Review all State and Operator Variations, prior to shipping this material.				
IMDG	UN1866	RESIN SOLUTION	3	II	
IMDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame - No smoking. Avoid release to the environment.

Environmental hazards : This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
: Not applicable.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Polyamide resin	68424-41-9	Yes	None.	None.	No	N/Ap
Methyl ethyl ketone	78-93-3	Yes	5000 lb/ 2270 kg	None.	No	N/Ap
Triethylenetetramine	112-24-3	Yes	None.	None.	No	N/Ap
n-Butyl alcohol	71-36-3	Yes	5000 lb/ 2270 kg	None.	Yes	1%
Isopropyl alcohol	67-63-0	Yes	None.	None.	Yes	1%

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 11 of 13

SAFETY DATA SHEET

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Physical hazards (Flammable liquid)

Health hazards (Skin irritation; Eye Damage; Skin sensitization; Specific target organ toxicity, single exposure)

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Polyamide resin	68424-41-9	No	N/Ap	No	No	No	No	No	No
Methyl ethyl ketone	78-93-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Triethylenetetramine	112-24-3	No	N/Ap	No	Yes	No	Yes	Yes	No
n-Butyl alcohol	71-36-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Isopropyl alcohol	67-63-0	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on or are exempt from the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:

Methyl ethyl ketone (Part 1, Group A Substance; Part 5: Individual Substances)

n-Butyl alcohol (Part 1, Group A Substance)

Isopropyl alcohol (Part 1, Group A Substance; Part 5: Individual Substances)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Polyamide resin	68424-41-9	Polymer	Present	Present	Not listed	KE-35140	Present	May be used as a single component chemical under an appropriate group standard.
Methyl ethyl ketone	78-93-3	201-159-0	Present	Present	(2)-542	KE-24094	Present	HSR001190
Triethylenetetramine	112-24-3	203-950-6	Present	Present	(2)-163	KE-02911	Present	HSR003570
n-Butyl alcohol	71-36-3	200-751-6	Present	Present	(2)-3049	KE-03867	Present	HSR001096
Isopropyl alcohol	67-63-0	200-661-7	Present	Present	(2)-207	KE-29363	Present	HSR001180

SAFETY DATA SHEET

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
AICS: Australian Inventory of Chemical Substances
AIHA: American Industrial Hygiene Association
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CSA: Canadian Standards Association
DOT: Department of Transportation
EC50: Effective Concentration 50%
EINECS: European Inventory of Existing Commercial chemical Substances
ENCS: Existing and New Chemical Substances
EPA: Environmental Protection Agency
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
IBC: Intermediate Bulk Container
IECSC: Inventory of Existing Chemical Substances
IMDG: International Maritime Dangerous Goods
IOC: Inventory of Chemicals
KECI: Korean Existing Chemicals Inventory
KECL: Korean Existing Chemicals List
LC: Lethal Concentration
LD: Lethal Dose
MA: Massachusetts
MN: Minnesota
N/Ap: Not Applicable
N/Av: Not Available
NIOSH: National Institute of Occupational Safety and Health
NJ: New Jersey
NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WEEL: Workplace Environmental Exposure Level
WHMIS: Workplace Hazardous Materials Identification System

CHO-SHIELD® 610, Part B

52-03-0610-0000

SDS Revision Date (mm/dd/yyyy): 08/13/2019

Page 13 of 13

SAFETY DATA SHEET

References : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2016
2. International Agency for Research on Cancer Monographs, searched 2017
3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2017(Chempendium, HSDB and RTECs).
4. Material Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - 2017 version.
6. California Proposition 65 List - 2017 version.
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2017.

Preparation Date (mm/dd/yyyy)

: 08/08/2018

Reviewed Date SDS (dd/mm/yyyy)

: 13/08/2019

Revision No.

: 2

Revision Information

: (M)SDS sections updated :1. IDENTIFICATION

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<p>Prepared for: Parker Hannifin Corp. Chomerics Division 77 Dragon Court Woburn, MA, U.S.A. 01888 Telephone: (781) 935-4850</p>	
<p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Parker Hannifin Corporation and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corporation expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corporation.

END OF DOCUMENT