

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Humiseal 1A20
Registration number	-
Synonyms	None.
Product code	Humiseal Europe 1A20
Issue date	05-June-2015
Version number	05
Revision date	24-January-2019
Supersedes date	11-December-2017

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Protective Coating for Printed Circuit Board
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	HUMISEAL EUROPE LTD.		
Address	505 Eskdale Road Winnersh Wokingham Berkshire RG41 5TU UK		
Division	A CHASE CORPORATION COMPANY		
Telephone	General Assistance	44 (0) 118 944 2333	
e-mail	europetechsupport@chasecorp.com		
Contact person	Not available.		

1.4. Emergency telephone number	Chemtrec U.K.	+(44) 870 820 0418
---------------------------------	---------------	--------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

Health hazards

Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Acute toxicity, inhalation	Category 3	H331 - Toxic if inhaled.
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Respiratory sensitisation	Category 1	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Environmental hazards

Hazardous to the aquatic environment,
long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with
long lasting effects.

Hazard summary

May be ignited by heat, sparks or flames. Toxic if inhaled. Harmful in contact with skin. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged exposure may cause chronic effects. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

Ethylbenzene, Toluene diisocyanate, XYLENES

Hazard pictograms



Signal word

Danger

Hazard statements

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist or vapour.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.

Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P311	Call a POISON CENTRE/doctor.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE/doctor.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information

71.43 % of the mixture consists of component(s) of unknown acute oral toxicity. 71.43 % of the mixture consists of component(s) of unknown acute dermal toxicity. 73.47 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 98.91 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 71.43 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards

Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
1-METHOXY-2-PROPYL ACETATE	20 - < 30	108-65-6 203-603-9	01-2119475791-29-xxxx	607-195-00-7	#
Classification:	Flam. Liq. 3;H226				
XYLENES	20 - < 30	1330-20-7 215-535-7	01-2119488216-32-XXXX	601-022-00-9	#
Classification:	Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, Acute Tox. 4;H332, Aquatic Chronic 2;H411				
Ethylbenzene	3 - < 5	100-41-4 202-849-4	01-2119489370-35-XXXX	601-023-00-4	#
Classification:	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Acute Tox. 4;H332, STOT RE 2;H373, Aquatic Chronic 2;H411				
Toluene	1 - < 3	108-88-3 203-625-9	01-2119471310-51-xxxx	601-021-00-3	#
Classification:	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, STOT RE 2;H373, Aquatic Chronic 2;H411				
Toluene diisocyanate	< 1	26471-62-5 247-722-4	01-211945491-34-xxxx	615-006-00-4	C
Classification:	Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, Acute Tox. 2;H330, Resp. Sens. 1;H334, STOT SE 3;H335, Carc. 2;H351, Aquatic Chronic 3;H412				
Other components below reportable levels	40 - < 50				

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTRE or doctor/physician.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Direct contact with eyes may cause temporary irritation. Difficulty in breathing. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapours and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapours and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
1-METHOXY-2-PROPYL ACETATE (CAS 108-65-6)	STEL	548 mg/m3
		100 ppm
	TWA	274 mg/m3
		50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	552 mg/m3
		125 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	441 mg/m ³ 100 ppm
	STEL	384 mg/m ³ 100 ppm
Toluene diisocyanate (CAS 26471-62-5)	TWA	191 mg/m ³ 50 ppm
	STEL	0.07 mg/m ³
XYLENES (CAS 1330-20-7)	TWA	0.02 mg/m ³
	STEL	441 mg/m ³ 100 ppm
	TWA	220 mg/m ³ 50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
1-METHOXY-2-PROPYL ACETATE (CAS 108-65-6)	STEL	550 mg/m ³ 100 ppm
	TWA	275 mg/m ³ 50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³ 200 ppm
	TWA	442 mg/m ³ 100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m ³ 100 ppm
	TWA	192 mg/m ³ 50 ppm
XYLENES (CAS 1330-20-7)	STEL	442 mg/m ³ 100 ppm
	TWA	221 mg/m ³ 50 ppm

Biological limit values**UK. EH40 Biological Monitoring Guidance Values (BMGVs)**

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines**UK EH40 WEL: Skin designation**

1-METHOXY-2-PROPYL ACETATE (CAS 108-65-6)	Can be absorbed through the skin.
Ethylbenzene (CAS 100-41-4)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
XYLENES (CAS 1330-20-7)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection

Wear appropriate chemical resistant gloves.

- Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Wear positive pressure self-contained breathing apparatus (SCBA). Chemical respirator with organic vapour cartridge.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Colour

Not available.

Odour

Not available.

Odour threshold

Not available.

pH

Does not apply.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

Not available.

Flash point

23.0 °C (73.4 °F) Closed cup ASTM D56 05

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Vapour pressure

7.65 hPa estimated

Vapour density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Negligible

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

70 - 130 cP

Viscosity temperature

25 °C (77 °F)

Explosive properties

Not explosive.

Oxidising properties

Not oxidising.

9.2. Other information

Brookfield viscosity	70 - 130 cP
Density	1.01 g/cm ³ estimated
Miscible (water)	Negligible
Percent volatile	27.91 % estimated
Specific gravity	1.01 estimated
VOC	511 g/l estimated

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong acids. Strong oxidising agents. Halogens.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Difficulty in breathing. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Toxic if inhaled. Harmful in contact with skin.

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12120 mg/kg
Oral		
LD50	Rat	2.6 g/kg
Toluene diisocyanate (CAS 26471-62-5)		
Acute		
Oral		
LD50	Rat	3060 mg/kg
XYLENES (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Toluene diisocyanate (CAS 26471-62-5)	2B Possibly carcinogenic to humans.
XYLENES (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects. Due to partial or complete lack of data the classification for hazardous to the aquatic environment, acute hazard, is not possible.

Product	Species		Test Results
Humiseal 1A20			
Aquatic			
Crustacea	EC50	Daphnia	71.8661 mg/l, 48 hours estimated
Fish	LC50	Fish	189.7168 mg/l, 96 hours estimated
Components	Species		Test Results
Ethylbenzene (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
XYLENES (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Ethylbenzene	3.15
Toluene	2.73
XYLENES	3.12 - 3.2

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Material name: Humiseal 1A20

Humiseal Europe 1A20 Version #: 05 Revision date: 24-January-2019 Issue date: 05-June-2015

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	30
Tunnel restriction code	D/E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

RID

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

ADN

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

IATA

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	No.
ERG Code	3L
14.6. Special precautions for user	Not available.

Other information

Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
14.6. Special precautions for user	Not available.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

XYLENES (CAS 1330-20-7)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

1-METHOXY-2-PROPYL ACETATE (CAS 108-65-6)

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Toluene diisocyanate (CAS 26471-62-5)

XYLENES (CAS 1330-20-7)

Other regulations

Pregnant women should not work with the product, if there is the least risk of exposure. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Revision information

SECTION 2: Hazards identification: Storage

Training information

Follow training instructions when handling this material.

Disclaimer

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose