

## SAFETY DATA SHEET

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name or designation of the mixture	HumiSeal 1A33 PB 48.3
Registration number	-
Synonyms	None.
Product code	Humiseal Europe 1A33 PB 48.3
Issue date	17-June-2015
Version number	02
Revision date	14-December-2017
Supersedes date	17-June-2015

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Protective Coating for Printed Circuit Board
Uses advised against	None known.

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Company name	HUMISEAL EUROPE LTD.	
Address	505 Eskdale Road Winnersh Wokingham Berkshire RG41 5TU UK	
Division	A CHASE CORPORATION COMPANY	
Telephone	General Assistance	44 (0) 118 944 2333
e-mail	europetechsupport@chasecorp.com	
Contact person	Not available.	

1.4. Emergency telephone number	Chemtrec USA	1-800-424-9300
	OutSide USA	+1 703-741-5970

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
-------------------	------------	--

##### Health hazards

Acute toxicity, inhalation	Category 4	H332 - Harmful if inhaled.
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Reproductive toxicity (the unborn child)	Category 2	H361d - Suspected of damaging the unborn child.

**Environmental hazards**

Hazardous to the aquatic environment,  
long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with  
long lasting effects.

**Hazard summary**

May be ignited by heat, sparks or flames. Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Possible reproductive hazard. Prolonged exposure may cause chronic effects. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects.

**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended**

**Contains:** 2-Octyl-2H-Isothiazol-3-one, Ethylbenzene, Toluene, Tris(nonylphenyl) phosphite, XYLENES

**Hazard pictograms****Signal word**

Danger

**Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements****Prevention**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapour.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

**Response**

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTRE/doctor if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

**Storage**

P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Disposal**

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Supplemental label information**

11.51 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 60.81 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 5.11 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

**2.3. Other hazards**

Not a PBT or vPvB substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
XYLENES	40 - < 50	1330-20-7 215-535-7	01-2119488216-32-XXXX	601-022-00-9	#
<b>Classification:</b>	Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, Acute Tox. 4;H332, Aquatic Chronic 2;H411				C
Methyl ethyl ketone	5 - < 10	78-93-3 201-159-0	01-2119457290-43-xxxx	606-002-00-3	#
<b>Classification:</b>	Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336				
Toluene	5 - < 10	108-88-3 203-625-9	01-2119471310-51-XXXX	601-021-00-3	#
<b>Classification:</b>	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Repr. 2;H361d, STOT RE 2;H373, Aquatic Chronic 2;H411				
2-Octyl-2H-Isothiazol-3-one	1 - < 3	26530-20-1 247-761-7	-	613-112-00-5	
<b>Classification:</b>	Acute Tox. 4;H302, Acute Tox. 3;H311, Skin Corr. 1B;H314, Skin Sens. 1;H317, Eye Dam. 1;H318, Acute Tox. 3;H331, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				
Ethylbenzene	1 - < 3	100-41-4 202-849-4	01-2119489370-35-XXXX	601-023-00-4	#
<b>Classification:</b>	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Acute Tox. 4;H332, STOT RE 2;H373, Aquatic Chronic 2;H411				
Tris(nonylphenyl) phosphite	< 0.2	26523-78-4 247-759-6	01-2119520601-54-XXXX	015-202-00-4	
<b>Classification:</b>	Skin Sens. 1;H317, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				

Other components below reportable levels 30 - < 40

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

#### General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures

##### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTRE or doctor/physician if you feel unwell.

##### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

##### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

##### Ingestion

Rinse mouth. Get medical attention if symptoms occur.

#### 4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Highly flammable liquid and vapour.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Special fire fighting procedures</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapours and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>For emergency responders</b>	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.
<b>6.2. Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
<b>6.3. Methods and material for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use.
<b>6.4. Reference to other sections</b>	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapours and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
<b>7.3. Specific end use(s)</b>	Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

## Occupational exposure limits

### UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	552 mg/m <sup>3</sup>
		125 ppm
	TWA	441 mg/m <sup>3</sup>
		100 ppm
2-Butanone (Methyl ethyl ketone) (CAS 78-93-3)	STEL	899 mg/m <sup>3</sup>
		300 ppm
	TWA	600 mg/m <sup>3</sup>
		200 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m <sup>3</sup>
		100 ppm
	TWA	191 mg/m <sup>3</sup>
		50 ppm
XYLENES (CAS 1330-20-7)	STEL	441 mg/m <sup>3</sup>
		100 ppm
	TWA	220 mg/m <sup>3</sup>
		50 ppm

### EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m <sup>3</sup>
		200 ppm
	TWA	442 mg/m <sup>3</sup>
		100 ppm
2-Butanone (Methyl ethyl ketone) (CAS 78-93-3)	STEL	900 mg/m <sup>3</sup>
		300 ppm
	TWA	600 mg/m <sup>3</sup>
		200 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m <sup>3</sup>
		100 ppm
	TWA	192 mg/m <sup>3</sup>
		50 ppm
XYLENES (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

## Biological limit values

### UK. EH40 Biological Monitoring Guidance Values (BMGVs)

Components	Value	Determinant	Specimen	Sampling time
2-Butanone (Methyl ethyl ketone) (CAS 78-93-3)	70 µmol/l	Butan-2-one	Urine	*
XYLENES (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

## Exposure guidelines

### UK EH40 WEL: Skin designation

Ethylbenzene (CAS 100-41-4)	Can be absorbed through the skin.
Methyl ethyl ketone (CAS 78-93-3)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
XYLENES (CAS 1330-20-7)	Can be absorbed through the skin.

## 8.2. Exposure controls

<b>Appropriate engineering controls</b>	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>General information</b>	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
<b>Eye/face protection</b>	Chemical respirator with organic vapour cartridge and full facepiece.
<b>Skin protection</b>	
- <b>Hand protection</b>	Wear appropriate chemical resistant gloves.
- <b>Other</b>	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	Chemical respirator with organic vapour cartridge and full facepiece.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>Hygiene measures</b>	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
<b>Environmental exposure controls</b>	Inform appropriate managerial or supervisory personnel of all environmental releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	Clear.
<b>Odour</b>	Aromatic
<b>Odour threshold</b>	Not available.
<b>pH</b>	Does not apply.
<b>Melting point/freezing point</b>	-94.9 °C (-138.82 °F) estimated
<b>Initial boiling point and boiling range</b>	79.59 °C (175.26 °F) estimated
<b>Flash point</b>	-1.0 °C (30.2 °F) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1 % estimated
<b>Flammability limit - upper (%)</b>	7 % estimated
<b>Vapour pressure</b>	23.18 hPa estimated
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	404 °C (759.2 °F) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	45 - 51 cP
<b>Viscosity temperature</b>	25 °C (77 °F)
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.
<b>9.2. Other information</b>	
<b>Brookfield viscosity</b>	45 - 51 cP

Density	0.93 g/cm <sup>3</sup>
Miscible (water)	Negligible
Percent volatile	64 - 68 % v/v
Specific gravity	0.94 estimated
VOC	564 g/l

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong acids. Strong oxidising agents. Halogens. Ammonia. Amines. Isocyanates. Caustics.
<b>10.6. Hazardous decomposition products</b>	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### 11.1. Information on toxicological effects

<b>Acute toxicity</b>	Harmful if inhaled.
<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Skin sensitisation</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Carcinogenicity</b>	Risk of cancer cannot be excluded with prolonged exposure.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
XYLENES (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
<b>Specific target organ toxicity - single exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - repeated exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Aspiration hazard</b>	Due to partial or complete lack of data the classification is not possible.
<b>Mixture versus substance information</b>	No information available.
<b>Other information</b>	Not available.

## SECTION 12: Ecological information

**12.1. Toxicity** Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

Components	Species	Test results
Ethylbenzene (CAS 100-41-4)		
<b>Aquatic</b>		
Crustacea	EC50 Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours

Components		Species	Test results
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	7.5 - 11 mg/l, 96 hours
Methyl ethyl ketone (CAS 78-93-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow ( <i>Cyprinodon variegatus</i> )	> 400 mg/l, 96 hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon ( <i>Oncorhynchus kisutch</i> )	8.11 mg/l, 96 hours
XYLENES (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	7.711 - 9.591 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

## 12.2. Persistence and degradability

## 12.3. Bioaccumulative potential

### Partition coefficient

#### n-octanol/water (log Kow)

Ethylbenzene	3.15
Methyl ethyl ketone	0.29
Toluene	2.73
XYLENES	3.12 - 3.2

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	Paint
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
<b>14.4. Packing group</b>	II



**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**RID**

**14.1. UN number** UN1263  
**14.2. UN proper shipping name** Paint  
**14.3. Transport hazard class(es)**  
    **Class** 3  
    **Subsidiary risk** -  
    **Label(s)** 3  
**14.4. Packing group** II  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**ADN**

**14.1. UN number** UN1263  
**14.2. UN proper shipping name** Paint  
**14.3. Transport hazard class(es)**  
    **Class** 3  
    **Subsidiary risk** -  
    **Label(s)** 3  
**14.4. Packing group** II  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IATA**

**14.1. UN number** UN1263  
**14.2. UN proper shipping name** PAINT  
**14.3. Transport hazard class(es)**  
    **Class** 3  
    **Subsidiary risk** -  
**14.4. Packing group** II  
**14.5. Environmental hazards** No.  
**ERG Code** 3L  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

**IMDG**

**14.1. UN number** UN1263  
**14.2. UN proper shipping name** PAINT  
**14.3. Transport hazard class(es)**  
    **Class** 3  
    **Subsidiary risk** -  
**14.4. Packing group** II  
**14.5. Environmental hazards**  
    **Marine pollutant** No.  
**EmS** F-E, S-E  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code** Not established.



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Ethylbenzene (CAS 100-41-4)

Methyl ethyl ketone (CAS 78-93-3)

Toluene (CAS 108-88-3)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

#### Other EU regulations

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

2-Octyl-2H-Isothiazol-3-one (CAS 26530-20-1)

Ethylbenzene (CAS 100-41-4)

Methyl ethyl ketone (CAS 78-93-3)

Toluene (CAS 108-88-3)

Tris(nonylphenyl) phosphite (CAS 26523-78-4)

XYLENES (CAS 1330-20-7)

#### Other regulations

Pregnant women should not work with the product, if there is the least risk of exposure. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. Additional information is given in the Safety Data Sheet.

#### National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

#### List of abbreviations

Not available.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose. The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.