











# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Humiseal 1B31EPA 604 PB35

of the mixture

Registration number

**Synonyms** None.

Humiseal Eu 1B31EPA 604 PB35 **Product code** 

10-February-2016 Issue date

Version number 04

14-November-2017 **Revision date** 27-October-2017 Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Protective Coating for Printed Circuit Board **Identified uses** 

None known. Uses advised against 1.3. Details of the supplier of the safety data sheet

Supplier

HUMISEAL EUROPE LTD. Company name

505 Eskdale Road **Address** 

Winnersh

Wokingham Berkshire RG41 5TU

**Division** A CHASE CORPORATION COMPANY

**Telephone** General Assistance 44 (0) 118 944 2333

europetechsupport@chasecorp.com e-mail

Not available. Contact person

1.4. Emergency telephone

number

Chemtrec USA

1-800-424-9300

OutSide USA +1 703-741-5970

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

## Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

**Health hazards** 

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

exposure dizziness.

May be ignited by heat, sparks or flames. May cause drowsiness and dizziness. Causes serious

eye irritation. Occupational exposure to the substance or mixture may cause adverse health

effects.

## 2.2. Label elements

**Hazard summary** 

# Label according to Regulation (EC) No. 1272/2008 as amended

Isopropyl alcohol, Propylene Glycol Methyl Ether Acetate Contains:

Hazard pictograms



Signal word Danger

**Hazard statements** 

Highly flammable liquid and vapour. H225 Causes serious eye irritation. H319 May cause drowsiness or dizziness. H336

**Precautionary statements** 

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Keep container tightly closed. P233

Ground/bond container and receiving equipment. P240

Use explosion-proof electrical/ventilating/lighting equipment. P241

Use only non-sparking tools. P242

Take precautionary measures against static discharge. P243

Avoid breathing mist or vapour. P261 Wash thoroughly after handling. P264

Use only outdoors or in a well-ventilated area. P271

P280 Wear protective gloves/eye protection/face protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with P303 + P361 + P353

water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304 + P340

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.
Call a POISON CENTRE/doctor if you feel unwell. P312 If eye irritation persists: Get medical advice/attention. P337 + P313 In case of fire: Use appropriate media to extinguish. P370 + P378

Storage

Store in a well-ventilated place. Keep container tightly closed. P403 + P233

Store in a well-ventilated place. Keep cool. P403 + P235

Store locked up. P405

**Disposal** 

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

76.33 % of the mixture consists of component(s) of unknown acute oral toxicity. 76.33 % of the Supplemental label information

> mixture consists of component(s) of unknown acute dermal toxicity. 99.93 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 99.93 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment, 99.93 % of the mixture

consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### **General information**

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Propylene Glycol Meth Acetate	yl Ether	60 - < 70	108-65-6 203-603-9	01-2119475791-29-xxxx	607-195-00-7	#
Classification:	Flam. Li	q. 3;H226				
Isopropyl alcohol		20 - < 30	67-63-0 200-661-7	01-2119457558-25-xxxx	603-117-00-0	
Classification:	Flam. Li	q. 2;H225, Eye	Irrit. 2;H319, STO	T SE 3;H336		

Other components below reportable levels 10 - < 20

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

# **SECTION 4: First aid measures**

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTRE or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

5.3. Advice for firefighters

**Special protective** equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

procedures

so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages

cannot be contained. For personal protection, see section 8 of the SDS.

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during For emergency responders

clean-up. Use personal protection recommended in Section 8 of the SDS.

Avoid discharge into drains, water courses or onto the ground. 6.2. Environmental precautions

Material name: Humiseal 1B31EPA 604 PB35

Humiseal Eu 1B31EPA 604 PB35 Version #: 04 Revision date: 14-November-2017 Issue date: 10-February-2016

## 6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

#### 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapour. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

# 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

# Occupational exposure limits

Components	osure Limits (WELs) Type	Value	
Isopropyl alcohol (CAS 67-63-0)	STEL	1250 mg/m3	
		500 ppm	
	TWA	999 mg/m3	
		400 ppm	
Propylene Glycol Methyl Ether Acetate (CAS 108-65-6)	STEL	548 mg/m3	
,		100 ppm	
	TWA	274 mg/m3	
		FO	
		50 ppm	
EU. Indicative Exposure L	imit Values in Directives 91/322/EEC.		
	imit Values in Directives 91/322/EEC, 2 Type		
Propylene Glycol Methyl Ether Acetate (CAS		2000/39/EC, 2006/15/EC, 2009/161/EU	
Propylene Glycol Methyl Ether Acetate (CAS	Туре	2000/39/EC, 2006/15/EC, 2009/161/EU Value	
EU. Indicative Exposure L Components  Propylene Glycol Methyl Ether Acetate (CAS 108-65-6)	Туре	2000/39/EC, 2006/15/EC, 2009/161/EU Value 550 mg/m3	
Propylene Glycol Methyl Ether Acetate (CAS	<b>Type</b> STEL	2000/39/EC, 2006/15/EC, 2009/161/EU Value 550 mg/m3	
Propylene Glycol Methyl Ether Acetate (CAS	<b>Type</b> STEL	2000/39/EC, 2006/15/EC, 2009/161/EU Value  550 mg/m3  100 ppm 275 mg/m3 50 ppm	

Bio

Rec

pro

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available.

#### **Exposure guidelines**

#### **UK EH40 WEL: Skin designation**

Propylene Glycol Methyl Ether Acetate (CAS 108-65-6) Can be absorbed through the skin.

Material name: Humiseal 1B31EPA 604 PB35

SDS LIK

#### 8.2. Exposure controls

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

## Individual protection measures, such as personal protective equipment

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear suitable protective clothing.

**Respiratory protection** Chemical respirator with organic vapour cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Environmental manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid.
Colour Not available.
Odour Not available.

Odour threshold Not available.

pH Does not apply.

Melting point/freezing point Initial boiling point and boiling -88.5 °C (-127.3 °F) estimated 82.5 °C (180.5 °F) estimated

range

Flash point

12.0 °C (53.6 °F) estimated

Evaporation rate 0.3 BuAc
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

2.5 % estimated

Flammability limit - upper

(%)

12 % estimated

Vapour pressure 20.25 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 399 °C (750.2 °F) estimated

Decomposition temperatureNot available.Viscosity30 - 40 cPViscosity temperature25 °C (77 °F)Explosive propertiesNot explosive.Oxidising propertiesNot oxidising.

9.2. Other information

Brookfield viscosity 30 - 40 cP

Material name: Humiseal 1B31EPA 604 PB35

Humiseal Eu 1B31EPA 604 PB35 Version #: 04 Revision date: 14-November-2017 Issue date: 10-February-2016

Density 0.78 g/cm3 estimated

Miscible (water) Negligible Percent volatile 70 - 76 % v/v

Specific gravity 0.95 VOC 684 q/l

# SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Acids. Strong oxidising agents. Isocyanates. Chlorine.

10.6. Hazardous

decomposition products

No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

**Symptoms** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### 11.1. Information on toxicological effects

**Acute toxicity** Not known.

Due to partial or complete lack of data the classification is not possible. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Skin sensitisation Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Carcinogenicity Due to partial or complete lack of data the classification is not possible. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard** 

Mixture versus substance

information

No information available.

Other information Not available

# **SECTION 12: Ecological information**

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

Components Species Test results

Isopropyl alcohol (CAS 67-63-0)

Aquatic

LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

# 12.2. Persistence and degradability

Material name: Humiseal 1B31EPA 604 PB35

Humiseal Eu 1B31EPA 604 PB35 Version #: 04 Revision date: 14-November-2017 Issue date: 10-February-2016

SDS UK

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# 12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Isopropyl alcohol 0.05

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT

and vPvB assessment

Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation

potential.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

**EU waste code**The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Special precautions**Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

#### ADR

**14.1. UN number** UN1263 **14.2. UN proper shipping** Paint

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Hazard No. (ADR) 33
Tunnel restriction code D/E
14.4. Packing group II
14.5. Environmental hazards No.

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

RID

**14.1. UN number** UN1263

14.2. UN proper shipping Paint

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards No.

**14.6. Special precautions** Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

**14.1. UN number** UN1263 **14.2. UN proper shipping** Paint

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group II
14.5. Environmental hazards No.

**14.6. Special precautions** Read safety instructions, SDS and emergency procedures before handling.

for user

Material name: Humiseal 1B31EPA 604 PB35

#### **IATA**

**14.1. UN number** UN1263 **14.2. UN proper shipping** PAINT

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk 
14.4. Packing group II

14.5. Environmental hazards No.
ERG Code 3L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

Not established.

aircraft

Cargo aircraft only Allowed with restrictions.

**IMDG** 

**14.1. UN number** UN1263 **14.2. UN proper shipping** PAINT

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk 
14.4. Packing group II

14.5. Environmental hazards
Marine pollutant No.

EmS F-E, S-E

14.6. Special precautions

for user

 $\label{lem:conditions} \mbox{Read safety instructions, SDS and emergency procedures before handling.}$ 

14.7. Transport in bulk according to Annex II of Marpol

and the IBC Code

ADN; ADR; IATA; IMDG; RID



# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

#### Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Isopropyl alcohol (CAS 67-63-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

#### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Isopropyl alcohol (CAS 67-63-0)

Propylene Glycol Methyl Ether Acetate (CAS 108-65-6)

Pregnant women should not work with the product, if there is the least risk of exposure. The Other regulations

> product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No

1907/2006, as amended. Additional information is given in the Safety Data Sheet.

Follow national regulation for work with chemical agents. Young people under 18 years old are not National regulations

allowed to work with this product according to EU Directive 94/33/EC on the protection of young

people at work, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

Not available. List of abbreviations References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any H-statements not written out in full under

Sections 2 to 15

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material. **Training information** 

Disclaimer The information and recommendations in this safety data sheet are, to the best of our knowledge,

> accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this

information and the suitability of the material or product for any particular purpose

Material name: Humiseal 1B31EPA 604 PB35

Humiseal Eu 1B31EPA 604 PB35 Version #: 04 Revision date: 14-November-2017 Issue date: 10-February-2016