

# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Humiseal 1B73 EPA Aerosol

of the mixture

Registration number

**Synonyms** None.

Humiseal Eu 1B73EPA Aerosol **Product code** 

17-June-2015 Issue date

Version number 07

07-December-2017 **Revision date** Supersedes date 19-September-2017

1.2. Relevant identified uses of the substance or mixture and uses advised against

Protective Coating for Printed Circuit Board **Identified uses** 

None known. Uses advised against 1.3. Details of the supplier of the safety data sheet

**Supplier** 

HUMISEAL EUROPE LTD. Company name

505 Eskdale Road **Address** 

Winnersh

Wokingham Berkshire RG41 5TU

**Division** A CHASE CORPORATION COMPANY

**Telephone** General Assistance 44 (0) 118 944 2333

europetechsupport@chasecorp.com e-mail

Not available. Contact person

1.4. Emergency telephone

number

Chemtrec USA 1-800-424-9300

OutSide USA +1 703-741-5970

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

# Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

**Health hazards** 

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Specific target organ toxicity - single

exposure

Category 3 narcotic effects

H336 - May cause drowsiness or

dizziness.

Material name: Humiseal 1B73 EPA Aerosol

## Hazard summary Aerosol CONTENTS UNDER PRESSURE.

Pressurised container may explode when exposed to heat or flame. May cause drowsiness and dizziness. Causes serious eye irritation. Occupational exposure to the substance or mixture may cause adverse health effects. This is a consumer care product that is safe for consumers when used according to the label directions. Like many consumer products, a small number of individuals may experience reactions such as redness, rash and / or swelling upon prolonged or repeated skin contact or eye contact.

#### 2.2. Label elements

## Label according to Regulation (EC) No. 1272/2008 as amended

Contains: ACETONE, Isopropyl alcohol, n-Butyl acetate

**Hazard pictograms** 



Signal word Danger

**Hazard statements** 

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Precautionary statements** 

Prevention

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P261 Avoid breathing mist or vapour.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/face protection.

Response

P<sub>101</sub> If medical advice is needed, have product container or label at hand.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a PÓISON CENTRE/doctor if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/attention.

**Storage** 

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** 

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information 43.75 % of the mixture consists of component(s) of unknown acute oral toxicity. 54.17 % of the

mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of

component(s) of unknown acute inhalation toxicity. 87.5 % of the mixture consists of

component(s) of unknown acute hazards to the aquatic environment. 77.08 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. EUH066 -

Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards** Not a PBT or vPvB substance or mixture.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**General information** 

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
ACETONE	30 - < 40	67-64-1 200-662-2	-	606-001-00-8	#

Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336

Material name: Humiseal 1B73 EPA Aerosol

SDS UK

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
n-Butyl acetate	10 - < 20	123-86-4 204-658-1	01-2119485493-29-xxxx	607-025-00-1	
Classification:	Flam. Liq. 3;H226, STC	T SE 3;H336, Aqu	uatic Chronic 3;H412		
Isopropyl alcohol	1 - < 3	67-63-0 200-661-7	01-2119457558-25-xxxx	603-117-00-0	
Classification:	Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336				

Other components below reportable levels 50 - < 60

# List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

## **SECTION 4: First aid measures**

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTRE or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

> present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion

May cause drowsiness and dizziness. Headache, Nausea, vomiting, Severe eve irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

Extremely flammable aerosol. General fire hazards

5.1. Extinguishing media

Suitable extinguishing

media

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Material name: Humiseal 1B73 EPA Aerosol

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the For emergency responders

SDS.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up Avoid discharge into drains, water courses or onto the ground.

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

# **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapour. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

Not available. 7.3. Specific end use(s)

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Occupational exposure limits

Components	Туре	Value
ACETONE (CAS 67-64-1)	STEL	3620 mg/m3
		1500 ppm
	TWA	1210 mg/m3
		500 ppm
Butane (CAS 106-97-8)	STEL	1810 mg/m3
		750 ppm
	TWA	1450 mg/m3
		600 ppm
Isopropyl alcohol (CAS 67-63-0)	STEL	1250 mg/m3
		500 ppm
	TWA	999 mg/m3
		400 ppm
n-Butyl acetate (CAS 123-86-4)	STEL	966 mg/m3
		200 ppm
	TWA	724 mg/m3
		150 ppm
EU. Indicative Exposure Limit Val	ues in Directives 91/322/EEC,	2000/39/EC, 2006/15/EC, 2009/161/EU
Components	Туре	Value

**ACETONE (CAS 67-64-1) TWA** 1210 mg/m3 500 ppm

**Biological limit values** Recommended monitoring No biological exposure limits noted for the ingredient(s).

procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available.

#### 8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

# Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Wear appropriate chemical resistant gloves. - Hand protection

Wear suitable protective clothing. - Other

Chemical respirator with organic vapour cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

**Environmental exposure** 

controls

Environmental manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

**Appearance** 

Liquid. Physical state **Form** Aerosol Colour Colorless Aromatic Odour **Odour threshold** Not available. pН Does not apply.

-187.6 °C (-305.68 °F) estimated Melting point/freezing point Initial boiling point and boiling -42.1 °C (-43.78 °F) estimated

range

Flash point -18.0 °C (-0.4 °F) **Evaporation rate** Not available. Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

1.4 % estimated

(%)

Flammability limit - upper

12.8 % estimated

(%)

3511.75 hPa estimated Vapour pressure

Not available. Vapour density Relative density Not available.

Solubility(ies)

Negligible Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** 287.78 °C (550 °F) estimated

**Decomposition temperature** Not available. Not available. Viscosity Not explosive. **Explosive properties** Oxidising properties Not oxidising

9.2. Other information

**Density** 0.74 g/cm3

30.99 kJ/g estimated **Heat of combustion (NFPA** 

30B)

Material name: Humiseal 1B73 EPA Aerosol

Humiseal Eu 1B73EPA Aerosol Version #: 07 Revision date: 07-December-2017 Issue date: 17-June-2015

Miscible (water) Negligible

Percent volatile 91 - 95 % v/v

Specific gravity 0.74 VOC 687.5 g/l

# **SECTION 10: Stability and reactivity**

**10.1. Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**10.4. Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

No hazardous decomposition products are known.

**10.5. Incompatible materials** Acids. Strong oxidising agents. Nitrates. Fluorine. Chlorine.

10.6. Hazardous

decomposition products

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

**Symptoms** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

# 11.1. Information on toxicological effects

Acute toxicity Not known.

**Skin corrosion/irritation**Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation

Skin sensitisation

Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information Not available.

# **SECTION 12: Ecological information**

**12.1. Toxicity**Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

Components **Species Test results ACETONE (CAS 67-64-1)** Aquatic Crustacea FC50 Water flea (Daphnia magna) 10294 - 17704 mg/l, 48 hours Fish LC50 Rainbow trout, donaldson trout 4740 - 6330 mg/l, 96 hours (Oncorhynchus mykiss) Isopropyl alcohol (CAS 67-63-0) Aquatic Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

Material name: Humiseal 1B73 EPA Aerosol

Components Species Test results

n-Butyl acetate (CAS 123-86-4)

**Aquatic** 

Fish LC50 Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours

#### 12.2. Persistence and

degradability

#### 12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

ACETONE -0.24
Isopropyl alcohol 0.05
n-Butyl acetate 1.78

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT Not a PBT or vPvB s

and vPvB assessment

Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects**The product contains volatile organic compounds which have a photochemical ozone creation potential.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

**EU waste code**The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

**Special precautions**Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

#### **ADR**

**14.1. UN number** UN1950

**14.2. UN proper shipping** Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code D

14.4. Packing group Not available.

14.5. Environmental hazards No.

**14.6. Special precautions** Read safety instructions, SDS and emergency procedures before handling.

for user

RID

**14.1. UN number** UN1950

**14.2. UN proper shipping** Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

**14.4. Packing group** Not available.

14.5. Environmental hazards No.

**14.6. Special precautions** Read safety instructions, SDS and emergency procedures before handling.

for user

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### **ADN**

UN1950 14.1. UN number

14.2. UN proper shipping Aerosols, [flammable]

14.3. Transport hazard class(es) 2.1 Class Subsidiary risk 2.1 Label(s)

Not available. 14.4. Packing group

14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

**IATA** 

14.1. UN number UN1950

Aerosols, flammable 14.2. UN proper shipping

name

14.3. Transport hazard class(es) 2.1 Class Subsidiary risk

14.4. Packing group Not available.

14.5. Environmental hazards No. **ERG Code** 101

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN1950 14.1. UN number **AEROSOLS** 14.2. UN proper shipping

name

14.3. Transport hazard class(es) Class Subsidiary risk

14.4. Packing group Not available.

14.5. Environmental hazards Marine pollutant No. F-D, S-U **EmS** 

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Not established. 14.7. Transport in bulk

according to Annex II of Marpol

and the IBC Code

ADN; ADR; IATA; IMDG; RID



# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended ACETONE (CAS 67-64-1)

Isopropyl alcohol (CAS 67-63-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

## Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ACETONE (CAS 67-64-1) Isopropyl alcohol (CAS 67-63-0) n-Butyl acetate (CAS 123-86-4)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. Additional information is given in the Safety Data Sheet.

National regulations Follow national regulation for work with chemical agents. Young people under 18 years old are not

allowed to work with this product according to EU Directive 94/33/EC on the protection of young

people at work, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any H-statements not written out in full under

Sections 2 to 15 H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Revision information Composition / Information on Ingredients: Ingredients

SECTION 7: Handling and storage: 7.2. Conditions for safe storage, including any incompatibilities

**Training information** Follow training instructions when handling this material.

Material name: Humiseal 1B73 EPA Aerosol

SDS UK