



## SAFETY DATA SHEET

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Trade name or designation of the mixture** HumiSeal Thinner 535

**Registration number** -

**Synonyms** HumiSeal T535, HUM T535

**Product code** EF0000-1114

**Issue date** 20-June-2015

**Version number** 05

**Revision date** 31-August-2023

**Supersedes date** 05-August-2020

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Thinner for protective coating.

**Uses advised against** No other uses are advised.

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

**Company name** HUMISEAL EUROPE LTD.

**Address** 505 Eskdale Road  
Winnersh  
Wokingham Berkshire RG41 5TU  
UK

**Division** A CHASE CORPORATION COMPANY

**Telephone** General Assistance +44 (0) 118 944 2333

**e-mail** europetechsupport@chasecorp.com

**Contact person** Not available.

**1.4. Emergency telephone number** Chemtrec U.K. +44 (0) 870 820 0418

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and vapour.

##### Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Reproductive toxicity (the unborn child) Category 2 H361d - Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure Category 3 narcotic effects H336 - May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Category 2 H373 - May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Category 1 H304 - May be fatal if swallowed and enters airways.

**Environmental hazards**Hazardous to the aquatic environment,  
long-term aquatic hazard

Category 3

H412 - Harmful to aquatic life with  
long lasting effects.**Hazard summary**

May be ignited by heat, sparks or flames. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Causes skin irritation. Possible reproductive hazard. Prolonged exposure may cause chronic effects. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects.

**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended****Contains:** Ethylbenzene, Toluene**Hazard pictograms****Signal word** Danger**Hazard statements**

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements****Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P235 Keep cool.  
 P260 Do not breathe mist/vapours.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

**Response**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.  
 P331 Do NOT induce vomiting.  
 P370 + P378 In case of fire: Use appropriate media to extinguish.

**Storage**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal**

Not available.

**Supplemental label information**

2 % of the mixture consists of component(s) of unknown acute dermal toxicity.

**2.3. Other hazards**

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****Mixture****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Toluene	90 - 100	108-88-3 203-625-9	01-2119471310-51	601-021-00-3	#
<b>Classification:</b> Flam. Liq. 2;H225, Skin Irrit. 2;H315, Repr. 2;H361d, STOT SE 3;H336, STOT RE 2;H373, Asp. Tox. 1;H304, Aquatic Chronic 3;H412					
Xylene	5 - < 10	1330-20-7 215-535-7	-	601-022-00-9	#
<b>Classification:</b> Flam. Liq. 3;H226, Acute Tox. 4;H312, Acute Tox. 4;H332, Skin Irrit. 2;H315					
Ethylbenzene	1 - < 3	100-41-4 202-849-4	01-2119489370-35	601-023-00-4	#
<b>Classification:</b> Flam. Liq. 2;H225, Acute Tox. 4;H332, STOT RE 2;H373, Asp. Tox. 1;H304, Aquatic Chronic 3;H412					

## List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. #: This substance has been assigned Union workplace exposure limit(s).

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
<b>4.1. Description of first aid measures</b>	
<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>4.2. Most important symptoms and effects, both acute and delayed</b>	Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>4.3. Indication of any immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Highly flammable liquid and vapour.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Special fire fighting procedures</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
<b>For emergency responders</b>	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>6.2. Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

### 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	552 mg/m <sup>3</sup>
		125 ppm
	TWA	441 mg/m <sup>3</sup>
		100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m <sup>3</sup>
		100 ppm
	TWA	191 mg/m <sup>3</sup>
		50 ppm
Xylene (CAS 1330-20-7)	STEL	441 mg/m <sup>3</sup>
		100 ppm
	TWA	220 mg/m <sup>3</sup>
		50 ppm

##### EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m <sup>3</sup>
		200 ppm
	TWA	442 mg/m <sup>3</sup>
		100 ppm
Toluene (CAS 108-88-3)	STEL	384 mg/m <sup>3</sup>
		100 ppm
	TWA	192 mg/m <sup>3</sup>
		50 ppm

Components	Type	Value
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Biological limit values****UK. EH40 Biological Monitoring Guidance Values (BMGVs)**

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**Exposure guidelines****UK EH40 WEL: Skin designation**

Ethylbenzene (CAS 100-41-4)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
Xylene (CAS 1330-20-7)	Can be absorbed through the skin.

**8.2. Exposure controls**

**Appropriate engineering controls** Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment**

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Chemical respirator with organic vapour cartridge and full facepiece.

**Skin protection**

**- Hand protection** Wear appropriate chemical resistant gloves.

**- Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapour cartridge and full facepiece.

**Thermal hazards** Not applicable.

**Hygiene measures** Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

**Physical state** Liquid.

**Form** Not available.

**Colour** Clear.

**Odour** Aromatic

**Odour threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -94.9 °C (-138.82 °F) estimated

<b>Initial boiling point and boiling range</b>	110.6 °C (231.08 °F) estimated
<b>Flash point</b>	7.0 °C (44.6 °F) Closed cup
<b>Evaporation rate</b>	3.6 BuAc
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
Explosive limit - lower (%)	1.6
Explosive limit – upper (%)	11.2
<b>Vapour pressure</b>	3.56 kPa estimated
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
Solubility (water)	Negligible.
Solubility (other)	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	480 °C (896 °F) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.

## 9.2. Other information

Density 0.87 g/cm<sup>3</sup>

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong acids. Strong oxidising agents. Halogens.
<b>10.6. Hazardous decomposition products</b>	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms** Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

### 11.1. Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Product	Species	Test Results
HumiSeal Thinner 535		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	13270 mg/kg
<b>Inhalation</b>		
LC50	Rat	79380 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	2.9 g/kg

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	15400 mg/kg
<b>Inhalation</b>		
<i>Vapour</i>		
LC50	Rat	17.63 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	3500 mg/kg
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 5000 mg/kg > 5000 mg/kg, 24 Hours
<b>Inhalation</b>		
<i>Vapour</i>		
LC50	Rat	> 20 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg 2.6 - 7.5 g/kg

Xylene (CAS 1330-20-7)

<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	3523 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Skin sensitisation</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Carcinogenicity</b>	Risk of cancer cannot be excluded with prolonged exposure.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Mixture versus substance information</b>	No information available.	

## SECTION 12: Ecological information

**12.1. Toxicity** Harmful to aquatic life with long lasting effects.

Product	Species	Test Results	
HumiSeal Thinner 535			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	10.7497, 48 hours
Fish	LC50	Fish	81.8675, 96 hours
<i>Acute</i>			
Crustacea	EC50	Daphnia	3.8194, 48 hours estimated
Fish	LC50	Fish	5.2299, 96 hours estimated

Components	Species		Test Results
Ethylbenzene (CAS 100-41-4)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia	1.8, 48 hours
		Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fish	4.2, 96 hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Invertebrates (Invertebrates)	3.78, 48 hours
Fish	LC50	Fish	5.5, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	6.702 - 10.032 mg/l, 96 hours

**12.2. Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

### 12.3. Bioaccumulative potential

#### Partition coefficient

##### n-octanol/water (log Kow)

Ethylbenzene (CAS 100-41-4)	3.15
Toluene (CAS 108-88-3)	2.73

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

**12.6. Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

<b>ADR</b>	
<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	PAINT RELATED MATERIAL
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Hazard No. (ADR)</b>	33
<b>Tunnel restriction code</b>	D/E
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.



**RID**

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	PAINT RELATED MATERIAL
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**ADN**

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	PAINT RELATED MATERIAL
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
Label(s)	3
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**IATA**

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	Paint related material
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Other information**

<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

**IMDG**

<b>14.1. UN number</b>	UN1263
<b>14.2. UN proper shipping name</b>	PAINT RELATED MATERIAL, MARINE POLLUTANT
<b>14.3. Transport hazard class(es)</b>	
Class	3
Subsidiary risk	-
<b>14.4. Packing group</b>	II
<b>14.5. Environmental hazards</b>	
Marine pollutant	Yes
<b>EmS</b>	F-E, S-E
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

As per section 2.10.2.7 of IMDG Code: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 Kg or less for solids are not subject to any other provisions of the IMDG Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of the IMDG Code relevant to any additional hazards continue to apply.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Toluene (CAS 108-88-3)

#### Other EU regulations

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

#### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

**National regulations**

According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information****List of abbreviations**

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TWA: Time Weighted Average.

vPvB: Very persistent and very bioaccumulative.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.