













SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

HumiSeal Thinner 904

of the mixture

Registration number

Synonyms None.

HumiSeal Europe Thinner 904 **Product code**

15-December-2015 Issue date

Version number 02

15-December-2017 **Revision date** 15-December-2015 Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Thinner for Protective Coaiting **Identified uses**

None known. Uses advised against 1.3. Details of the supplier of the safety data sheet

Supplier

HUMISEAL EUROPE LTD. Company name

505 Eskdale Road **Address**

Winnersh

Wokingham Berkshire RG41 5TU

Division A CHASE CORPORATION COMPANY

Telephone General Assistance 44 (0) 118 944 2333

europetechsupport@chasecorp.com e-mail

Not available. Contact person

1.4. Emergency telephone

number

Chemtrec USA 1-800-424-9300

OutSide USA +1 703-741-5970

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

SDS UK

Health hazards

exposure

Skin corrosion/irritation H315 - Causes skin irritation. Category 2

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

dizziness.

Aspiration hazard Category 1 H304 - May be fatal if swallowed

and enters airways.

Environmental hazards

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long lasting effects.

Material name: HumiSeal Thinner 904

long-term aquatic hazard

HumiSeal Europe Thinner 904 Version #: 02 Revision date: 15-December-2017 Issue date: 15-December-2015

cause drowsiness and dizziness. Causes skin irritation. Dangerous for the environment if

discharged into watercourses.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: METHYL CYCLOHEXANE

Hazard pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapour.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/face protection.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.

P331 Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use appropriate media to extinguish.

P391 Collect spillage.

Storage

P235 Keep cool.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information 100 % of the mixture consists of component(s) of unknown acute oral toxicity. 100 % of the

mixture consists of component(s) of unknown acute dermal toxicity. 100 % of the mixture consists

of component(s) of unknown acute inhalation toxicity. 100 % of the mixture consists of

component(s) of unknown acute hazards to the aquatic environment.

2.3. Other hazardsNot a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
METHYL CYCLOHEXANE	90 - 100	108-87-2 203-624-3	01-2119556887-18-xxxx	601-018-00-7	

Classification: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Aquatic

Chronic 2;H411

Material name: HumiSeal Thinner 904

SDS UK

CAS-No. / EC **REACH Registration No.** INDEX No. Chemical name % Notes No. Ethyl cyclohexane 5 - < 10 1678-91-7 216-835-0 Classification: Aquatic Chronic 2;H411

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTRE or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Get medical attention if irritation develops and persists.

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and

delayed

Ingestion

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders

Material name: HumiSeal Thinner 904

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the

SDS). Not available.

7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Wear appropriate chemical resistant gloves. - Hand protection Wear appropriate chemical resistant clothing.

Respiratory protection

Chemical respirator with organic vapour cartridge and full facepiece.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Material name: HumiSeal Thinner 904

Environmental exposure

Inform appropriate managerial or supervisory personnel of all environmental releases.

controls

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid. Liquid. **Form** Colour Clear. Odour Aromatic Odour threshold Not available. Does not apply.

Melting point/freezing point -126.6 °C (-195.88 °F) estimated 100.9 °C (213.62 °F) estimated Initial boiling point and boiling

range

-6.0 °C (21.2 °F) Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

1.2 % estimated

(%)

Flammability limit - upper

6.7 % estimated

(%)

Vapour pressure 59.12 hPa estimated

Vapour density Not available. Not available Relative density

Solubility(ies)

Solubility (water) Nealiaible Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 250 °C (482 °F) estimated

Decomposition temperature Not available. **Viscosity** Not available. **Explosive properties** Not explosive. Oxidising properties Not oxidising

9.2. Other information

Density 0.78 g/cm3 Negligible Miscible (water) Percent volatile 100 % Specific gravity 0.78 100 % VOC

SECTION 10: Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. 10.1. Reactivity

Material is stable under normal conditions. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

No hazardous decomposition products are known. 10.6. Hazardous

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful

Causes skin irritation. Skin contact

Direct contact with eyes may cause temporary irritation. Eye contact

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

May be fatal if swallowed and enters airways. Acute toxicity

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation Skin sensitisation

Germ cell mutagenicity

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Carcinogenicity

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard

May be fatal if swallowed and enters airways.

Mixture versus substance

information

No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects. Due to partial or complete lack of data the

classification for hazardous to the aquatic environment, acute hazard, is not possible.

Components **Species Test results**

Ethyl cyclohexane (CAS 1678-91-7)

Aquatic

Fish LC50 6 - 13 mg/l, 96 hours Striped bass (Morone saxatilis)

METHYL CYCLOHEXANE (CAS 108-87-2)

Aquatic

Fish LC50 Striped bass (Morone saxatilis) 5.8 mg/l, 96 hours

12.2. Persistence and

degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

> METHYL CYCLOHEXANE 3.61

Not available. **Bioconcentration factor (BCF)** 12.4. Mobility in soil

12.5. Results of PBT

No data available.

and vPvB

Not a PBT or vPvB substance or mixture.

assessment 12.6. Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: HumiSeal Thinner 904

HumiSeal Europe Thinner 904 Version #: 02 Revision date: 15-December-2017 Issue date: 15-December-2015

^{*} Estimates for product may be based on additional component data not shown.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1263

Paint related material 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Subsidiary risk Label(s) 3 Hazard No. (ADR) 33 D/E **Tunnel restriction code** 14.4. Packing group

14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1263

14.2. UN proper shipping Paint related material

name

14.3. Transport hazard class(es)

3 Subsidiary risk 3 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1263

Paint related material 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

3 Class Subsidiary risk 3 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1263

14.2. UN proper shipping Paint Related Material

name

14.3. Transport hazard class(es)

3 Class Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards No. **ERG Code**

14.6. Special precautions

for user

Other information

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

14.1. UN number UN1263 14.2. UN proper shipping PAINT RELATED MATERIAL

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk
14.4. Packing group ||

14.5. Environmental hazards

Marine pollutant No. EmS F-E, S-E

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Transport in bulk Not established.

according to Annex II of Marpol and the IBC Code

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended METHYL CYCLOHEXANE (CAS 108-87-2)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

METHYL CYCLOHEXANE (CAS 108-87-2)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. Additional information is given in the Safety Data Sheet.

Material name: HumiSeal Thinner 904

SDS UK

National regulations Follow national regulation for work with chemical agents.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Not available. List of abbreviations Not available. References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under

Sections 2 to 15

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material. **Training information**

Disclaimer The information and recommendations in this safety data sheet are, to the best of our knowledge,

accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this

information and the suitability of the material or product for any particular purpose