

HumiSeal[®] Thinner 673

Technical Data Sheet

The use of HumiSeal coatings may be required, at times, to lower the viscosity of the product as received from the factory. This can be readily achieved by adding to the coating a pre-determined amount of HumiSeal Thinner assigned to the particular type of HumiSeal coating used. HumiSeal thinners are blends of solvents and diluents, which are carefully formulated to maintain the original optimum system balance when added to the corresponding coating type.

Properties of HumiSeal[®] Thinner 673

THINNER NO.	673
CHEMICAL TYPE	Ketone/Ester
Relative Evaporation rate (BuAC = 1)	2.1
Specific Gravity	0.89
Boiling Point °C	141
Vapour Pressure (mmHg)	49
Vapour density (Air =1)	3.5
Flash point °C (TCC)	-9
Shelf Life	18 months
Colour	Clear

Directions For Use: Add HumiSeal Thinner until desired viscosity is obtained.

Handling Precautions: HumiSeal Thinners are flammable and the following standard safety precautions should still be observed. Use in well ventilated area. Protective gloves and goggles should be worn. In case of prolonged skin contact, wash with water. In case of eye contact, wash with water. Avoid prolonged breathing of vapors.

Unused portions of HumiSeal products must be disposed of in strict compliance with Local, State, and Federal laws governing such matters. Refer to the appropriate Material Safety Data Sheet (MSDS) for more specific product information.

Consult MSDS/SDS prior to use.

Contact HumiSeal®

HumiSeal North America

201 Zeta Drive
Pittsburgh, PA 15238
USA
Tel: +1 412-828-1500
Toll Free (US only): 866-828-5470
sales@humiseal.com

HumiSeal Technical Center

295 University Avenue
Westwood, MA 02090
USA
Tel: +1 781-332-0734
Fax: +1 781-332-0703
techsupport@humiseal.com

HumiSeal Europe

505 Eskdale Road, IQ Winnersh
Berkshire RG41 5TU
UK
Tel: +44 (0)1189 442 333
Fax: +44 (0)1189 335 799
europesales@chasecorp.com

HumiSeal Europe Support

Tel: +44 (0)1189 442 333
Fax: +44 (0)1189 335 799
europetechsupport@chasecorp.com

HumiSeal S.A.R.L

4/6 Avenue Eiffel
78420 Carrieres-Sur-Seine
France
Tel: +33 (0) 1 30 09 86 86
Fax: +33 (0) 1 30 09 86 87
humiseal.sarl@chasecorp.com

HumiSeal Asian Support

Tel: 852-9451-6434
Fax: 852-2413-6289
asiatechsupport@humiseal.com

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.