













# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Humiseal UV40 Solar

of the mixture

Registration number

**Synonyms** None.

HumiSeal Europe UV40 Solar **Product code** 

22-February-2017 Issue date

Version number 02

04-January-2018 **Revision date** 22-February-2017 Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Protective Coating for Printed Circuit Board **Identified uses** 

None known. Uses advised against 1.3. Details of the supplier of the safety data sheet

**Supplier** 

HUMISEAL EUROPE LTD. Company name

505 Eskdale Road **Address** 

Winnersh

Wokingham Berkshire RG41 5TU

**Division** A CHASE CORPORATION COMPANY

Telephone General Assistance 44 (0) 118 944 2333

europetechsupport@chasecorp.com e-mail

Not available. Contact person

1.4. Emergency telephone

number

Chemtrec USA

1-800-424-9300

OutSide USA +1 703-741-5970

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

### Classification according to Regulation (EC) No 1272/2008 as amended

**Health hazards** 

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Specific target organ toxicity - single exposure

Category 3 respiratory tract irritation

H335 - May cause respiratory

irritation.

**Environmental hazards** 

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with long-term aquatic hazard

long lasting effects.

**Hazard summary** Harmful in contact with skin. Causes serious eye irritation. Causes skin irritation. May cause

irritation to the respiratory system. Dangerous for the environment if discharged into

watercourses.

Material name: Humiseal UV40 Solar

SDS UK

#### 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, ISOBORNYL ACRYLATE, n-Butyl acetate

**Hazard pictograms** 



Signal word Wa	rnıng
----------------	-------

#### **Hazard statements**

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

#### Prevention

P261 Avoid breathing mist or vapour.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.
P280 Wear eye protection/face protection.
P280 Wear protective gloves/protective clothing.

#### Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a PÓISON CENTRE/doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

#### **Storage**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

### Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Supplemental label information

94.55 % of the mixture consists of component(s) of unknown acute oral toxicity. 97.24 % of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute dermal toxicity. 94.55 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 97.24 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 60.91 % of the mixture consists of unknown long-term hazards to the aquatic environment. 60.91 % of the mixture consists of

component(s) of unknown long-term hazards to the aquatic environment.

# **2.3. Other hazards** None known.

### **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### **General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
ISOBORNYL ACRYLATE	30 - < 4	5888-33-5 227-561-6	01-2119957862-25-XXXX	607-133-00-9	
Classification: S	kin Irrit. 2;H315, Ey	e Irrit. 2;H319, STO	T SE 3;H335, Aquatic Chronic	2;H411	Α
n-Butyl acetate	1 - < 3	123-86-4 204-658-1	01-2119485493-29-xxxx	607-025-00-1	
Classification: Fi	lam. Liq. 3;H226, S	TOT SE 3;H336, Aq	uatic Chronic 3;H412		
Phenylbis(2,4,6-trimethylbersphine oxide	nzoyl)pho < 1	162881-26-7 423-340-5	01-2119936813-33-xxxx	015-189-00-5	
Classification: S	kin Sens. 1;H317, A	Aquatic Chronic 4;H4	413		

Material name: Humiseal UV40 Solar

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Tosyl isocyanate		< 1	4083-64-1 223-810-8	01-211990050-47-XXXX	615-012-00-7	
Classification:	Skin Irrit. 2;H	315, Eye	Irrit. 2;H319, Resp.	Sens. 1;H334, STOT SE 3;H3	335	
Bis(1,2,2,6,6-pentamethyl-4sebacate	1-piperidyl)	< 0.3	41556-26-7 255-437-1	-	-	
Classification: -						

Other components below reportable levels 60 - < 70

# List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

**Composition comments** The full text for all R- and H-phrases is displayed in section 16.

### **SECTION 4: First aid measures**

**General information** If you feel unwell, seek medical advice (show the label where possible). Ensure that medical

personnel are aware of the material(s) involved, and take precautions to protect themselves. Show

this safety data sheet to the doctor in attendance.

### 4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTRE or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention

if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated

clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical advice/attention if you feel unwell. Ingestion

4.2. Most important symptoms and effects, both acute and

delayed

4.3. Indication of any

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

immediate medical attention and special treatment needed under observation. Symptoms may be delayed.

### **SECTION 5: Firefighting measures**

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Unsuitable extinguishing

media

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

procedures

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Humiseal UV40 Solar

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the For emergency responders

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth

and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

# **SECTION 7: Handling and storage**

7.1. Precautions for safe

handling

Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials

(see Section 10 of the SDS).

Not available. 7.3. Specific end use(s)

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Occupational exposure limits

UK. EH40	) Workplace	Exposure	Limits	(WELs)

Components	Туре	Value	
n-Butyl acetate (CAS 123-86-4)	STEL	966 mg/m3	
,		200 ppm	
	TWA	724 mg/m3	
		150 nnm	

**Biological limit values** 

procedures

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available

Predicted no effect concentrations (PNECs) Not available.

### 8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

Use personal protective equipment as required. Personal protection equipment should be chosen **General information** 

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. - Other

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with Respiratory protection

organic vapour cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material Hygiene measures

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

**Environmental exposure** 

controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

**Appearance** 

Liquid. Physical state **Form** Liquid. Colour Light yellow. Characteristic. Odour **Odour threshold** Not available. Does not apply. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point 76.0 °C (168.8 °F)

**Evaporation rate** < 1 BuAc Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit - upper

Not available.

0.03 hPa estimated Vapour pressure Vapour density Not available. Not available Relative density

Solubility(ies)

Solubility (water) Negligible Not available. **Partition coefficient** 

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. 500 - 800 cP **Viscosity** 20 °C (68 °F) Viscosity temperature **Explosive properties** Not explosive. Oxidising properties Not oxidising

9.2. Other information

500 - 800 cP **Brookfield viscosity Density** 1.06 g/cm3 Miscible (water) Negligible 3 % v/v Percent volatile Specific gravity 1.06 VOC 35 g/l

# **SECTION 10: Stability and reactivity**

The product is stable and non-reactive under normal conditions of use, storage and transport. 10.1. Reactivity

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

Material name: Humiseal UV40 Solar

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Harmful in contact with skin. Causes skin irritation. Skin contact

Eve contact Causes serious eye irritation.

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of Ingestion

occupational exposure.

**Symptoms** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

### 11.1. Information on toxicological effects

In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and **Acute toxicity** 

central nervous system effects. Harmful in contact with skin. May cause respiratory irritation.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eve irritation.

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Skin sensitisation Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Carcinogenicity Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

**Aspiration hazard** Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Not available. Other information

# **SECTION 12: Ecological information**

12.1. Toxicity Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are

not met for hazardous to the aquatic environment, acute hazard.

Components Species **Test results** 

n-Butyl acetate (CAS 123-86-4)

**Aquatic** 

12.2. Persistence and

LC50 Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours Fish

\* Estimates for product may be based on additional component data not shown.

degradability

No data is available on the degradability of this product.

12.3. Bioaccumulative potential

**Partition coefficient** n-octanol/water (log Kow)

n-Butyl acetate 1.78

Not available. **Bioconcentration factor (BCF)** No data available 12.4. Mobility in soil 12.5. Results of PBT Not available.

assessment

and vPvB

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Material name: Humiseal UV40 Solar

HumiSeal Europe UV40 Solar Version #: 02 Revision date: 04-January-2018 Issue date: 22-February-2017

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow Disposal methods/information

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. **Special precautions** 

# **SECTION 14: Transport information**

#### **ADR**

14.1. UN number

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ISOBORNYL ACRYLATE)

name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) Hazard No. (ADR) 90 **Tunnel restriction code** Ε 14.4. Packing group Ш 14.5. Environmental hazards Yes

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN3082

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ISOBORNYL ACRYLATE)

name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards Yes

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

**ADN** 

14.1. UN number UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ISOBORNYL ACRYLATE) 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

9 Class Subsidiary risk 9 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards Yes

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

**IATA** 

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG** 

14.1. - 14.6.: Not regulated as dangerous goods.

Not established.


14.7. Transport in bulk according to Annex II of Marpol

and the IBC Code

Material name: Humiseal UV40 Solar

HumiSeal Europe UV40 Solar Version #: 02 Revision date: 04-January-2018 Issue date: 22-February-2017

ADN; ADR; RID



#### Marine pollutant



# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ISOBORNYL ACRYLATE (CAS 5888-33-5)

n-Butyl acetate (CAS 123-86-4)

Tosyl isocyanate (CAS 4083-64-1)

The product is classified and labelled in accordance with EC directives or respective national laws. Other regulations

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as

**National regulations** Follow national regulation for work with chemical agents.

No Chemical Safety Assessment has been carried out. 15.2. Chemical safety

assessment

### **SECTION 16: Other information**

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

**Revision information** SECTION 2: Hazards identification: Hazard statements

SECTION 2: Hazards identification: Supplemental label information Composition / Information on Ingredients: Ingredient Classification

SECTION 5: Firefighting measures: General fire hazards

SECTION 16: Other information: Disclaimer

**Training information** Follow training instructions when handling this material.

**Disclaimer**The information and recommendations in this safety data sheet are, to the best of our knowledge,

accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, expressed or implied. It is the responsibility of the user to determine the applicability of this

information and the suitability of the material or product for any particular purpose

Material name: Humiseal UV40 Solar

SDS UK