



## Heavy duty concentrated degreaser for ultrasonics

### AQUASOLV Ultrasonic Cleaner-Plus (Aqua 22)

S

#### FEATURES/BENEFITS:

<b>Powerful</b>	Removes heavy oils & greases, brake dust and carbon contamination
<b>Efficient</b>	Highly concentrated, can be used effectively at low concentrations
<b>Specifically Formulated</b>	Cavitates & de-gases easily to maximise ultrasonic cleaning action
<b>Non-Flammable</b>	Improves safety profile in the workplace
<b>Multi-Surface Compatible</b>	For Ferrous & Non-Ferrous metals, plastics, rubber and glass
<b>Non-staining</b>	Can be used with Aluminium components without blackening or staining

#### USE:

Ultrasonic Cleaner-Plus is used at 2-5% dilution in water and at operating temperatures between 40-70 °C depending on soil. It can be used in single or multi-stage ultrasonic cleaning processes.

#### APPLICATIONS:

For use in Ultrasonic Cleaning Baths. The Plus formulation removes heavy oils, greases, stubborn contaminants and brake dust in remanufacturing operations. Designed to be used at 5-10% dilution. Compatible with aluminium. Ideal for maintenance, overhaul and interstage cleaning processes.

#### PRECAUTIONS:

*For further information see MSDS*

#### SPECIFICATIONS:

Form ..... Liquid  
Colour ..... Brown  
Odour ..... Non descript  
Melting Point..... Undetermined  
Boiling point..... 100 °C  
Flashpoint: ..... Non applicable  
Density (20 °C) ..... 1,1 g/cm<sup>3</sup>  
Miscibility in water ..... Fully miscible  
pH (20 °C) ..... 12