

SAFETY DATA SHEET

This Safety Data Sheet is provided in compliance with the EC Regulations 1907/2006, 1272/2008, 2015/830 and 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: RT125 PART A (RESIN)

- UFI: Not applicable

- Product Part Number: RT125 PART A (RESIN)

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Resin

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Resintech Ltd

- Address of Supplier: Unit 1-2 Horcott Industrial Estate

Fairford

Gloucestershire GL7 4BX

UK

- Telephone: +44 (0)1285 712755

- Responsible Person: Alex Paton

- Email: Info@resintech.co.uk

1.4 Emergency telephone number

- Emergency Telephone: +44 (0)1285712755 (Monday-Friday 8am-4.30pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- CLP: Skin Sens. 1, Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2

2.2 Label elements





- Signal Word: Warning

- Contains: Bis-[4-(2,3-epoxipropoxi)phenyl]propane

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

Datasheet Number: RT125 PART A (RESIN) - v5.3.0

SECTION 2: Hazards identification (....)

Precautionary statements

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P501 - Dispose of contents/container to an authorised waste collection point

Supplemental Hazard information (EU)

EUH205 - Contains epoxy constituents. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

2.3 Other hazards

- Not a PBT according to REACH Annex XIII
- Substance not identified as having endocrine disrupting properties

SECTION 3: Composition/information on ingredients

3.2 Mixtures

	CAS Number	EC Number	REACH Registration Number	Categories	H Statements	Concentration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	01-2119456619- 26-0000	Skin Irrit. 2 Skin Sens. 1 Eye Irrit. 2 Aquatic Chronic 2	H315 H317 H319 H411	50 - 70%
Kaolin	1332-58-7	310-194-1	Not applicable	Substance with a work place exposure limit	None	10 - 30%
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	271-893-4	01-2119379499- 16-0000	Substance with a work place exposure limit	None	1 - 5%
Carbon Black	1333-86-4	215-609-9	01-2119384822- 32-0000	Substance with a work place exposure limit	None	<1%
titanium dioxide	13463-67-7	236-675-5	Not applicable	Carc. 2	H351	<1%

SECTION 4: First aid measures

4.1 General

- Use personal protective equipment as required.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)
- Wash contaminated clothing before reuse.
- In cases of severe exposure, allergic reaction in susceptible people may develop

Contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Datasheet Number: RT125 PART A (RESIN) - v5.3.0

SECTION 4: First aid measures (....)

Contact with skin

If skin irritation or rash occurs: Get medical advice/attention.

After contact with skin, wash immediately with plenty of soap and water

Ingestion

If swallowed, rinse mouth with water (only if the person is conscious) Give water or milk to drink
Get medical advice/attention if you feel unwell.

Inhalation

Remove patient to fresh air Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

- In cases of severe exposure, allergic reaction in susceptible people may develop
- In cases of severe exposure, redness and irritation may develop

4.3 Indication of any immediate medical attention and special treatment needed

- Treat symptomatically

SECTION 5: Firefighting measures

5.1 Extinguishing media

- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide

5.2 Special hazards arising from the substance or mixture

- Decomposition products may include toxic and irritant fumes
- Decomposition products may include carbon oxides
- Decomposition products may include aldehydes
- Hydrogen chloride may be formed

5.3 Advice for firefighters

- Keep container(s) exposed to fire cool, by spraying with water
- Prevent run off water from entering drains if possible
- Wear Positive-Pressure Breathing Apparatus

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Wear protective clothing as per section 8
- Wash thoroughly after dealing with spillage
- Avoid contact with skin and eyes

6.2 Environmental precautions

- Avoid release to the environment.
- Absorb spillage in suitable inert material
- Do not discharge into drains or the environment, dispose to an authorised waste collection point
- immiscible with water

6.3 Methods and material for containment and cleaning up

- Wear protective clothing as per section 8

Datasheet Number: RT125 PART A (RESIN) - v5.3.0

RT125 PART A (RESIN)

Revised: 24/6/2024

SECTION 6: Accidental release measures (....)

- Absorb spillage in suitable inert material
- Do not discharge into drains or the environment, dispose to an authorised waste collection point
- Wash thoroughly after dealing with spillage
- Collect spillage.

6.4 Reference to other sections

- Wear protective clothing as per section 8
- See Section 11 Toxicological Information

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Avoid release to the environment.
- Wear protective clothing as per section 8
- Take off contaminated clothing and wash it before reuse.
- In cases of severe exposure, allergic reaction in susceptible people may develop
- Do not eat, drink or smoke when using this product.
- After contact with skin, wash immediately with plenty of soap and water
- Wash hands and working surfaces thoroughly after handling.
- Use good personal hygiene practices
- Wash contaminated clothing before reuse.
- Dispose of contents/container to an authorised waste collection point

7.2 Conditions for safe storage, including any incompatibilities

- Keep container tightly closed, in a cool, well ventilated place
- Keep cool. Protect from sunlight.
- Keep away from food, drink and animal feedingstuffs

7.3 Specific end use(s)

- See Section 1.2

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

bis-[4-(2,3-epoxipropoxi)phenyl]propane

DNEL (Industry; inhalational, long term systemic effects): 4.93 mg/m³

DNEL (Industry; dermal, long term systemic effects): 0.75 mg/kg bw/day

DNEL (Consumer; inhalational, long term systemic effects): 0.87 mg/m³

DNEL (Consumer; dermal, long term systemic effects): 0.0893 mg/kg bw/day

DNEL (Consumer; oral, long term systemic effects): 0.5 mg/kg bw/day

Kaolin

WEL (respirable dust): 2 mg/m³ (8 hour TWA)

Silane, dichlorodimethyl-, reaction products with silica

WEL (inhalable dust): 6 mg/m³ (8 hour TWA)
WEL (respirable dust): 2.6 mg/m³ (8 hour TWA)

Carbon Black

Datasheet Number: RT125 PART A (RESIN) - v5.3.0

SECTION 8: Exposure controls/personal protection (....)

DNEL (Industry; inhalational, long term systemic effects): 1 mg/m³ DNEL (Consumer; inhalational, long term systemic effects): 0.06 mg/m³

WEL (inhalable dust): (TWA) 3 mg/m³ (BE), (TWA) 2 mg/m³ (CZ), (TWA) 3.5 mg/m³ (DK), (TWA) 3.5 mg/m³ (FI),

(STEL) 7 mg/m³ (FI), (TWA) 3.5 mg/m³ (FR), (TWA) 3.5 mg/m³ (GR), (STEL) 7 mg/m³ (GR), (TWA) 3 mg/m³ (IE), (STEL) 15 mg/m³ (IE), (TWA) 3 mg/m³ (IT), (TWA) 3.5 mg/m³ (NO), (STEL) 7 mg/m³ (NO), (TWA) 4 mg/m³ (PL), (TWA) 3 mg/m³ (PT), (TWA) 2 mg/m³ (SK), (STEL) 10 mg/m³ (SK), (TWA) 3.5 mg/m³ (ES), (TWA) 3 mg/m³ (SE), (TWA) 3.5 mg/m³ (UK),

(STEL) 7 mg/m3 (UK), (USA) TLV (TWA): 3 mg/m3

8.2 Exposure controls







- This Safety Data Sheet does not constitute a workplace risk assessment
- In case of inadequate ventilation wear respiratory protection.
- Eyewash bottles should be available
- Wear suitable protective clothing, eye/face protection and gloves
- Gloves should be chemical resistant and comply with an approved standard such as EN 455 or EN 374 and made from latex, nitrile or neoprene.

Protective clothing should based on the results of an exposure assessment. A polymer laminate apron is recommended in most cases.

Eye and face protection should be chemical resistant and comply with an approved standard such as EN 166.

If a respirator is needed following an exposure assessment it should conform to EN 136 or EN 143 (P3)

- Check with personal protection equipment manufacturer
- Use good personal hygiene practices
- Do not eat, drink or smoke when using this product.
- Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: PasteColour: Black

- Odour: Characteristic odour

- Boiling Point/Range: ≥200°C

Flammability: Flash point: ≥150 °C (CC)
 pH: Immiscible with water
 Solubility in water: Immiscible with water
 Density: Density (water=1): 1.27

9.2 Other information

- No information available

SECTION 10: Stability and reactivity

Datasheet Number: RT125 PART A (RESIN) - v5.3.0

SECTION 10: Stability and reactivity (....)

10.1 Reactivity

- Reference to other sections

10.2 Chemical stability

- Considered stable under normal conditions

10.3 Possibility of hazardous reactions

- No hazardous reactions known if used for its intended purpose

10.4 Conditions to avoid

- No hazard expected under normal conditions of use

10.5 Incompatible materials

- Strong oxidising agent
- Strong acids

10.6 Hazardous decomposition products

- No hazardous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Estimated LD₅₀ (oral) (ATE) : >2000 mg/kgEstimated LD₅₀ (dermal) (ATE) : >4000 mg/kg

Estimated LD₅₀ (inhalational) (ATE): >20 mg/l/4hr (gas/vapour)

bis-[4-(2,3-epoxipropoxi)phenyl]propane

LD₅₀ (oral, rat): >15,000 mg/kg LD₅₀ (skin, rat): >23,000 mg/kg

titanium dioxide

LD₅₀ (dermal, rabbit): >10,000 mg/kg

LC₅₀ (inhalation, rat): >6.82 mg/l/dust/mist 4h

LD₅₀ (oral, rat): >10,000 mg/kg

Silane, dichlorodimethyl-, reaction products with silica

LD₅₀ (oral, rat): >5,000 mg/kg

Carbon Black

 LD_{50} (oral, rat): >2,000 mg/kg LD_{50} (dermal, rabbit): >2,000 mg/kg LC_{50} (inhalation, rat): (4h) >4.6 mg/m³

Kaolin

Estimated LD₅₀ (dermal) (ATE) : >5,000 mg/kg Estimated LD₅₀ (oral) (ATE) : >10,000 mg/kg

Skin corrosion/irritation

SECTION 11: Toxicological information (....)

May cause irritation

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on the available data, the classification criteria are not met

Germ cell mutagenicity

Based on the available data, the classification criteria are not met

Carcinogenicity

Based on the available data, the classification criteria are not met

Contains: Titanium Dioxide

Reproductive toxicity

Based on the available data, the classification criteria are not met

STOT (specific target organ toxicity) - single exposure

Based on the available data, the classification criteria are not met

STOT (specific target organ toxicity) - repeated exposure

Based on the available data, the classification criteria are not met

Aspiration hazard

Based on the available data, the classification criteria are not met

11.2 Information on other hazards

- No information available

SECTION 12: Ecological information

12.1 Toxicity

bis-[4-(2,3-epoxipropoxi)phenyl]propane

EC₅₀ (daphnia): 1.8 mg/l (48 hr) LC₅₀ (fish): 2 mg/l (96 hr) PNEC (Fresh water): 0.006 mg/l PNEC (intermittent): 0.018 mg/l PNEC (Marine water): 0.0006 mg/l PNEC (Sediment; fresh water): 0.341 mg/kg PNEC (Sediment; marine water): 0.0341 mg/kg PNEC (Soil): 0.0647 mg/kg PNEC (STP): 10 mg/l

titanium dioxide

Datasheet Number: RT125 PART A (RESIN) - v5.3.0

RT125 PART A (RESIN)

Revised: 24/6/2024

SECTION 12: Ecological information (....)

 EC_{50} (daphnia): >100 mg/l (48 hr) LC_{50} (fish): >100 mg/l (96 hr)

Silane, dichlorodimethyl-, reaction products with silica

LC₅₀ (fish): >10,000 mg/l (96 hr)

Carbon Black

EC₅₀ (daphnia): >1,000 mg/l (48 hr) LC₅₀ (fish): >1,000 mg/l (96 hr)

PNEC (Fresh water): 50 mg/l

Kaolin

EC₅₀ (daphnia): >1,100 mg/l/48h, Estimated Value

12.2 Persistence and degradability

- Not readily biodegradable

12.3 Bioaccumulative potential

- Bioaccumulation is insignificant

12.4 Mobility in soil

- immiscible with water

12.5 Results of PBT and vPvB assessment

- Not a PBT according to REACH Annex XIII

12.6 Endocrine disrupting properties

- Substance not identified as having endocrine disrupting properties

12.7 Other adverse effects

- No information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
- Wear protective clothing as per section 8
- Dispose of contents/container to an authorised waste collection point

SECTION 14: Transport information





14.1 UN number or ID number

- UN No.: 3082

14.2 UN proper shipping name

- Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane)

RT125 PART A (RESIN)

Revised: 24/6/2024

SECTION 14: Transport information (....)

14.3 Transport hazard class(es)

- Hazard Class: 9

14.4 Packing group

- Packing Group: III

14.5 Environmental hazards

- Marine Pollutant
- Environmentally hazardous

14.6 Special precautions for user

IMDG EmS: F-A, S-FTunnel Code: (E)Emergency Action Code: 3Z

14.7 Maritime transport in bulk according to IMO instruments

- Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- This Safety Data Sheet is provided in compliance with the Health and Safety at Work Act
- This Safety Data Sheet is provided in compliance with the EC Regulations 1907/2006, 1272/2008, 2015/830 and 2020/878

15.2 Chemical safety assessment

- This product is either exempt from REACH or does not meet the minimum volume threshold for a chemical safety assessment (CSA)

SECTION 16: Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H351: Suspected of causing cancer. H411: Toxic to aquatic life with long lasting effects.

Sections updated: 1.1, 8.2, 11.1, 12.1

This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own use.

Datasheet Number: RT125 PART A (RESIN) - v5.3.0