Regulation (EU) n. 2020/878

Safety Data Sheet date: 28/7/2022, version 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: HYSO 99 SDS code: P20000

UFI: C6YR-RMTK-RU1N-HR52

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Solvent

Cleaner

Industrial uses

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel: +33 (0)2 97 43 76 83 - Fax: +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax

+353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel: +33 (0)2 97 43 76 83 - Fax: +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax

+353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France: ORFILA (INRS) +33 (0)1 45 42 59 59 International: CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- igoplus Warning, STOT SE 3, May cause drowsiness or dizziness.
- Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.
- Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS

propan-2-ol; isopropyl alcohol; isopropanol

cyclohexane

n-hexane

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. N	umber	Classification
>= 90%	HYDROCARBONS, C7-C9, N-ALKANES.	EC:	920-750-0	♦ 2.6/2 Flam. Liq. 2 H225
	ISOALKANES,			

	CYCLICS	REACH No.:	01- 2119473851 -33	 \$3.10/1 Asp. Tox. 1 H304 \$3.8/3 STOT SE 3 H336 \$4.1/C2 Aquatic Chronic 2 H411 EUH066
>= 1% - < 3%	propan-2-ol; isopropyl alcohol; isopropanol	Index number: CAS: EC: REACH No.:	603-117-00-0 67-63-0 200-661-7 01- 2119457558 -25	 2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336
>= 1% - < 3%	cyclohexane	Index number: CAS: EC:	601-017-00-1 110-82-7 203-806-2	 \$2.6/2 Flam. Liq. 2 H225 \$3.10/1 Asp. Tox. 1 H304 \$3.2/2 Skin Irrit. 2 H315 \$3.8/3 STOT SE 3 H336 \$4.1/A1 Aquatic Acute 1 H400 \$4.1/C1 Aquatic Chronic 1 H410
>= 1% - < 3%	n-hexane	Index number: CAS: EC:	601-037-00-0 110-54-3 203-777-6	 \$2.6/2 Flam. Liq. 2 H225 \$3.7/2 Repr. 2 H361f \$3.10/1 Asp. Tox. 1 H304 \$3.9/2 STOT RE 2 H373 \$3.2/2 Skin Irrit. 2 H315 \$3.8/3 STOT SE 3 H336 \$4.1/C2 Aquatic Chronic 2 H411 Specific Concentration Limits: C >= 5%: STOT RE 2 H373

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS

- OEL Type: National TWA: 1200 mg/m3, 260 ppm Notes: ExxonMobil
- OEL Type: National TWA: 1000 mg/m3 STEL: 1500 mg/m3 Notes: vapor, France propan-2-ol; isopropyl alcohol; isopropanol CAS: 67-63-0
 - OEL Type: National STEL: 980 mg/m3, 400 ppm Notes: France
 - OEL Type: National TWA: 500 mg/m3, 200 ppm Notes: DFG, Y Germany
 - OEL Type: National TWA: 999 mg/m3, 400 ppm STEL: 1250 mg/m3, 500 ppm -

Notes: United Kingdom

- OEL Type: ACGIH TWA(8h): 200 ppm STEL: 400 ppm Notes: A4, BEI Eye and URT irr, CNS impair
- OEL Type: National TWA: 999 mg/m3, 400 ppm STEL: 1250 mg/m3, 500 ppm
- OEL Type: OSHA PEL TWA: 980 mg/m3, 400 ppm
- OEL Type: NIOSH REL TWA: 980 mg/m3, 400 ppm STEL: 1225 mg/m3, 500 ppm
- OEL Type: National TWA: 500 mg/m3, 200 ppm STEL(30min (Miw)): 1960 mg/m3, 800 ppm Notes: Österreich

cyclohexane - CAS: 110-82-7

- OEL Type: National TWA(8h): 700 mg/m3, 200 ppm Notes: Germany
- OEL Type: National TWA(8h): 700 mg/m3, 200 ppm STEL: 1300 mg/m3, 375 ppm -

Notes: France VLEC - INRS TMP N° 84

- OEL Type: EU TWA(8h): 700 mg/m3, 200 ppm
- OEL Type: ACGIH TWA(8h): 100 ppm Notes: CNS impair
- OEL Type: National TWA(8h): 700 mg/m3, 200 ppm STEL(15'): 2800 mg/m3, 800 ppm Notes: Österreich
- OEL Type: National TWA(8h): 200 ppm Notes: Cyprus
- OEL Type: National TWA(8h): 700 mg/m3 STEL: 2000 mg/m3 Notes: Czech Republic
- OEL Type: National TWA: 50 ppm Notes: Denmark
- OEL Type: National TWA(8h): 350 mg/m3, 100 ppm STEL(15'): 1050 mg/m3, 300 ppm Notes: United Kingdom

n-hexane - CAS: 110-54-3

- OEL Type: National - TWA(8h): 72 mg/m3, 20 ppm - Notes: France VLEC - Note R3 - INRS TMP N° 59, 84

- OEL Type: National TWA(8h): 180 mg/m3, 50 ppm Notes: Germany
- OEL Type: EU TWA(8h): 72 mg/m3, 20 ppm
- OEL Type: ACGIH TWA(8h): 50 ppm Notes: Skin, BEI CNS impair, peripheral neuropathy, eye irr
- OEL Type: National TWA: 72 mg/m3, 20 ppm STEL(15min (Miw)): 288 mg/m3, 80 ppm Notes: Österreich
- OEL Type: National TWA(8h): 72 mg/m3, 20 ppm Notes: UK

DNEL Exposure Limit Values

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS

Worker Industry: 773 mg/kg b.w./day - Consumer: 699 mg/kg b.w./day - Exposure: Human

Dermal - Frequency: Short Term, systemic effects

Worker Industry: 2035 mg/m3 - Consumer: 608 mg/m3 - Exposure: Human Inhalation -

Frequency: Short Term, systemic effects

Consumer: 699 mg/kg b.w./day - Exposure: Human Oral - Frequency: Short Term,

systemic effects

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Worker Industry: 500 mg/kg - Consumer: 89 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

n-hexane - CAS: 110-54-3

Worker Industry: 773 mg/kg b.w./day

Worker Industry: 2035 mg/m3

PNEC Exposure Limit Values

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Target: Fresh Water - Value: 140.9 mg/l Target: Marine water - Value: 140.9 mg/l

Target: Freshwater sediments - Value: 552 mg/kg Target: Marine water sediments - Value: 552 mg/kg

Target: Soil (agricultural) - Value: 28 mg/kg

Target: Microorganisms in sewage treatments - Value: 2251 mg/l

Target: Water (intermittent discharge) - Value: 140.9 mg/l

Target: Oral (secondary poisoning) (foodstuff) - Value: 160 mg/kg

Biological Exposure Index

n-hexane - CAS: 110-54-3

Value: 5 mg/g - medium: Urinary creatinine - Biological Indicator: 2.5-hexanedione in the

urine - Sampling Period: End of turn - Source: IBE

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Use closed fitting safety goggles, don't use eye lens.

Safety goggles (EN 166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable gloves type: NF EN374

NBR (nitrile rubber). PVA (Polyvinyl alcohol). Respiratory protection:

Use adequate protective respiratory equipment.

Mask with filter "A1", brown colour (NF EN14387)

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid		
Colour:	Colourless		
Odour:	N.A.		
Melting point/freezing point:	Not Relevant		
Boiling point or initial boiling point and boiling range:	82 °C	NF T67-101	
Flammability:	Flam. Liq. 2, H225		
Lower and upper explosion limit:	N.A.		liquid
Flash point (°C):	-7 °C	NF EN 2719	
Auto-ignition temperature:	287 °C		
Decomposition temperature:	N.A.		
pH:	N.A.		
Kinematic viscosity:	<= 14 mm2/ sec (40 °C)		

Solubility in water:	N.A.			
Solubility in oil:	N.A.			
Partition coefficient n-octanol/water (log value):	N.A.			
Vapour pressure:	11.9 mmHg (20°C)			
Density and/or relative density:	0.733	ISO 649, ASTM D1298		
Relative vapour density:	3.9			
Particle characteristics:				
Particle size:	N.A.			

9.2. Other information

Properties	Value	Method:	Notes
Viscosity:	< 7 mm²/s (40°C)		

Volatile Organic compounds - VOCs = 733 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

```
HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS
Acute toxicity:
      Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
      Test: LD50 - Route: Skin - Species: Rabbit > 2800 mg/kg - Notes: 24h
      Test: LC50 - Route: Inhalation Vapour - Species: Rat > 23300 mg/m3 - Duration: 4h
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
Acute toxicity:
      Test: LD50 - Route: Oral - Species: Rat = 4570 mg/kg
      Test: LC50 - Route: Inhalation - Species: Rat = 20 mg/l - Duration: 8h
      Test: LC50 - Route: Inhalation Vapour - Species: Rat > 25000 mg/m3 - Duration: 6 hours
      Test: LD50 - Route: Skin - Species: Rabbit = 12.800 mg/kg
Reproductive toxicity:
      Test: NOAEL - Route: Oral - Species: Rat = 500 mg/kg
STOT-repeated exposure:
      Test: NOAEL - Route: Inhalation - Species: Rat = 1.3 mg/l
      Test: NOAEL - Route: Inhalation Vapour - Species: Rat (Male, female) = 12.5 mg/l
cyclohexane - CAS: 110-82-7
Acute toxicity:
      Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg
      Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
      Test: LC50 - Route: Inhalation Vapour - Species: Rat > 19.1 mg/l - Duration: 4h
n-hexane - CAS: 110-54-3
Acute toxicity:
      Test: LC50 - Route: Inhalation - Species: Rat > 23.3 mg/l - Duration: 4h
      Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
      Test: LD50 - Route: Skin - Species: Rabbit > 2800 mg/kg
```

If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:

Acute toxicity;

Skin corrosion/irritation;

Serious eye damage/irritation;

Respiratory or skin sensitisation;

Germ cell mutagenicity;

Carcinogenicity;

Reproductive toxicity;

STOT-single exposure;

STOT-repeated exposure;

Aspiration hazard.

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

Other toxicological information:

propan-2-ol; isopropyl alcohol; isopropanol

Severe eye damage/irritation:

Irritating to eyes

Foetal development:

Toxic effects on foetal development at doses that produce effects in mothers.

No teratogenic effects, NOAEL: 400 mg/kg Maternal no-effect concentration 400 mg/kg (rat)

Absence of toxic effects on foetal development. NOAEL: > 480 mg/kg. Maternal No-effect

Concentration: 240 mg/kg (rabbit)

Inhalation:

Irritating to eyes and respiratory tract (vapour, 1.0 mg/l)

-

cyclohexane

Inhalation:

Avoid inhalation of vapours: may cause lung inflammation.

Respiratory irritation:

Coughing, mucus production and shortness of breath

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS

a) Aquatic acute toxicity:

Endpoint: EL50

- Species: Algae > 10 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

Endpoint: EL50

- Species: Daphnia > 4.6 mg/l - Duration h: 48

Endpoint: LL50

- Species: Fish > 3 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: DSEO-R (NOELR) - Species: Algae = 6.3 mg/l - Duration h: 72 - Notes:

(Pseudokirchneriella subcapitata - biomass - OECD 201)

b) Aquatic chronic toxicity:

Endpoint: DSEO-R (NOELR) - Species: Daphnia = 1 mg/l - Duration h: 504 - Notes: OECD 211

Endpoint: DSEO-R (NOELR) - Species: Fish = 0.57 mg/l - Duration h: 672 - Notes: Oncorhynchus

mykiss -QSAR Petrotox

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 48 - Notes: Leuciscus melanotus

Endpoint: LC50 - Species: Fish = 9640 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: LC50 - Species: Daphnia > 10.000 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: NOAEC - Species: Algae = 1800 mg/l - Duration h: 84 - Notes: Algues vertes / Green algae

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 100 mg/l - Duration h: 72 - Notes: Pseudokirchneriella

```
subcapitata
c) Bacteria toxicity:
      Species: bacteria = 1.050 mg/I
cyclohexane - CAS: 110-82-7
a) Aquatic acute toxicity:
      Endpoint: EC50 - Species: Aquatic invertebrates > 10 mg/l - Notes: Daphnia magna
      Endpoint: EC50 - Species: Aquatic invertebrates < 100 mg/l - Notes: Daphnia magna
      Endpoint: EL50
      - Species: Daphnia = 3 mg/l - Duration h: 48 - Notes: Daphnia magna
      Endpoint: LC50 - Species: Fish = 4.5 mg/l - Duration h: 48 - Notes: Fathead Minnow
      Endpoint: LL50
      - Species: Fish > 13.4 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss
      Endpoint: EL50
      - Species: Algae > 10 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata
      Endpoint: EC50 - Species: Aquatic plants = 9.317 mg/kg/d - Duration h: 36 - Notes: Selenastrum
      capricornutum
      Endpoint: DSEO-R (NOELR) - Species: Algae = 10 mg/l - Duration h: 72 - Notes:
      Pseudokirchneriella subcapitata
b) Aquatic chronic toxicity:
      Endpoint: EL50
      - Species: Aquatic invertebrates = 1.6 mg/l - Duration h: 504 - Notes: Daphnia magna
      Endpoint: LOEC
      - Species: Aquatic invertebrates = 0.32 mg/l - Duration h: 504 - Notes: Daphnia magna
      Endpoint: NOEC - Species: Aquatic invertebrates = 0.17 mg/l - Duration h: 504 - Notes: Daphnia
      magna
      Endpoint: DSEO-R (NOELR) - Species: Daphnia = 1 mg/l - Duration h: 504 - Notes: Daphnia
      magna
n-hexane - CAS: 110-54-3
a) Aquatic acute toxicity:
      Endpoint: EL50
      - Species: Daphnia = 3 mg/l
      Endpoint: EL50
      - Species: Algae > 10 mg/l - Notes: Pseudokirchneriella subcapitata
      Endpoint: LL50
      - Species: Fish > 13.4 mg/l - Notes: Oncorhynchus mykiss
      Endpoint: DSEO-R (NOELR) - Species: Algae = 10 mg/l - Duration h: 72 - Notes:
      Pseudokirchneriella subcapitata
b) Aquatic chronic toxicity:
      Endpoint: NOEC - Species: Daphnia = 0.17 mg/l - Duration h: 504
      Endpoint: LOEC
      - Species: Daphnia = 0.32 mg/l - Duration h: 504
12.2. Persistence and degradability
HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS
      Biodegradability: Readily biodegradable - Duration: 28 days - %: 98
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
      Biodegradability: Readily biodegradable - Duration: 5 days - %: 53 - Notes: Aerobie, activated
```

P20000 - version 7 Page 11 / 17

sludge

Biodegradability: Oxidizes rapidly by photochemical reactions in air.

Biodegradability: Photodegradation (in air) - overall half-life time - Test: Degradation by OH

radicals: Direct photolysis - Duration: 33 hours

cyclohexane - CAS: 110-82-7

Biodegradability: Biodegradability rate - Duration: 28 days - %: 9 Biodegradability: Manometer Breathing - Duration: 28 days - %: 77

n-hexane - CAS: 110-54-3

Biodegradability: Biodegradability rate - Duration: 28 days - %: 98

12.3. Bioaccumulative potential

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Estimated not significantly bioaccumulative.

Log Pow <=4

Log Kow 0.05 - Notes: 25°C

cyclohexane - CAS: 110-82-7

Log Kow 3.44

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

14 06 03* Other solvents and solvent mixtures

SECTION 14: Transport information





14.1. UN number or ID number

 ADR-UN Number:
 1993

 IATA-UN Number:
 1993

 IMDG-UN Number:
 1993

14.2. UN proper shipping name

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7-C9,

N-ALKANES, ISOALKANES, CYCLICS, propan-2-ol; isopropyl

alcohol; isopropanol)

IATA-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7-C9,

N-ALKANES, ISOALKANES, CYCLICS, propan-2-ol; isopropyl alcohol; isopropanol)

IMDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7-C9,

N-ALKANES, ISOALKANES, CYCLICS, propan-2-ol; isopropyl

alcohol; isopropanol)

14.3. Transport hazard class(es)

ADR-Class: 3

ADR - Hazard identification number: 33

IATA-Class: 3
IATA-Label: 3
IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

14.5. Environmental hazards

ADR-Enviromental Pollutant: Yes IMDG-Marine pollutant: Yes

Most important toxic component: HYDROCARBONS, C7-C9, N-ALKANES,

ISOALKANES, CYCLICS

IMDG-EmS: F-E , S-E

14.6. Special precautions for user

ADR-Subsidiary hazards:

ADR-S.P.: 274 601 640C

ADR-Transport category (Tunnel restriction code): 2 (D/E)

IATA-Passenger Aircraft: 353
IATA-Subsidiary hazards: IATA-Cargo Aircraft: 364
IATA-S.P.: A3
IATA-ERG: 3H
IMDG-Subsidiary hazards: -

IMDG-Stowage and handling: Category B

IMDG-Segregation: -

Q.L.: 1L Q.E.: E2

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

```
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
```

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 57

Restriction 75

Listed or in compliance with the following international inventories:

N.A.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS (CAS: 64742-49-0)

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

HYSO 99

aliphatic hydrocarbons >= 30%

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P5c, E2

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1

	Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
--	-------------------	--------	--

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
STOT SE 3, H336	Calculation method
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality: this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods.INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STE: Short-term exposure.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

STOT SE: May cause drowsiness or dizziness

TLV: Threshold Limiting Value.
TWA: Time-weighted average

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.