

## TEROSON PV 3046

April 2021

### PRODUCT DESCRIPTION

<b>Technology</b>	PVC Plastisol
<b>Product Type</b>	Seam Sealer Solvent Free Heat Curing

TEROSON PV 3046 is a solvent free seam sealant that can be cured at temperatures of minimum 140°C (effective metal temperature) for 10 minutes. The material can be coated with many usual primer and top coat paints without adverse effects on the surface.

#### Application Areas:

TEROSON PV 3046 serves as a seam sealant between metal sheet butt and overlap joints (interior / exterior seams) on vehicle bodies. The material is applied to electro-dip steel sheets.

### TECHNICAL DATA

Colour	light ivory RAL 1015
Density	approx. 1.3 g/cm <sup>3</sup>
Consistency	pasty
Solids (2 h / 120°C)	approx. 98%
<u>Rheological characteristics:</u>	
Equipment	MCR 301
Measuring system	Z 3 (25°C)
Viscosity 25°C	3.9 to 4.3 Pa.s
Yield Point 25°C	380 to 420 Pa
Sag resistance	< =5 mm
Particle size	< 100 µm
<u>Corrosion resistance:</u>	
salt spray test (DIN 50021) (35°C, salt solution 5%, 480h)	no under-rusting, no loss of adhesion
constant condensation (based on DIN 50017-KK)	no under-rusting, no loss of adhesion
Ageing resistance (120h, 80°C)	non-brittle / no adhesion strength loss
<u>Behaviour in the cold:</u>	
Storage	8 hrs -20°C
Mandrel bending test	70 mm Ø
Adhesion	good adhesion to substrate surface (cathodic EC)
Paintability/ Paint compability	good lamination with usual filler and top coat paints
Over backing	no cracks, no loss of adhesion
Baking conditions	50 min. 165°C + 30 min. 160°C + 90 min. 135°C

#### Mechanical properties:

Tensile strength (DIN 53504)	min. 2.4 MPa
Elongation at break (DIN 53504)	min. 180 %
In service temperature range	-30 to 80 °C

### DIRECTIONS FOR USE

#### Preliminary Statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

#### Application:

TEROSON PV 3046 is applied by high pressure pumps with a follower plate having compression ratio from 48:1 to 80:1 or with flow guns with a compression ratio of 12:1 to 24:1 (nozzle diameter 0.3 to 3.0 mm). The material is homogeneous and contains no lumps or abrasive fillers. Robotic spraying application is possible.

#### Classification:

Please refer to the corresponding **Material Safety Data Sheets** for details on:

**Hazards identification**  
**Transport information**  
**Regulatory information**

#### Storage:

Recommended transport temperature, °C	15 to 30
Recommended storage temperature, °C	15 to 30
Shelf- life, months	3

## ADDITIONAL INFORMATION

### Disclaimer

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.2

---

For further information please see [www.henkel.com/industrial](http://www.henkel.com/industrial), or contact your local sales representative.

