

TEROSON SB 450

April 2014

PRODUCT DESCRIPTION

TEROSON SB 450 provides the following product characteristics:

Technology	Cleaner
Product Type	Alcoholic solution
Components	One-component
Application	Surface Treatment
Appearance	Colourless, Clear
Consistency	Thin fluid
Odor	Alcoholic

TEROSON SB 450 is an alcoholic solution designed for the cleaning of difficult to bond surfaces. It contains active ingredients that improve the adhesion of elastic adhesives and sealants on surfaces on which adhesion is usually difficult to achieve.

Application Areas:

TEROSON SB 450 is used for cleaning and if necessary to improve adhesion of elastic adhesives and sealants on metals, plastics and coated surfaces.

TECHNICAL DATA

Density, g/cm ³ :	approx. 0.8
Flash-off time, min:	10 to 60
* ISO 291 standard climate:	23°C, 50% relative air humidity

DIRECTIONS OF USE

Preliminary Statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application:

A thorough cleaning of the substrates is essential to achieve a serviceable adhesion on metals, plastics and coated surfaces. TEROSON SB 450 is applied finely and evenly by a suitable clean cloth or paper. The cloth or paper should be changed by apparent contamination. In order to control whether TEROSON SB 450 covers the entire substrate, the product contains a UV indicator. It is particularly well visible under a UV lamp with a wave length of approx. 380 nm. After withdrawal of the product, the container should be closed tightly to prevent access of humidity. By exposure to water/humidity TEROSON SB 450 loses its activity and becomes cloudy.

Cleaning:

Splashes should be removed at once by an absorbing material.

Storage:

Shelf life:	
Frost-Sensitive	No
Recommended storage temperature, °C	10 to 25
Shelf-life (in unopened original packaging), 12 months	

ADDITIONAL INFORMATION

Disclaimer:

Note:
The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The

Henkel AG & Co.KGaA



40191 Düsseldorf, Germany
Phone: +49-211-797-0
www.henkel.com

product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.0

