

## TEROSON WX 400

Known as Terotex-HV 400 October 2013

### PRODUCT DESCRIPTION

TEROSON WX 400 provides the following product characteristics:

<b>Application</b>	Anticorrosive Agent
<b>Technology</b>	Anticorrosive Agent for cavity conservation with high solids
<b>Basis</b>	Waxes, Polymers and Anticorrosive additives

TEROSON WX 400 is a solvent containing anticorrosive agent for cavity conservation with high solids, based on waxes, polymers and anticorrosive additives. The material is a thixotropic solution which can be well atomized. This leads to optimum protection even of those areas which are difficult to reach and also between narrow sheet metal tolerances. TEROSON WX 400 infiltrates and displaces humidity. The product contains a high content of corrosion inhibitors.

TEROSON WX 400 atomizes to a fine fog during spraying, has excellent penetration characteristics, penetrates well into the gaps to be protected (e.g. welding seams), but does not run off significantly from lower seams. The material may also be applied at temperatures starting at 10°C, but penetration is improved when product and car body have normal room temperature.

After complete drying TEROSON WX 400 forms a plastic, water-repellent film with a beige transparent colour.

#### Application Areas:

TEROSON WX 400 is primarily used in garages for spraying cavities in motor vehicle bodies in addition to the existing cavity conservation applied to new cars, for follow-up treatment after 2 - 3 years and after an accident damage repair.

#### TECHNICAL DATA

(Typical Test Results)

Colour	beige transparent
Odour	characteristic odour
Consistency	thixotropic
Density	approx. 0.96 g/cm <sup>3</sup>
Solid	approx. 60 %
Dripping Temperature of the solids (DIN 51801)	approx. 150 °C
Sag resistance	min. 100 µm
Penetration	>55 mm; gap 0,1 mm
Paint compatibility	no permanent changes of the top-coat
Removability after 24 hrs	dried material can easily be removed
Behaviour in the repair paint oven (1.5 hrs at 90°C)	no running off

Behaviour in the cold	no cracks
Layer thickness	40 µm
Storage	2 d -40 °C
Mandrel	70 mm Ø
Corrosion resistance	no corrosion
salt spray test to DIN 50021 (35°C, salt solution 5%, 240 hrs)	
Application temperature	15 to 25 °C
In service temperature	-40 to 90 °C
Short exposure (up to 1 h)	120 °C

### PRELIMINARY STATEMENT

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

#### Application:

##### Processing with the can:

TEROSON WX 400 can be applied, with the HV Cup Pistol with the respective probes. Application pressure for the HV Cup Pistol is 2 - 4 bar. Do not spray onto rubber parts!

After a longer storage period as well as at temperatures below 10°C the material builds up a certain thixotropy. However, this is broken during spraying procedure - the material, therefore, exhibits its normal characteristics after application.

Depending on the cavity to be treated the drying period can last up to several days; assure sufficient ventilation during drying.

#### Cleaning

TEROSON WX 400 drips can easily be wiped off. For cleaning dried material TEROSON VR 10 is suitable; larger areas can be steam jet cleaned. Contamination on painted areas should be removed immediately.

#### Storage:

Frost sensitive	yes
Recommended storage temperature	15 to 25 °C; thickens at lower temperatures and must be brought to application temperature prior to use
Shelf life	24 months



**Disclaimer**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.3

