

Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: DAMICOAT 2407-02 RED

· Article number: 352929

· Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

- · Application of the substance / the mixture No further relevant information available.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Von Roll Italia S.r.l. Via Rigolfo, 73 10028 TROFARELLO (TO) ITALY
- · Further information obtainable from: Giovanni Rocco info.italy@vonroll.com

· Emergency telephone number:

Tel: +390116493111 (h. 8/12 ÷ 13/17 italian time)

Fax: +390116493112

National Poisons Information Service (Birmingham Unit) City Hospital

Dudley Rd - Birmingham Tel: 844 892 0111 mail@npis.org"

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



) flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 1)

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

602 GHS07

HS07 GHS0

· Signal word Danger

· Hazard-determining components of labelling:

xylene

ethylbenzene

REACTION MIXTURE OF ETHYLBENZENE AND XYLENES

Idrocarburi, C9, aromatici

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH208 Contains Acido neodecanoico, sale di cobalto, cobalt(II) 2-ethylhexanoate, Diidrossido di cobalto, 2-n-butyl-benzo[d] isothiazol-3-one. May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

		(Contd. of page
Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥25-<40%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	>3.5-<7.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Idrocarburi, C9, aromatici Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335; STOT SE 3, H336	≥2.5-<4.75%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-XXXX	REACTION MIXTURE OF ETHYLBENZENE AND	≤4.5%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	>2-2.1%
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33-XXXX	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	>0.7-<1.2%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<1.1%
CAS: 27253-31-2 EINECS: 248-373-0	Acido neodecanoico, sale di cobalto Repr. 2, H361f; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	>0.4-<0.5%
CAS: 22464-99-9	"2-ethylhexanoic acid, zirconium salt" \$ Repr. 2, H361d	>0.1-<0.4%
CAS: 136-52-7 EINECS: 205-250-6	cobalt(II) 2-ethylhexanoate Resp. Sens. 1, H334; Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	>0.1-<0.25%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-211947310-51	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	>0-<0.3%
CAS: 21041-93-0 EINECS: 244-166-4	Diidrossido di cobalto Resp. Sens. 1, H334; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319; Skin Sens. 1, H317	<i>≥</i> 0.1–<0.2%
CAS: 4299-07-4 ELINCS: 420-590-7 Reg.nr.: 01-0000016721-74	2-n-butyl-benzo[d]isothiazol-3-one Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≤0.1%



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 3)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 4)

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:

108-88-3 toluene

Sk

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

CONSERVARE IN AMBIENTE FRESCO MAX 30°C - STORE IN A COOL PLACE (MAX 30°)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

Ing	redients with limit values that require monitoring at the workplace:	
133	0-20-7 xylene	
WE	L Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
100	-41-4 ethylbenzene	
WE	L Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk	
71-	36-3 butan-1-ol	
WE	L Short-term value: 154 mg/m³, 50 ppm Sk	
123	-86-4 n-butyl acetate	
WE	L Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
136	-52-7 cobalt(II) 2-ethylhexanoate	

(Contd. on page 6)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

			(Contd. of	pa
DNELs				
		F ETHYLBENZENE AND XYLE		
Oral	Acute - inhalatio	on, systemic effects - Consumer	260 mg/m³ (human)	
	Long-term - ora	l, systemic effects - Consumers	12.5 mg/kg (human)	
Inhalative	Acute - inhalati	on, local effects - Consumer	260 mg/m³ (human)	
	Long-term - inhalation, systemic effects - Consum.		$65.3 \text{ mg/m}^3 \text{ (human)}$	
<i>64742-48-</i>		oleum), hydrotreated heavy		
Oral	Long-term - ora	l, systemic effects - Consumers	125 mg/kg (human)	
Dermal	Long-term – dermal, systemic effects - Workers		208 mg/kg (human)	
	Long-term - dermal, systemic effects - Consumers		125 mg/kg (human)	
Inhalative	Long-term – inh	alation, systemic effects - Workers	871 mg/m^3 (human)	
	Long-term - inhalation, systemic effects - Consum.		185 mg/m³ (human)	
123-86-4 n	ı-butyl acetate			
Oral	Acute- oral, syst	temic effect - Wworkers	2 mg/kg (human)	
	Acute-oral, syst	emic effects - Consumers	2 mg/kg (human)	
Dermal	Acute - dermal,	systemic effect - Workers	11 mg/kg (human)	
	Long-term - dermal, systemic effects - Consumers		6 mg/kg (human)	
	Acute - dermal,	systemic effect - Consumers	6 mg/kg (human)	
Inhalative	Acute – inhalati	on, local effects - Workers	600 mg/m³ (human)	
	Long-term – inhalation, systemic effects - Workers		11 mg/m^3 (human)	
	Long-term - inhalation, local effect - Workers		300 mg/m^3 (human)	
	Acute - inhalation, local effects - Consumer		$35.7 \text{ mg/m}^3 (/)$	
			300 mg/m³ (human)	
PNECs				
REACTIO	N MIXTURE O	F ETHYLBENZENE AND XYLE	NES	
Fresh Wate	er	0.18 mg/l (/)		
Water, inte	ermittent release	0.36 mg/l (/)		
Marine water		0.0981 mg/l (/)		
Freshwater sediments		0.981 mg/kg (/)		
Marine water sediments		0.0981 mg/kg (/)		
STP Microorganisms		35.6 mg/l (/)		
123-86-4 n	ı-butyl acetate			
Fresh Water		0.18 mg/l (/)		
Water, intermittent release				
Marine water		0.018 mg/l (/)		
Freshwate	r sediments	0.981 mg/kg (/)		
Marine wa	ter sediments	0.0981 mg/kg (/)		
CTD 14:	organisms	35.6 mg/l (/)		



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 6)

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

(Contd. on page 8)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

	(Contd. of page
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Undetermined.
Flash point:	>23-<60 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	6.7–8.2 hPa
Density at 20 °C:	$1.1-1.2 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	25.3-<47.6 %
VOC (EC)	25.29-<47.61 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 9)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 8)

· Hazardous decomposition products: No dangerous decomposition products known.

Informati		cological affects	
		c ological effects on available data, the classification criteria are not met.	
		evant for classification:	
		Estimates)	
Oral	LD50	37,619–38,072 mg/kg (rat)	
Dermal	LD50	>4,443–7,520 mg/kg	
Inhalative	LC50/4 h	>22.6–41.4 mg/l	
1330-20-7	xylene		
	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	11 mg/l (ATE)	
100-41-4 е			
	LD50	3,500 mg/kg (rat)	_
Dermal	LD50	17,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	11 mg/l (ATE)	
REACTIO	N MIXTU	VRE OF ETHYLBENZENE AND XYLENES	
Dermal	LD50	1,100 mg/kg (ATE)	
Inhalative	LC50/4 h	11 mg/l (ATE)	
71-36-3 bi	ıtan-1-ol		
Oral	LD50	790 mg/kg (rat)	
Dermal	LD50	3,400 mg/kg (rabbit)	
Inhalative	LC50/4 h	8,000 mg/l (rat)	
64742-48-	9 Naphtha	(petroleum), hydrotreated heavy	
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rab)	
123-86-4 1	ı-butyl ace	tate	
Oral	LD50	13,100 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
		>21 mg/l (rat)	
27253-31-		eodecanoico, sale di cobalto	
Oral	LD50	500 mg/kg (ATE)	
108-88-3 t	oluene		
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,320 mg/l (mouse)	



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 9)

21041-93-0 Diidrossido di cobalto

 Oral
 LD50
 500 mg/kg (ATE)

 Inhalative
 LC50/4 h
 1.5 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. This disposal considerations refer to intact product without external contaminations.

(Contd. on page 11)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 10)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

UN-Number	THUSE
ADR, IMDG, IATA	UN1866
UN proper shipping name	
ADR	UN1866 RESIN SOLUTION
IMDG	RESIN SOLUTION
IATA	Resin solution
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
Transport in bulk according to Annex II of Marp	pol
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 11)

· UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department.
- · Contact: -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 13)



Printing date 29.03.2022 Version number 3 Revision: 29.03.2022

Trade name: DAMICOAT 2407-02 RED

(Contd. of page 12)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation — Category 1
Eye Irrit. 2: Serious eye damage/eye irritation — Category 2
Pean Son, 1: Peanington constitution — Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB